

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : Wirkstoff für Zinkstaub L
Material number : 088176VA0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company :

Telephone :
Telefax :
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Flammable liquids, Category 2, H225
Skin corrosion/irritation, Category 3, H316
Serious eye damage/eye irritation, Category 2A, H319

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

Specific target organ toxicity - single exposure, Category 3,
 Respiratory system, Central nervous system, H335H336
 Specific target organ toxicity - repeated exposure, Category 2,
 H373
 Aspiration hazard, Category 1, H304
 Short-term (acute) aquatic hazard, Category 1, H400
 Long-term (chronic) aquatic hazard, Category 2, H411

GHS-Labeling

Symbol(s)



Signal word

: Danger

Hazard statements

: H225: Highly flammable liquid and vapour.
 H304: May be fatal if swallowed and enters airways.
 H316: Causes mild skin irritation.
 H319: Causes serious eye irritation.
 H335: May cause respiratory irritation.
 H336: May cause drowsiness or dizziness.
 H373: May cause damage to organs through prolonged or
 repeated exposure.
 H400: Very toxic to aquatic life.
 H411: Toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open
 flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P280 Wear protective gloves/ protective clothing/ eye
 protection/ face protection/ hearing protection.
Response:
 P301 + P310 IF SWALLOWED: Immediately call a POISON
 CENTER/doctor.
 P314 Get medical advice/ attention if you feel unwell.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

P331 Do NOT induce vomiting.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification	CAS-No.
acetone	67-64-1
Solvent naphtha (petroleum), light arom.	64742-95-6
xylene	1330-20-7
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1

SECTION 3: Composition/information on ingredients

Substance name : ZINKSTAUB-SPRAY/L WS IBC

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
acetone	67-64-1 200-662-2	Flam. Liq.;2;H225 Acute Tox.;5;H303 Acute Tox.;5;H313 Eye Irrit.;2A;H319 STOT SE;3;H336	20 - 25
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	10 - 20

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

Solvent naphtha (petroleum), light arom.	64742-95-6	Flam. Liq.;3;H226 Acute Tox.;5;H303 Acute Tox.;5;H313 STOT SE;3;H335, H336 Asp. Tox.;1;H304 Aquatic Chronic;2;H411	10 - 20
xylene	1330-20-7 215-535-7	Flam. Liq.;3;H226 Acute Tox.;4;H332 ;2;H315 ;2A;H319 STOT SE;3;H335 STOT RE;2;H373 Asp. Tox.;1;H304	1 - 10
naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha	64742-82-1 265-185-4	Flam. Liq.;3;H226 STOT SE;3;H336 STOT RE;1;H372 Asp. Tox.;1;H304 Aquatic Chronic;2;H411	2,5 - 10
zinc oxide	1314-13-2 215-222-5	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	1 - 2,5
Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates	68308-64-5 939-607-9	Acute Tox.;4;H302 Acute Tox.;3;H311 ;1C;H314 ;1;H318 Aquatic Acute;1;H400	0,25 - 1

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

		Aquatic Chronic;1;H410	
--	--	---------------------------	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, ABC powder, Foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

SECTION 7: Handling and storage
7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.
- No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

- Further information on storage conditions : Protect from humidity and water.
- Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
acetone	67-64-1	TWA	500 ppm 1 210 mg/m ³	2000-06-16	2000/39/EC
Further information		Indicative			
acetone	67-64-1	AGW	500 ppm 1 200 mg/m ³	2015-03-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(l)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a			

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

		limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).				
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).				
Solvent naphtha (petroleum), light arom.	64742-95-6	AGW	100 mg/m ³	2009-02-16	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixturesCommission for dangerous substancesSee also No. 2.9 of the TRGS 900				
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000-06-16	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skinIndicative				
xylene	1330-20-7	STEL	100 ppm 442 mg/m ³	2000-06-16	2000/39/EC

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

Further information		Identifies the possibility of significant uptake through the skin Indicative			
xylene	1330-20-7	AGW	100 ppm 440 mg/m ³	2010-08-04	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)Skin absorption			

8.2 Exposure controls
Personal protective equipment

- Eye protection : Goggles
- : Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

Recommended preventive skin protection
 Skin should be washed after contact.
 The suitability for a specific workplace should be discussed
 with the producers of the protective gloves.

- : The suitability for a specific workplace should be discussed
 with the producers of the protective gloves.
- Skin and body protection : Choose body protection according to the amount and
 concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration
 requires.
- : In the case of vapour formation use a respirator with an
 approved filter.

Environmental exposure controls

- General advice :
 - : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform
 respective authorities.
- Water : The product should not be allowed to enter drains, water
 courses or the soil.
- :

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: No data available
Odour	: characteristic
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 55 °C
Flash point	: -19 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: ca. 1,28 g/cm ³
Solubility(ies)	
Water solubility	: immiscible
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: 11 - 13 s at 20 °C Cross section: 4 mm Method: DIN 53211

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

Bases
Oxidizing agents**10.6 Hazardous decomposition products**

Hazardous decomposition products : No data available

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****acetone :**

Acute oral toxicity : LD50 Rabbit: 4 700 - 5 800 mg/kg

Mouse: 3 000 mg/kg

Rat: 9 800 mg/kg

Acute inhalation toxicity : LC50 Rat: 76 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

Acute dermal toxicity : LD50 Rabbit: > 2 000 mg/kg

zinc powder — zinc dust (stabilised) :

Acute oral toxicity : Rat: > 2 000 mg/kg

Solvent naphtha (petroleum), light arom. :

Acute oral toxicity : LD50 Rat: 3 492 mg/kg

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

xylene :

Acute inhalation toxicity : The component/mixture is moderately toxic after short term inhalation.

naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha :

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates :

Acute oral toxicity : The component/mixture is moderately toxic after single ingestion.

Acute dermal toxicity : The component/mixture is toxic after single contact with skin.

Skin corrosion/irritation**Product**

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation**Product**

Eye irritation

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

Further information

Product

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

acetone (67-64-1) :

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21 600 mg/l

zinc (7440-66-6) :

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

Solvent naphtha (petroleum), light arom. (64742-95-6) :

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1) :

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

Quaternary ammonium compounds, coco alkylethylidimethyl, Et sulfates (68308-64-5) :

M-Factor : 10

Ecotoxicology Assessment

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life., Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

courses or the soil.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

SECTION 14: Transport information**14.1 UN number**

ADR : 1263
TDG : 1263
CFR : 1263
IMDG : 1263
IATA : 1263

14.2 Proper shipping name

ADR : PAINT
TDG : PAINT
CFR : PAINT
IMDG : PAINT
(,Zinc powder, stabilized)
IATA : PAINT

14.3 Transport hazard class

ADR : 3
TDG : 3

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

CFR : 3**IMDG** : 3**IATA** : 3**14.4 Packing group****ADR**

Packaging group : II

Classification Code : F1

Hazard Identification Number : 33

Labels : 3

Tunnel restriction code : (D/E)

TDG

Packaging group : II

Labels : 3

CFR

Packaging group : II

Labels : 3

IMDG

Packaging group : II

Labels : 3

EmS Number : F-E, S-E

IATAPacking instruction (cargo
aircraft) : 364Packing instruction
(passenger aircraft) : 353

Packing instruction (LQ) : Y341

Packaging group : II

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

Labels : 3

14.5 Environmental hazards**IMDG** : Marine pollutant**ADR** : Environmentally hazardous**14.6 Special precautions for user****14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Prohibition/Restriction**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Prohibition/Restriction

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Prohibition/Restriction

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

15.2 Chemical safety assessment

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020

No data available

SECTION 16: Other information**Full text of H-Statements**

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H303	: May be harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H311	: Toxic in contact with skin.
H313	: May be harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H316	: Causes mild skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Wirkstoff für Zinkstaub L

Version 2.1

Revision Date 08.01.2020

Print Date 07.08.2020
