

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## STAPA DL REFLEXAL 212/80 Aluminium Paste

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : STAPA DL REFLEXAL 212/80 Aluminium Paste  
Material number : 050900GD0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company :  
  
Telephone :  
Telefax :  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

#### 1.4 Emergency telephone number

**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

---

### SECTION 2: Hazards identification

**GHS Classification**

Not a dangerous substance according to GHS.

**GHS-Labeling**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA DL REFLEXAL 212/80 Aluminium Paste

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

### Hazardous components which must be listed on the label

### Other hazards which do not result in classification

Combustible Solids

## SECTION 3: Composition/information on ingredients

Substance name : STAPA\* DL Resist 2156/80

Substance No. :

### Hazardous components

| Chemical name                 | CAS-No.<br>EINECS-No.  | Classification and<br>labelling | Concentration[%] |
|-------------------------------|------------------------|---------------------------------|------------------|
| aluminium powder (stabilised) | 7429-90-5<br>231-072-3 | Flam. Sol.;1;H228               | 50 - 100         |

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Move the victim to fresh air.  
Do not leave the victim unattended.

No hazards which require special first aid measures.

If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

**STAPA DL REFLEXAL 212/80 Aluminium Paste**

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media : Dry sand, Special powder against metal fire
- Unsuitable extinguishing media : Water, Foam, ABC powder, Carbon dioxide (CO<sub>2</sub>)

**5.2 Special hazards arising from the substance or mixture**

This information is not available.

**5.3 Advice for firefighters**

- Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

**STAPA DL REFLEXAL 212/80 Aluminium Paste**

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Avoid dust formation.

**6.2 Environmental precautions**

This information is not available.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
  
Sweep up and shovel.  
Do not flush with water.  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA DL REFLEXAL 212/80 Aluminium Paste

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

This information is not available.

**STAPA DL REFLEXAL 212/80 Aluminium Paste**

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

**SECTION 8: Exposure controls/personal protection**
**8.1 Control parameters**
**Germany:**

| Components                              | CAS-No.   | Value type<br>(Form of exposure)  | Control parameters     | Update     | Basis       |
|---|-----------|---|------------------------|------------|-------------|
| aluminium powder (stabilised)           | 7429-90-5 | AGW (Inhalable fraction)  | 10 mg/m <sup>3</sup>   | 2014-04-02 | DE TRGS 900 |
| Peak-limit: excursion factor (category) |           | 2;(II)  |                        |            |             |
| Further information                     |           | Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission). |                        |            |             |
| aluminium powder (stabilised)           | 7429-90-5 | AGW (Alveolate fraction)  | 1,25 mg/m <sup>3</sup> | 2014-04-02 | DE TRGS 900 |
| Peak-limit: excursion factor (category) |           | 2;(II)  |                        |            |             |
| Further information                     |           | Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission). |                        |            |             |

**United States of America (USA):**

| Components                    | CAS-No.   | Value type<br>(Form of exposure) | Control parameters                  | Update     | Basis |
|-------------------------------|-----------|----------------------------------|-------------------------------------|------------|-------|
| aluminium powder (stabilised) | 7429-90-5 | TWA (total dust)                 | 50 Million particles per cubic foot | 2012-07-01 |       |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable)                 | 5 mg/m <sup>3</sup>                 | 2013-10-08 |       |
| aluminium                     | 7429-90-5 | TWA (total dust)                 | 15 mg/m <sup>3</sup>                | 2012-07-01 |       |

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA DL REFLEXAL 212/80 Aluminium Paste

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

|                               |           |                                |                                     |            |  |
|-------------------------------|-----------|--------------------------------|-------------------------------------|------------|--|
| powder (stabilised)           |           |                                |                                     |            |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (total)                    | 10 mg/m3                            | 2013-10-08 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable fraction)      | 5 mg/m3                             | 2012-07-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable fraction)      | 15 Million particles per cubic foot | 2012-07-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | PEL (Total dust)               | 10 mg/m3                            | 2014-11-26 |  |
| aluminium powder (stabilised) | 7429-90-5 | PEL (respirable dust fraction) | 5 mg/m3                             | 2014-11-26 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable fraction)      | 1 mg/m3                             | 2008-01-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA                            | 5 mg/m3                             | 2005-09-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Total)                    | 15 mg/m3                            | 1989-01-19 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable fraction)      | 5 mg/m3                             | 1989-01-19 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (total dust)               | 15 mg/m3                            | 2011-07-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable fraction)      | 5 mg/m3                             | 2011-07-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Total dust)               | 15 mg/m3                            | 1989-01-19 |  |

**STAPA DL REFLEXAL 212/80 Aluminium Paste**

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

|                               |           |                                |                     |            |  |
|-------------------------------|-----------|--------------------------------|---------------------|------------|--|
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable dust fraction) | 5 mg/m <sup>3</sup> | 1989-01-19 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (welding fumes)            | 5 mg/m <sup>3</sup> | 2013-10-08 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (pyro powders)             | 5 mg/m <sup>3</sup> | 2013-10-08 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable fraction)      | 1 mg/m <sup>3</sup> | 2013-03-01 |  |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Fumes)                    | 5 mg/m <sup>3</sup> | 1989-01-19 |  |
| aluminium powder (stabilised) | 7429-90-5 | PEL (Welding fumes)            | 5 mg/m <sup>3</sup> | 2017-10-02 |  |
| aluminium powder (stabilised) | 7429-90-5 | PEL (Pyro powders)             | 5 mg/m <sup>3</sup> | 2017-10-02 |  |

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Safety glasses

Hand protection

Material : Solvent-resistant gloves

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).  
 The exact break through time can be obtained from the protective glove producer and this has to be observed.



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## STAPA DL REFLEXAL 212/80 Aluminium Paste

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

- Skin and body protection : Long sleeved clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.

### Environmental exposure controls

- Water : The product should not be allowed to enter drains, water courses or the soil.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : Pasty solid
- Colour : silver
- Odour : characteristic
- pH : No data available
- Freezing point : No data available

**STAPA DL REFLEXAL 212/80 Aluminium Paste**

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

|  |                      |
|--|----------------------|
| Boiling point/boiling range            | : No data available  |
| Flash point                            | : No data available  |
| Bulk density                           | : No data available  |
| Flammability (solid, gas)              | : Combustible Solids |
| Auto-flammability                      | : not auto-flammable |
| Upper explosion limit                  | : No data available  |
| Lower explosion limit                  | : No data available  |
| Vapour pressure                        | : No data available  |
| Density                                | : No data available  |
| Water solubility                       | : No data available  |
| Miscibility with water                 | : immiscible         |
| Solubility in other solvents           | : No data available  |
| Partition coefficient: n-octanol/water | : No data available  |
| Ignition temperature                   | : No data available  |
| Thermal decomposition                  | : No data available  |
| Viscosity, dynamic                     | : No data available  |
| Viscosity, kinematic                   | : No data available  |
| Flow time                              | : No data available  |
| Explosive properties                   | : Not explosive      |

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

**STAPA DL REFLEXAL 212/80 Aluminium Paste**

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.  
Contact with acids and alkalis may release hydrogen.  
Mixture reacts slowly with water resulting in evolution of hydrogen.  
Vapour/air-mixtures are explosive at intense warming.

Stable under recommended storage conditions.

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow to dry.

No data available

**10.5 Incompatible materials**

Materials to avoid : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

**10.6 Hazardous decomposition products**

Hazardous decomposition products : No data available

Other information : No data available

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

**STAPA DL REFLEXAL 212/80 Aluminium Paste**

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

---

No data available

**Skin corrosion/irritation**

No data available

**Serious eye damage/eye irritation**

No data available

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**STAPA DL REFLEXAL 212/80 Aluminium Paste**

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

---

**Further information****Product**No data available

---

**SECTION 12: Ecological information****12.1 Toxicity**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**

Additional ecological information : No data available

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**STAPA DL REFLEXAL 212/80 Aluminium Paste**

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

- Product : In accordance with local and national regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
In accordance with local and national regulations.

---

**SECTION 14: Transport information****14.1 UN number****14.2 Proper shipping name****14.3 Transport hazard class****14.4 Packing group****14.5 Environmental hazards****14.6 Special precautions for user**

Not classified as dangerous in the meaning of transport regulations.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## STAPA DL REFLEXAL 212/80 Aluminium Paste

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

#### 15.2 Chemical safety assessment

No data available

---

### SECTION 16: Other information

#### Full text of H-Statements

H228 : Flammable solid.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET



Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## STAPA DL REFLEXAL 212/80 Aluminium Paste

Version 2.1

Revision Date 06.03.2020

Print Date 07.08.2020

---