

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

HYDRO PELLETT 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : HYDRO PELLETT 1300
Material number : 024074HV0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company :

Telephone :
Telefax :
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number

NCEC:

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Skin corrosion/irritation, Category 3, H316
Short-term (acute) aquatic hazard, Category 3, H402
Long-term (chronic) aquatic hazard, Category 3, H412

HYDRO PELLETT 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

GHS-Labeling

Signal word : Warning

Hazard statements : H316: Causes mild skin irritation.
H412: Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.
Response:
P332 + P313 If skin irritation occurs: Get medical advice/
attention.
Disposal:
P501 Dispose of contents/ container to an approved waste
disposal plant.

Hazardous components which must be listed on the label
Other hazards which do not result in classification

Combustible Solids

SECTION 3: Composition/information on ingredients

Substance name : HYDRO PELLETT 1300 NEU

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	50 - 100

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

Phosphoric acid, C11-14-isoalkyl esters, C13-rich	154518-38-4 (52933-07-0)	;2;H315 ;1;H318 Aquatic Acute;2;H401 Aquatic Chronic;2;H411	3 - 10
Fatty acids, C14-18 and C16-18-unsatd.	67701-06-8 266-930-6	Acute Tox.;5;H313	1 - 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
- No hazards which require special first aid measures.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

HYDRO PELLETT 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : ABC powder, Carbon dioxide (CO₂), Water, Foam

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Contact with water liberates extremely flammable gas (hydrogen).

Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

HYDRO PELLETT 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.
Evacuate personnel to safe areas.
Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Do not use a vacuum cleaner.

Do not flush with water.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

This information is not available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Avoid dust formation. Routine housekeeping should be
instituted to ensure that dusts do not accumulate on surfaces.
Store away from heat.

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	5 mg/m ³	2013-10-08	
aluminium	7429-90-5	TWA (total dust)	15 mg/m ³	2012-07-01	

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

powder (stabilised)					
aluminium powder (stabilised)	7429-90-5	TWA (total)	10 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	PEL (Total dust)	10 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	PEL (respirable dust fraction)	5 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m3	2008-01-01	
aluminium powder (stabilised)	7429-90-5	TWA	5 mg/m3	2005-09-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total dust)	15 mg/m3	1989-01-19	

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

aluminium powder (stabilised)	7429-90-5	TWA (respirable dust fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (welding fumes)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (pyro powders)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m3	2013-03-01	
aluminium powder (stabilised)	7429-90-5	TWA (Fumes)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	PEL (Welding fumes)	5 mg/m3	2017-10-02	
aluminium powder (stabilised)	7429-90-5	PEL (Pyro powders)	5 mg/m3	2017-10-02	
2,2',2''-nitrilotriethanol	102-71-6	TWA	5 mg/m3	2013-03-01	
2,2',2''-nitrilotriethanol	102-71-6	PEL	5 mg/m3	2014-11-26	

8.2 Exposure controls
Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

Material : Protective gloves

HYDRO PELLETT 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

- Remarks :
- The suitability for a specific workplace should be discussed with the producers of the protective gloves.
 - The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
 - The exact break through time can be obtained from the protective glove producer and this has to be observed.
- :
- The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection :
- Long sleeved clothing
 - Dust impervious protective suit
 - Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection :
- Use suitable breathing protection if workplace concentration requires.
 - Breathing apparatus with filter.
 - P1 filter

Environmental exposure controls

- General advice :
- Prevent product from entering drains.
 - Prevent further leakage or spillage if safe to do so.
 - If the product contaminates rivers and lakes or drains inform respective authorities.
- Water :
- The product should not be allowed to enter drains, water courses or the soil.

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

:

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: pellets
Colour	: silver
Odour	: characteristic
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: Not applicable
Bulk density	: No data available
Flammability (solid, gas)	: Combustible Solids
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materialsMaterials to avoid : Acids
Bases
Oxidizing agents

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

Water

10.6 Hazardous decomposition products

Hazardous decomposition products : No data available

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****Fatty acids, C14-18 and C16-18-unsatd. :**

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 46 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

Skin corrosion/irritation**Product**

May cause skin irritation and/or dermatitis.

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

Serious eye damage/eye irritation**Product**

Result: No eye irritation

Product dust may be irritating to eyes, skin and respiratory system.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

Further information**Product**

No data available

SECTION 12: Ecological information**12.1 Toxicity****Components:****Phosphoric acid, C11-14-isoalkyl esters, C13-rich (154518-38-4) :**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l
Exposure time: 96 hToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 6,31 mg/l
aquatic invertebrates Exposure time: 48 hToxicity to algae : EC50 (algae): 150 mg/l
Exposure time: 72 h**12.2 Persistence and degradability**

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

HYDRO PELLETT 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
In accordance with local and national regulations.

SECTION 14: Transport information**14.1 UN number****14.2 Proper shipping name****14.3 Transport hazard class****14.4 Packing group**

HYDRO PELLET 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

14.5 Environmental hazards**14.6 Special precautions for user**

Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

15.2 Chemical safety assessment

No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

HYDRO PELLETT 1300

Version 2.0

Revision Date 07.12.2019

Print Date 06.08.2020

SECTION 16: Other information**Full text of H-Statements**

H228	: Flammable solid.
H313	: May be harmful in contact with skin.
H315	: Causes skin irritation.
H316	: Causes mild skin irritation.
H318	: Causes serious eye damage.
H401	: Toxic to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.