

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## ProFLAKE Zn 1590 MS Zinc Paste

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ProFLAKE Zn 1590 MS Zinc Paste  
Material number : 026142K30

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company :  
  
Telephone :  
Telefax :  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

#### 1.4 Emergency telephone number

**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

---

### SECTION 2: Hazards identification

#### GHS Classification

: Short-term (acute) aquatic hazard, Category 1, H400  
Long-term (chronic) aquatic hazard, Category 1, H410

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## ProFLAKE Zn 1590 MS Zinc Paste

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

### GHS-Labeling

Symbol(s)

:



Signal word

: Warning

Hazard statements

: H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**  
 P273 Avoid release to the environment.  
**Response:**  
 P391 Collect spillage.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

### Hazardous components which must be listed on the label

### Other hazards which do not result in classification

Combustible Solids

## SECTION 3: Composition/information on ingredients

Substance name : STAPA 4 ZN

Substance No. :

### Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
zinc powder — zinc dust	7440-66-6	Aquatic Acute;1;H400	50 - 100

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

(stabilised)	231-175-3	Aquatic Chronic;1;H410	
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	Flam. Liq.;4;H227 Asp. Tox.;1;H304	10 - 20

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.  
Remove from exposure, lie down.
- No hazards which require special first aid measures.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- Flush eyes with water as a precaution.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## ProFLAKE Zn 1590 MS Zinc Paste

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

### 4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : Carbon dioxide (CO<sub>2</sub>), Water

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Contact with water liberates extremely flammable gas (hydrogen).

Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Avoid dust formation.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
  
Pick up and transfer to properly labelled containers.  
Do not flush with water.  
Contain spillage, and then collect with non-combustible  
absorbent material, (e.g. sand, earth, diatomaceous earth,  
vermiculite) and place in container for disposal according to  
local / national regulations (see section 13).  
  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Avoid creating dust. Routine housekeeping should be

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

instituted to ensure that dusts do not accumulate on surfaces.

For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

Normal measures for preventive fire protection.

Hygiene measures : Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.

Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

This information is not available.

**SECTION 8: Exposure controls/personal protection**
**8.1 Control parameters**
**Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m <sup>3</sup>	2017-11-30	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## ProFLAKE Zn 1590 MS Zinc Paste

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

Further information	Group exposure limit for hydrocarbon solvent mixtures Commission for dangerous substances See also No. 2.9 of the TRGS 900
---------------------	--

### United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (total dust)	15 mg/m <sup>3</sup>	2012-07-01	
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2012-07-01	
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
zinc powder — zinc dust (stabilised)	7440-66-6	PEL (Total dust)	10 mg/m <sup>3</sup>	2014-11-26	
zinc powder — zinc dust (stabilised)	7440-66-6	PEL (respirable dust fraction)	5 mg/m <sup>3</sup>	2014-11-26	
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	64742-48-9	TWA	500 ppm 2 000 mg/m <sup>3</sup>	2007-01-01	
Naphtha (petroleum), hydrotreated heavy; Low	64742-48-9	TWA	400 ppm 1 600 mg/m <sup>3</sup>	1989-01-19	



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## ProFLAKE Zn 1590 MS Zinc Paste

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

boiling point					
hydrogen treated naphtha					

### United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (total dust)	15 mg/m <sup>3</sup>	2012-07-01	
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2012-07-01	
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
zinc powder — zinc dust (stabilised)	7440-66-6	PEL (Total dust)	10 mg/m <sup>3</sup>	2014-11-26	
zinc powder — zinc dust (stabilised)	7440-66-6	PEL (respirable dust fraction)	5 mg/m <sup>3</sup>	2014-11-26	
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogentreated naphtha	64742-48-9	TWA	500 ppm 2 000 mg/m <sup>3</sup>	2007-01-01	
Naphtha (petroleum), hydrotreated heavy; Low	64742-48-9	TWA	400 ppm 1 600 mg/m <sup>3</sup>	1989-01-19	

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

boiling point					
hydrogen					
treated					
naphtha					

**8.2 Exposure controls**
**Personal protective equipment**

Eye protection : Safety glasses

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

The exact break through time can be obtained from the protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection

: Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

Respiratory protection : Use suitable breathing protection if workplace concentration requires.  
In the case of dust or aerosol formation use respirator with an approved filter.

**Environmental exposure controls**

General advice :  
: Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Water : Do not flush into surface water or sanitary sewer system.  
:

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance : Pasty solid  
Colour : silver  
Odour : characteristic  
pH : No data available  
Freezing point : No data available  
Boiling point/boiling range : No data available  
Flash point : No data available  
Bulk density : No data available

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

Flammability (solid, gas)	: Combustible Solids
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

**9.2 Other information**

Self-Accelerating decomposition temperature (SADT)	: No data available
Self-heating substances	: No data available
Heat of combustion	: No data available
Impact sensitivity	: No data available
Surface tension	: No data available

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

Conductivity : No data available  
Sublimation point : No data available  
Molecular weight : No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow evaporation to dryness.

No data available

**10.5 Incompatible materials**

Materials to avoid : Acids  
Bases  
Oxidizing agents

**10.6 Hazardous decomposition products**

Hazardous decomposition products : No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## ProFLAKE Zn 1590 MS Zinc Paste

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

Other information : No data available

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

###### Components:

###### **zinc powder — zinc dust (stabilised) :**

Acute oral toxicity : Rat: > 2 000 mg/kg

###### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha :**

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Acute inhalation toxicity : LC50 Rat: Test atmosphere: vapour

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity : LD50 Rabbit: > 5 000 mg/kg

##### Skin corrosion/irritation

No data available

##### Serious eye damage/eye irritation

No data available

##### Respiratory or skin sensitisation

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

---

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product**

No data available

---

**SECTION 12: Ecological information****12.1 Toxicity**

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

**Components:****zinc (7440-66-6) :****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.



**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

- Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
In accordance with local and national regulations.

**SECTION 14: Transport information****14.1 UN number****ADR** : 3077**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : 3077**IATA** : 3077**14.2 Proper shipping name**

**ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,  
N.O.S.  
(Zinc powder, stabilized )

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,  
N.O.S.  
(,Zinc powder, stabilized )

**IATA**

: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,  
N.O.S.  
(Zinc powder, stabilized)

**14.3 Transport hazard class****ADR** : 9**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : 9**IATA** : 9**14.4 Packing group****ADR**

Packaging group : III

Classification Code : M7

Hazard Identification Number : 90

Labels : 9

**TDG**

Not dangerous goods

**CFR**

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

Not dangerous goods

**IMDG**

Packaging group : III  
Labels : 9  
EmS Number : F-A, S-F

**IATA**

Packing instruction (cargo aircraft) : 956  
Packing instruction (passenger aircraft) : 956  
Packing instruction (LQ) : Y956  
Packaging group : III  
Labels : 9

**14.5 Environmental hazards**

**IMDG** : Marine pollutant  
**ADR** : Environmentally hazardous

**14.6 Special precautions for user****IMDG Code- segregation group:**

: IMDG Code segregation group 7 - Heavy metals and their salts

For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## ProFLAKE Zn 1590 MS Zinc Paste

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

#### 15.2 Chemical safety assessment

No data available

---

### SECTION 16: Other information

#### Full text of H-Statements

H227 : Combustible liquid.  
H304 : May be fatal if swallowed and enters airways.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**ProFLAKE Zn 1590 MS Zinc Paste**

Version 2.0

Revision Date 10.12.2019

Print Date 07.08.2020

---