

Date of impression 18.12.2020/17:07:25
page/of 1/1

edition 15.11.2020

material denomination **STANDART Pyro UZ Aluminium Powder**
material-no. 047103F50
material description Lamellar Aluminium-Powder
 produced of pure Aluminium 99,5 %

material specification

| insp. characteristic | specification | unit |
|--|----------------------|-------------|
| T100018 bulk density | 0,14 - 0,18 | g/cm3 |
| T100120 active metal content | >= 91 | % |
| T100005 sieving < 100 µm Wet Screen Analysis with Benzine | 80,0 - 90,0 | % |
| T100042 total grease | 1,0 - 1,7 | % |
| T100296 combustion time | Typical value 25 | s |

total shelf life in month: 36

EC-safety data sheet-no. 047103F50

The Data on this technical information sheet correspond with the current status of our knowledge and experience.
 The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.
 We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

| | | |
|--------------------|------------|-----------------|
| Draft | Approval | Release |
| Technical services | Production | Quality control |
| 15.11.2020 | 15.11.2020 | 15.11.2020 |

This document has been printed automatically and will not be signed.