

**Date of impression** 18.11.2020/14:17:19  
**page/of** 1/1

**edition** 16.12.2019

**material denomination** METALURE A-31010 AE  
**material-no.** 052350IA0  
**material description** Metalure Dispersion (PVD Pigment) in Ethyl Acetate  
 for Paints and Printing Inks  
 Stir before using !

**material specification**

insp. characteristic	specification	unit
Tl00011 dL* 45°	-2,0 - 2,0	
Tl00056 clean check	<= 21,3	%
Tl00138 Visual appearance (bar down)	pass	
Tl00146 delta gloss	-55 - 55	
Tl00146 mirror gloss	-40 - 40	
Tl02003 D 10	3,3 - 5,3	µm
Tl02003 D 50	9,5 - 10,5	µm
Tl02003 D 90	<= 21,0	µm
Tl02015 pigment content / non volatile	9,95 - 10,15	%
Tl02021 acetone content	<= 4,0	%
Tl02021 GC	pass	

total shelf life in month: 24

EC-safety data sheet-no. 052350IA0

The Data on this technical information sheet correspond with the current status of our knowledge and experience.  
 The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.  
 We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

Draft	Approval	Release
Technical services	Production	Quality control
16.12.2019	16.12.2019	16.12.2019

This document has been printed automatically and will not be signed.