

**PRIMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : PRIMASTAR SX-5321  
Material number : 052283LS0

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company :  
  
Telephone :  
Telefax :  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Flammable liquids, Category 4, H227  
Acute toxicity, Category 4, Oral, H302  
Acute toxicity, Category 4, Inhalation, H332

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## PRISMASTAR SX-5321

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

Acute toxicity, Category 4, Dermal, H312  
 Skin corrosion/irritation, Category 2, H315  
 Serious eye damage/eye irritation, Category 2A, H319

### GHS-Labeling

Symbol(s)

:



Signal word

:

Warning

Hazard statements

:

H227: Combustible liquid.  
 H302 + H312 + H332: Harmful if swallowed, in contact with skin or if inhaled.  
 H315: Causes skin irritation.  
 H319: Causes serious eye irritation.

Precautionary statements

:

**Prevention:**  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
 P302 + P352 + P312 IF ON SKIN: Wash with plenty of water. Call a POISON CENTER/doctor if you feel unwell.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
**Storage:**  
 P403 Store in a well-ventilated place.

### Hazardous components which must be listed on the label

Identification  
 2-butoxyethanol  
 propane-1,2-diol

CAS-No.  
 111-76-2  
 57-55-6

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## PRISMSTAR SX-5321

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

### SECTION 3: Composition/information on ingredients

Substance name : pstar sx-5321

Substance No. :

#### Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
2-butoxyethanol	111-76-2 203-905-0	Flam. Liq.;4;H227 Acute Tox.;4;H302 Acute Tox.;4;H312 Acute Tox.;4;H332 Skin Irrit.;2;H315 Eye Irrit.;2;H319	50 - 100
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	1 - 10
Aziridine, homopolymer	9002-98-6	Acute Tox.;4;H302 Eye Irrit.;2A;H319 ;;	0,1 - 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : Move the victim to fresh air.  
Do not leave the victim unattended.

**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

	<p>Move out of dangerous area.          Show this safety data sheet to the doctor in attendance.</p>
If inhaled	<p>: If unconscious, place in recovery position and seek medical advice.          If symptoms persist, call a physician.</p>
In case of skin contact	<p>: Wash off immediately with soap and plenty of water.</p> <p>If skin irritation persists, call a physician.          If on skin, rinse well with water.          If on clothes, remove clothes.</p>
In case of eye contact	<p>: Immediately flush eye(s) with plenty of water.</p> <p>Immediately flush eye(s) with plenty of water.          Remove contact lenses.          Keep eye wide open while rinsing.          If eye irritation persists, consult a specialist.</p>
If swallowed	<p>: Keep respiratory tract clear.          Do not give milk or alcoholic beverages.          Never give anything by mouth to an unconscious person.          If symptoms persist, call a physician.</p>

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**SECTION 5: Firefighting measures**
**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

Carbon dioxide (CO<sub>2</sub>)Unsuitable extinguishing media : ABC powder, Carbon dioxide (CO<sub>2</sub>), Water, Foam

High volume water jet

**5.2 Special hazards arising from the substance or mixture**

This information is not available.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.**6.2 Environmental precautions**

Environmental precautions : Prevent further leakage or spillage if safe to do so.

**6.3 Methods and materials for containment and cleaning up**Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

**PRISMSTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
 Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage**
**7.1 Precautions for safe handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

No smoking. Keep in a well-ventilated place. Observe label

**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Keep away from oxidizing agents and strongly acid or alkaline materials. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

This information is not available.

**SECTION 8: Exposure controls/personal protection**
**8.1 Control parameters**
**Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
2-butoxyethano l	111-76-2	TWA	20 ppm 98 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information		Identifies the possibility of significant uptake through the skin Indicative			
2-butoxyethano l	111-76-2	STEL	50 ppm 246 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information		Identifies the possibility of significant uptake through the			

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## PRISMASTAR SX-5321

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

		skinIndicative			
2-butoxyethanol	111-76-2	AGW	10 ppm 49 mg/m <sup>3</sup>	2012-01-12	DE TRGS 900
Peak-limit: excursion factor (category)		4;(II)			
Further information		Commission for dangerous substancesSkin absorptionWhen there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

### United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	2013-03-01	
2-butoxyethanol	111-76-2	TWA	5 ppm 24 mg/m <sup>3</sup>	2013-10-08	
2-	111-76-2	TWA	50 ppm	1997-08-04	



**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

butoxyethano l			240 mg/m <sup>3</sup>		
2- butoxyethano l	111-76-2	TWA	25 ppm 120 mg/m <sup>3</sup>	1989-01-19	
2- butoxyethano l	111-76-2	PEL	20 ppm 97 mg/m <sup>3</sup>	2014-11-26	
propane-1,2- diol	57-55-6	TWA	10 mg/m <sup>3</sup>	2008-01-01	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m <sup>3</sup>	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (total)	10 mg/m <sup>3</sup>	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	PEL (Total dust)	10 mg/m <sup>3</sup>	2014-11-26	
aluminium powder (stabilised)	7429-90-5	PEL (respirable dust fraction)	5 mg/m <sup>3</sup>	2014-11-26	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m <sup>3</sup>	2008-01-01	
aluminium	7429-90-5	TWA	5 mg/m <sup>3</sup>	2005-09-01	

**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

powder (stabilised)					
aluminium powder (stabilised)	7429-90-5	TWA (Total)	15 mg/m <sup>3</sup>	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m <sup>3</sup>	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2011-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total dust)	15 mg/m <sup>3</sup>	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (welding fumes)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (pyro powders)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m <sup>3</sup>	2013-03-01	
aluminium powder (stabilised)	7429-90-5	TWA (Fumes)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium powder (stabilised)	7429-90-5	PEL (Welding fumes)	5 mg/m <sup>3</sup>	2017-10-02	
aluminium powder (stabilised)	7429-90-5	PEL (Pyro powders)	5 mg/m <sup>3</sup>	2017-10-02	



**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: No data available
Odour	: characteristic
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 171 °C
Flash point	: 65 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Water solubility	: No data available
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available

**PRIMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

Viscosity, kinematic : No data available

Flow time : No data available

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

**10.5 Incompatible materials**Materials to avoid : Acids  
Bases  
Oxidizing agents**10.6 Hazardous decomposition products**

**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

Hazardous decomposition products : No data available

Other information : No data available

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity****Components:****2-butoxyethanol :**

Acute inhalation toxicity : > 3,1 mg/l

Exposure time: 1 h

Test atmosphere: vapour

Acute dermal toxicity : The component/mixture is moderately toxic after single contact with skin.

**Aziridine, homopolymer :**

Acute oral toxicity : Rat: 2 200 mg/kg

**Skin corrosion/irritation****Product**

May cause skin irritation in susceptible persons.

**Serious eye damage/eye irritation**

**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

**Product**

Eye irritation

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information**

**Product**

No data available

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

---

**SECTION 12: Ecological information****12.1 Toxicity**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**

Additional ecological information : No data available



**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

- Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

---

**SECTION 14: Transport information****14.1 UN number****14.2 Proper shipping name****14.3 Transport hazard class****14.4 Packing group****14.5 Environmental hazards****14.6 Special precautions for user**

Not classified as dangerous in the meaning of transport regulations.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

**PRISMSTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

No data available

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Prohibition/Restriction**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

**15.2 Chemical safety assessment**

No data available

**SECTION 16: Other information****Full text of H-Statements**

H227	: Combustible liquid.
H228	: Flammable solid.
H302	: Harmful if swallowed.
H302 + H312 + H332	: Harmful if swallowed, in contact with skin or if inhaled.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

**PRISMASTAR SX-5321**

Version 2.0

Revision Date 05.12.2019

Print Date 07.08.2020

---

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.