

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : STAPA HYDROXAL E 601 Aluminium Paste  
Product code : 021335KA0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company :  
  
E-mail address of person responsible for the SDS : msds.eckart@altana.com

#### 1.4 Emergency telephone number

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008)**  
Not a dangerous substance according to GHS.

#### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008)**  
Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

#### Additional Labelling

EUH210      Safety data sheet available on request.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

---

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Hazardous components

Chemical name	CAS-No. EC-No. Index-No.	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

	Registration number		
aluminium powder (stabilised)	7429-90-5 231-072-3 01-2119529243-45	Flam. Sol. 1; H228	>= 50 - <= 100
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	95-38-5 202-414-9 01-2119777867-13-0000	Acute Tox. 4; H302 Skin Corr. 1C; H314 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 3 - < 5
octylphosphonic acid	4724-48-5 225-218-5	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT RE 2; H373	>= 1 - < 3

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move the victim to fresh air.  
Do not leave the victim unattended.
- No hazards which require special first aid measures.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Remove contact lenses.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand  
Special powder against metal fire

Unsuitable extinguishing media : Water  
Foam  
ABC powder  
Carbon dioxide (CO<sub>2</sub>)

#### 5.2 Special hazards arising from the substance or mixture

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Avoid dust formation.

#### 6.2 Environmental precautions

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Pick up and arrange disposal without creating dust.  
Sweep up and shovel.  
Do not flush with water.  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.

For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

This information is not available.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version  
2.0

Revision Date:  
06.12.2019

SDS Number:  
102000022612

Print Date: 07.08.2020  
Date of first issue: 16.02.2015

	any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	TWA (Respirable)	4 mg/m <sup>3</sup>	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of		

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version  
2.0

Revision Date:  
06.12.2019

SDS Number:  
102000022612

Print Date: 07.08.2020  
Date of first issue: 16.02.2015

inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	Workers	Skin contact	Long-term systemic effects	0.06 mg/kg
	Workers	Inhalation	Long-term systemic effects	0.46 mg/m <sup>3</sup>
	Workers	Skin contact	Acute systemic effects	2 mg/kg
octylphosphonic acid	Workers	Inhalation	Acute systemic effects	14 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	4 mg/kg
	Workers	Inhalation	Long-term systemic effects	0.14 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	0.02 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0.071 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	Fresh water	0.00003 mg/l
	Marine water	0.000003 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

	Fresh water sediment	0.376 mg/kg
	Marine sediment	0.0376 mg/kg
	Soil	0.075 mg/kg
	clarification plant	0.27 mg/l
	Sporadic Release	0.0003 mg/l
octylphosphonic acid	Fresh water	0.04 mg/l
	Fresh water sediment	0.49 mg/kg
	STP	100 mg/l
	Soil	0.075 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses

Hand protection  
Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Long sleeved clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Protective suit

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

#### Environmental exposure controls

Water : The product should not be allowed to enter drains, water courses or the soil.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : Pasty solid

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---

Colour : silver

Odour : characteristic

Odour Threshold : No data available

pH : 7

Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : The product is not flammable.

Self-ignition : not auto-flammable

Auto-ignition temperature : No data available

Smoldering temperature : No data available

Decomposition temperature : No data available

Explosive properties : Not explosive

Oxidizing properties : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 1.3 g/cm<sup>3</sup>

Bulk density : No data available

Solubility(ies)  
Water solubility : insoluble

Solubility in other solvents : No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Flow time : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.  
Contact with acids and alkalis may release hydrogen.  
Mixture reacts slowly with water resulting in evolution of hydrogen.  
Vapour/air-mixtures are explosive at intense warming.

Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

No data available

### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

### 10.6 Hazardous decomposition products

Contact with water or humid air : This information is not available.

Thermal decomposition : This information is not available.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version  
2.0

Revision Date:  
06.12.2019

SDS Number:  
102000022612

Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.

##### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

##### Components:

##### **aluminium powder (stabilised):**

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

##### **octylphosphonic acid:**

Acute oral toxicity : (Rat): 500 - 2,000 mg/kg

##### **Skin corrosion/irritation**

Not classified based on available information.

##### Product:

Result: No skin irritation

Remarks: Based on available data, the classification criteria are not met.

##### Components:

##### **2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol:**

Result: Corrosive, category 1C - where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days.

Remarks: Extremely corrosive and destructive to tissue.

##### **octylphosphonic acid:**

Remarks: Extremely corrosive and destructive to tissue.

##### **Serious eye damage/eye irritation**

Not classified based on available information.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version  
2.0

Revision Date:  
06.12.2019

SDS Number:  
102000022612

Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---

### **Product:**

Result: No eye irritation

Remarks: Based on available data, the classification criteria are not met.

### **Components:**

#### **2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol:**

Result: No eye irritation

Remarks: May cause irreversible eye damage.

#### **octylphosphonic acid:**

Remarks: May cause irreversible eye damage.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

#### **STOT - repeated exposure**

Not classified based on available information.

### **Components:**

#### **2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol:**

Assessment: May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

Not classified based on available information.

### **Further information**

### **Product:**

Remarks: No data available

### **Components:**

#### **2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol:**

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---

Remarks: No data available

**octylphosphonic acid:**

Remarks: No data available

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

**Product:**

**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : This product has no known ecotoxicological effects.

Long-term (chronic) aquatic hazard : This product has no known ecotoxicological effects.

**Components:**

**2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol:**

M-Factor (Short-term (acute) aquatic hazard) : 10

M-Factor (Long-term (chronic) aquatic hazard) : 1

**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---

### 12.6 Other adverse effects

#### **Product:**

Additional ecological information : Information given is based on tests on the mixture itself.

#### **Components:**

##### **2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

##### **octylphosphonic acid:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles  
European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances

### 13.1 Waste treatment methods

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## SECTION 14: Transport information

### 14.1 UN number

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not permitted for transport

### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not permitted for transport

### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---

**IATA** : Not permitted for transport

### 14.4 Packing group

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA (Cargo)** : Not permitted for transport

**IATA (Passenger)** : Not permitted for transport

### 14.5 Environmental hazards

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.  
Due to the risk of hydrogen development we recommend to refrain from airfreighting this/these product(s).

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

### 15.2 Chemical safety assessment

---

## SECTION 16: Other information

### Full text of H-Statements

H228 : Flammable solid.  
H302 : Harmful if swallowed.  
H314 : Causes severe skin burns and eye damage.  
H318 : Causes serious eye damage.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version 2.0      Revision Date: 06.12.2019      SDS Number: 102000022612      Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Flam. Sol.	:	Flammable solids
Skin Corr.	:	Skin corrosion
STOT RE	:	Specific target organ toxicity - repeated exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA HYDROXAL E 601 Aluminium Paste

Version  
2.0

Revision Date:  
06.12.2019

SDS Number:  
102000022612

Print Date: 07.08.2020  
Date of first issue: 16.02.2015

---