

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : SILVEROTO 500 8113 PST A025  
Material number : 013142G60

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company :  
  
Telephone :  
Telefax :  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Flammable solids, Category 1, H228  
Eye irritation, Category 2A, H319  
Specific target organ toxicity - single exposure, Category 3,

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## SILVEROTO 500 8113 PST A025

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

Central nervous system, H336

### GHS-Labeling

Symbol(s)



Signal word

: Danger

Hazard statements

: H228: Flammable solid.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P243 Take precautionary measures against static discharge.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P370 + P378 In case of fire: Use for extinction: Dry sand.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

### Hazardous components which must be listed on the label

Identification  
ethyl acetate

CAS-No.  
141-78-6

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## SILVEROTO 500 8113 PST A025

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

### SECTION 3: Composition/information on ingredients

Substance name : silveroto 500 8113 pst 0811

Substance No. :

#### Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	60 - 100
ethyl acetate	141-78-6 205-500-4	Flam. Liq.;2;H225 Eye Irrit.;2A;H319 STOT SE;3;H336	30 - 60

For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.

Move the victim to fresh air.  
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water.

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

If on clothes, remove clothes.

Wash off immediately with soap and plenty of water.

- In case of eye contact : Immediately flush eye(s) with plenty of water.  
 Remove contact lenses.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.
- Immediately flush eye(s) with plenty of water.
- If swallowed : Keep respiratory tract clear.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**SECTION 5: Firefighting measures**
**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : Water, Foam, Carbon dioxide (CO<sub>2</sub>), ABC powder

**5.2 Special hazards arising from the substance or mixture**

This information is not available.

**5.3 Advice for firefighters**

Special protective equipment : Use personal protective equipment.

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

: Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.  
Avoid dust formation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Use personal protective equipment.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Do not flush with water.  
Keep in suitable, closed containers for disposal.  
  
Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

**6.4 Reference to other sections**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## SILVEROTO 500 8113 PST A025

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

For personal protection see section 8.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust formation. Ensure adequate ventilation.

Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

Avoid dust formation. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

Further information on : Protect from humidity and water. Do not allow to dry.

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

storage conditions

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

This information is not available.

**SECTION 8: Exposure controls/personal protection**
**8.1 Control parameters**
**Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
ethyl acetate	141-78-6	AGW	200 ppm 730 mg/m <sup>3</sup>	2017-06-08	DE TRGS 900
Peak-limit: excursion factor (category)		2;(l)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	STEL	400 ppm 1 468 mg/m <sup>3</sup>	2017-02-01	2017/164/EU
Further information		Indicative			
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m <sup>3</sup>	2017-02-01	2017/164/EU
Further information		Indicative			

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)



**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

- Remarks :
- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
  - : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).  
 The exact break through time can be obtained from the protective glove producer and this has to be observed.  
 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
 Recommended preventive skin protection  
 Skin should be washed after contact.  
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection :
- : Long sleeved clothing  
 Safety shoes
  - : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection :
- : In the case of dust or aerosol formation use respirator with an approved filter.
  - : Use suitable breathing protection if workplace concentration requires.

**Environmental exposure controls**

General advice : Prevent product from entering drains.

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

Water

:

:

: The product should not be allowed to enter drains, water  
courses or the soil.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance	: Pasty solid
Colour	: silver
Odour	: solvent-like
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 76 °C
Flash point	: No data available
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: not auto-flammable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 2,16 g/cm <sup>3</sup>

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

Water solubility	: No data available
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not explosive Vapours may form explosive mixture with air.

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.  
Contact with acids and alkalis may release hydrogen.  
Mixture reacts slowly with water resulting in evolution of hydrogen.  
Vapours may form explosive mixture with air.

Stable under recommended storage conditions.

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

---

**10.4 Conditions to avoid**

Conditions to avoid : Heat, flames and sparks.  
Do not allow to dry.

**10.5 Incompatible materials**

Materials to avoid : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

**10.6 Hazardous decomposition products**

Other information : No data available

---

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity****Components:****ethyl acetate :**

Acute oral toxicity : Rat: 5 620 mg/kg

Acute inhalation toxicity : LC50 Rat: 56 mg/l

Exposure time: 4 h

Test atmosphere: vapour

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

Acute dermal toxicity : LD50 Rabbit: &gt; 18 000 mg/kg

**Skin corrosion/irritation****Product**

May cause skin irritation in susceptible persons.

**Serious eye damage/eye irritation****Product**

May cause irreversible eye damage.

**Respiratory or skin sensitisation**

No data available

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

**Aspiration toxicity**

No data available

**Further information****Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,  
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may  
degrease the skin.

**SECTION 12: Ecological information****12.1 Toxicity****Components:****ethyl acetate (141-78-6) :**

Toxicity to daphnia and other : (Daphnia (water flea)): 717 mg/l  
aquatic invertebrates

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

---

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**Additional ecological information : No data available

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14: Transport information****14.1 UN number**

**ADR** : 1325  
**TDG** : 1325  
**CFR** : 1325

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

**IMDG** : 1325**IATA** : 1325**14.2 Proper shipping name****ADR** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste )**TDG** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste )**CFR** : FLAMMABLE SOLIDS, ORGANIC, N.O.S.  
(Aluminum pigment paste )**IMDG** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(,Aluminium pigment paste )**IATA** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)**14.3 Transport hazard class****ADR** : 4.1**TDG** : 4.1**CFR** : 4.1**IMDG** : 4.1**IATA** : 4.1**14.4 Packing group****ADR**

Packaging group : II

Classification Code : F1

Hazard Identification Number : 40

Labels : 4.1

Tunnel restriction code : (E)

**TDG**



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## SILVEROTO 500 8113 PST A025

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

Packaging group : II  
Labels : 4.1

### CFR

Packaging group : II  
Labels : 4.1

### IMDG

Packaging group : II  
Labels : 4.1  
EmS Number : F-G, S-G

### IATA

Packing instruction (cargo aircraft) : 448  
Packing instruction (passenger aircraft) : 445  
Packing instruction (LQ) : Y441  
Packaging group : II  
Labels : 4.1

## 14.5 Environmental hazards

**IMDG** :

## 14.6 Special precautions for user

### IMDG Code- segregation group:

: IMDG Code segregation group 15 - Powdered metals

## 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

**SILVEROTO 500 8113 PST A025**

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

**15.2 Chemical safety assessment**

No data available

**SECTION 16: Other information****Full text of H-Statements**

H225 : Highly flammable liquid and vapour.  
H228 : Flammable solid.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET



Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## SILVEROTO 500 8113 PST A025

Version 2.0

Revision Date 02.12.2019

Print Date 06.08.2020

---