

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version 6.0 Revision Date: 16.12.2019 SDS Number: 102000028180 Print Date: 06.08.2020
Date of first issue: 04.09.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ROTOSTAR UV 166 877 FLEXO INK
Product code : 023411U20

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company :

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|------------------------------------------------|----------------------------------------------------------|
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Reproductive toxicity, Category 2 | H361d: Suspected of damaging the unborn child. |
| Long-term (chronic) aquatic hazard, Category 3 | H412: Harmful to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version
6.0

Revision Date:
16.12.2019

SDS Number:
102000028180

Print Date: 06.08.2020
Date of first issue: 04.09.2017

H361d Suspected of damaging the unborn child.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Hazardous components which must be listed on the label:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid
Epoxy acrylate
ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate
2-Propenoic acid, ester with C12-16-alkyl glycidyl ether
Glycerol, propoxylated, esters with acrylic acid

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification REGULATION (EC) No 1272/2008 | Concentration (% w/w) |
|---------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------|--------------------------|
| Propylidynetrimethanol, ethoxylated, esters with acrylic acid | 28961-43-5 500-066-5 01-2119489900-30 | Eye Irrit. 2; H319 Skin Sens. 1; H317 | >= 50 - <= 100 |
| Epoxy acrylate | 55818-57-0 01-2119490020-53 | Skin Sens. 1; H317 | >= 10 - < 20 |
| ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate | 84434-11-7 282-810-6 | Aquatic Chronic 2; H411 Skin Sens. 1B; H317 | >= 10 - < 20 |
| aluminium powder (stabilised) | 7429-90-5 231-072-3 01-2119529243-45 | Flam. Sol. 1; H228 | >= 1 - < 10 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version 6.0 Revision Date: 16.12.2019 SDS Number: 102000028180 Print Date: 06.08.2020
Date of first issue: 04.09.2017

| | | | |
|----------------------------------------------------------|--------------------------------------------|----------------------------------------------|-------------|
| 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate | 6846-50-0 229-934-9 01-2119451093-47 | Repr. 2; H361d Aquatic Chronic 3; H412 | >= 3 - < 10 |
| 2-Propenoic acid, ester with C12-16-alkyl glycidyl ether | 68071-40-9 01-2120755565-46-xxxx | Skin Sens. 1; H317 | >= 1 - < 10 |
| Glycerol, propoxylated, esters with acrylic acid | 52408-84-1 500-114-5 | Eye Irrit. 2; H319 Skin Sens. 1; H317 | >= 1 - < 10 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Flush eyes with water as a precaution.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging the unborn child.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version 6.0 Revision Date: 16.12.2019 SDS Number: 102000028180 Print Date: 06.08.2020
Date of first issue: 04.09.2017

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand
ABC powder
Foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 06.08.2020 |
| 6.0 | 16.12.2019 | 102000028180 | Date of first issue: 04.09.2017 |

Do not flush with water.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids.
Do not store together with oxidizing and self-igniting products.
Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version 6.0 Revision Date: 16.12.2019 SDS Number: 102000028180 Print Date: 06.08.2020
Date of first issue: 04.09.2017

strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|----------------------|---------|
| aluminium powder (stabilised) | 7429-90-5 | TWA (Inhalable) | 10 mg/m ³ | GB EH40 |
| Further information | The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | | |
| | | TWA (Respirable) | 4 mg/m ³ | GB EH40 |
| Further information | The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | | |
| | | TWA (inhalable dust) | 10 mg/m ³ | GB EH40 |
| Further information | For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version
6.0

Revision Date:
16.12.2019

SDS Number:
102000028180

Print Date: 06.08.2020
Date of first issue: 04.09.2017

| | | | |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------|
| | termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | |
| | TWA (Respirable dust) | 4 mg/m ³ | GB EH40 |
| Further information | For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|---------------------------------------------------------------|-----------|-----------------|----------------------------|------------------------|
| Propylidynetrimethanol, ethoxylated, esters with acrylic acid | Workers | Skin contact | Long-term systemic effects | 0.8 mg/kg |
| | Workers | Inhalation | Long-term systemic effects | 16.2 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 0.5 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 4.9 mg/m ³ |
| | Consumers | Ingestion | Long-term systemic effects | 1.4 mg/kg |
| Epoxy acrylate | Workers | Skin contact | Long-term systemic effects | 33 mg/kg |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version
6.0

Revision Date:
16.12.2019

SDS Number:
102000028180

Print Date: 06.08.2020
Date of first issue: 04.09.2017

| | | | | |
|----------------------------------------------------|-----------|--------------|----------------------------|-------------------------|
| | Workers | Inhalation | Long-term systemic effects | 1.17 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 0.29 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 16.67 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 0.17 mg/kg |
| ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate | Workers | Skin contact | Long-term systemic effects | 1.7 mg/kg |
| | Workers | Inhalation | Long-term systemic effects | 5.88 mg/m ³ |
| aluminium powder (stabilised) | Workers | Inhalation | Long-term local effects | 3.72 mg/m ³ |
| | Consumers | Oral | Long-term systemic effects | 3.95 mg/kg |
| | Workers | Inhalation | Long-term systemic effects | 3.72 mg/m ³ |
| 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate | Workers | Skin contact | Long-term systemic effects | 5.00 mg/kg |
| | Workers | Inhalation | Long-term systemic effects | 17.62 mg/m ³ |
| | Consumers | Ingestion | Long-term systemic effects | 5.00 mg/kg |
| | Consumers | Skin contact | Long-term systemic effects | 5.00 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 4.35 mg/m ³ |
| Glycerol, propoxylated, esters with acrylic acid | Workers | Inhalation | Long-term systemic effects | 16.22 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 1.92 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 4.87 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 1.15 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 1.39 mg/kg |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|---------------------------------------------------------------|---------------------------|-------------|
| Propylidynetrimethanol, ethoxylated, esters with acrylic acid | Soil | 0.006 mg/kg |
| | Fresh water | 0.002 mg/l |
| | Fresh water sediment | 0.008 mg/kg |
| | STP | 10 mg/l |
| | Marine water | 0.00 mg/l |
| | Marine sediment | 0.001 mg/kg |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version
6.0

Revision Date:
16.12.2019

SDS Number:
102000028180

Print Date: 06.08.2020
Date of first issue: 04.09.2017

| | | |
|----------------------------------------------------|----------------------------|----------------|
| Epoxy acrylate | Fresh water | 0.1 mg/l |
| | Marine water | 0.01 mg/l |
| | Fresh water sediment | 35.8 mg/kg |
| | Marine sediment | 3.58 mg/kg |
| | clarification plant | 10 mg/l |
| | Soil | 7.1 mg/kg |
| | | |
| aluminium powder (stabilised) | Fresh water | 0.0749 mg/l |
| | clarification plant | 20 mg/l |
| 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate | Fresh water | 0.014 mg/l |
| | Marine water | 0.0014 mg/l |
| | Fresh water sediment | 5.29 mg/kg |
| | Soil | 1.05 mg/kg |
| | STP | 3 mg/l |
| | Marine sediment | 0.529 mg/kg |
| | oral (secondary poisoning) | 83.3 mg/kg |
| Glycerol, propoxylated, esters with acrylic acid | Fresh water | 0.00574 mg/l |
| | Marine water | 0.000574 mg/l |
| | Fresh water sediment | 0.01697 mg/kg |
| | Marine sediment | 0.001697 mg/kg |
| | STP | 10 mg/l |
| | Soil | 0.00111 mg/kg |

8.2 Exposure controls

Personal protective equipment

Eye protection : Goggles

Safety glasses

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version
6.0

Revision Date:
16.12.2019

SDS Number:
102000028180

Print Date: 06.08.2020
Date of first issue: 04.09.2017

concentration of the dangerous substance at the work place.
Respiratory protection : Use suitable breathing protection if workplace concentration requires.

Environmental exposure controls

Water : The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : silver
Odour : characteristic
Odour Threshold : No data available
pH : No data available
Freezing point : No data available
Boiling point/boiling range : > 100 °C
Flash point : > 100 °C
Evaporation rate : No data available
Flammability (solid, gas) : No data available
Self-ignition : No data available
Auto-ignition temperature : No data available
Smoldering temperature : No data available
Decomposition temperature : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Upper explosion limit / Upper flammability limit : No data available
Lower explosion limit / Lower flammability limit : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version 6.0 Revision Date: 16.12.2019 SDS Number: 102000028180 Print Date: 06.08.2020
Date of first issue: 04.09.2017

Vapour pressure : No data available
Relative vapour density : No data available
Relative density : No data available
Density : No data available
Bulk density : No data available
Water solubility : No data available
Solubility in other solvents : No data available
Partition coefficient: n-octanol/water : No data available
Decomposition temperature : No data available
Viscosity, dynamic : No data available
Viscosity, kinematic : No data available
Flow time : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.
Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.
No data available

10.5 Incompatible materials

Materials to avoid : Acids

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version 6.0 Revision Date: 16.12.2019 SDS Number: 102000028180 Print Date: 06.08.2020
Date of first issue: 04.09.2017

Bases
Oxidizing agents

10.6 Hazardous decomposition products

Contact with water or humid air : This information is not available.

Thermal decomposition : This information is not available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Acute oral toxicity : (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: May cause skin irritation and/or dermatitis.

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version
6.0

Revision Date:
16.12.2019

SDS Number:
102000028180

Print Date: 06.08.2020
Date of first issue: 04.09.2017

Species: Rabbit
Exposure time: 4 h
Method: OECD Test Guideline 404
Result: No skin irritation

Glycerol, propoxylated, esters with acrylic acid:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Result: Irritating to eyes.

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species: Rabbit
Exposure time: 72 h
Method: OECD Test Guideline 405
Result: No eye irritation

Glycerol, propoxylated, esters with acrylic acid:

Remarks: Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks: Causes sensitisation.
May cause sensitisation of susceptible persons by skin contact.

Components:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Result: May cause sensitisation by skin contact.

Remarks: Causes sensitisation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version
6.0

Revision Date:
16.12.2019

SDS Number:
102000028180

Print Date: 06.08.2020
Date of first issue: 04.09.2017

May cause sensitisation of susceptible persons by skin contact.

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: Causes sensitisation.

May cause sensitisation of susceptible persons by skin contact.

2-Propenoic acid, ester with C12-16-alkyl glycidyl ether:

Result: May cause sensitisation by skin contact.

Glycerol, propoxylated, esters with acrylic acid:

Remarks: Causes sensitisation.

May cause sensitisation of susceptible persons by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Components:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Remarks: No data available

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Remarks: No data available

Glycerol, propoxylated, esters with acrylic acid:

Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version 6.0 Revision Date: 16.12.2019 SDS Number: 102000028180 Print Date: 06.08.2020
Date of first issue: 04.09.2017

SECTION 12: Ecological information

12.1 Toxicity

Components:

Propylidynetrimehanol, ethoxylated, esters with acrylic acid:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 10,232.73 mg/l

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 2.46 mg/l

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

Components:

Propylidynetrimehanol, ethoxylated, esters with acrylic acid:

Additional ecological information : No data available

ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

Additional ecological information : An environmental hazard cannot be excluded in the event of

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

Version 6.0 Revision Date: 16.12.2019 SDS Number: 102000028180 Print Date: 06.08.2020
Date of first issue: 04.09.2017

information unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

Glycerol, propoxylated, esters with acrylic acid:

Additional ecological information : No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number

14.2 UN proper shipping name

14.3 Transport hazard class(es)

14.4 Packing group

14.5 Environmental hazards

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 06.08.2020 |
| 6.0 | 16.12.2019 | 102000028180 | Date of first issue: 04.09.2017 |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

| | | |
|-------------------------------------------------------------------------------------------|---|----------------|
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). | : | Not applicable |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer | : | Not applicable |
| Regulation (EC) No 850/2004 on persistent organic pollutants | : | Not applicable |

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

| | | |
|-------|---|----------------------------------------------------|
| H228 | : | Flammable solid. |
| H317 | : | May cause an allergic skin reaction. |
| H319 | : | Causes serious eye irritation. |
| H361d | : | Suspected of damaging the unborn child. |
| H411 | : | Toxic to aquatic life with long lasting effects. |
| H412 | : | Harmful to aquatic life with long lasting effects. |

Full text of other abbreviations

| | | |
|-----------------|---|--------------------------------------------------------|
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard |
| Eye Irrit. | : | Eye irritation |
| Flam. Sol. | : | Flammable solids |
| Repr. | : | Reproductive toxicity |
| Skin Sens. | : | Skin sensitisation |
| GB EH40 | : | UK. EH40 WEL - Workplace Exposure Limits |
| GB EH40 / TWA | : | Long-term exposure limit (8-hour TWA reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV 166 877 FLEXO INK

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 06.08.2020 |
| 6.0 | 16.12.2019 | 102000028180 | Date of first issue: 04.09.2017 |

International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN