UNIPAK UV 286 875 LITHO INK

Version	Revision Date:	SDS Number:	Print Date: 19.07.2026
9.0	16.07.2026	102000034455	Date of first issue: 22.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : UNIPAK UV 286 875 LITHO INK

Product code : 026852N40

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone

NCEC: +44 1235 239670 (Europe)
Call and response in your language is possible.
Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :

Signal Word : Warning

Hazard Statements :

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P391	Collect spillage.

Hazardous ingredients which must be listed on the label:

Copper
Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid
Propylidynetrimethanol, ethoxylated, esters with acrylic acid
Poly(oxy-1,2-ethanediyl),a,a'-[(1-methylethylidene)di-4,1-phenylene]bis[w_hydroxy-, polymer with 1,3-
diisocyanatomethylbenzene, 2-propenoate
(ester) 3,5,5-trimethylhexanoate (ester)
4,4'-Isopropylidenediphenol, ethoxylated, esters with acrylic acid and isononanoic acid
Glycerol, propoxylated, esters with acrylic acid
Bisphenol A epoxy acrylate
2,6-bis(1,1-dimethylethyl)-4-(phenylenemethylene)cyclohexa-2,5-dien-1-one

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Copper	7440-50-8 231-159-6	Acute Tox. 4; H302 Eye Irrit. 2; H319 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	>= 25 - < 50
Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid	216689-76-8	Skin Sens. 1; H317	>= 10 - < 20
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	28961-43-5 500-066-5	Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 10 - < 20
Poly(oxy-1,2-ethanediyl),a,a'-[(1-methylethylidene)di-4,1-phenylene]bis[w_hydroxy-, polymer with 1,3-diisocyanatomethylbenzene, 2-propenoate (ester) 3,5,5-trimethylhexanoate (ester)	2146146-71-4	Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 10 - < 20
4,4'-Isopropylidenediphenol, ethoxylated, esters with acrylic acid and isononanoic acid	Not Assigned 919-846-5	Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 2.5 - < 10
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3 030-001-01-9	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute	>= 2.5 - < 10

		aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
Glycerol, propoxylated, esters with acrylic acid	52408-84-1 500-114-5	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 10
Fatty acids, C18-unsatd., dimers, polymers with acrylic acid and epichlorohydrin	68938-18-1	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10
Bisphenol A epoxy acrylate	55818-57-0 500-130-2	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 1 - < 2.5
2-hydroxy-1-(4-(4-(2-hydroxy-2-methylpropionyl)benzyl)phenyl)-2-methylpropan-1-one	474510-57-1 444-860-9 606-140-00-4	STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2.5
2,6-bis(1,1-dimethylethyl)-4-(phenylenemethylene)cyclohexa-2,5-dien-1-one	7078-98-0 429-460-4 606-117-00-9	Skin Sens. 1; H317 Aquatic Chronic 4; H413	>= 0.1 - < 0.25
octadecylamine	124-30-1 204-695-3 612-282-00-8	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373 (Liver, Gastrointestinal tract, Immune system) Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1010	>= 0.0025 - < 0.025

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Take the victim into fresh air.

Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Remove to fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

If skin irritation persists, call a physician.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Special powder against metal fire
Dry sand
ABC powder

Unsuitable extinguishing media : Water
High volume water jet
Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Pick up and transfer to properly labeled containers.
Do not flush with water.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Advice on protection against fire and explosion	:	Keep away from heat and sources of ignition. No smoking. Normal measures for preventive fire protection.
Hygiene measures	:	General industrial hygiene practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.
Further information on storage conditions	:	Protect from humidity and water.
Advice on common storage	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.
Dampness	:	Keep in a dry, cool and well-ventilated place.
Further information on storage stability	:	No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Copper	7440-50-8	TWA (Fumes)	0.2 mg/m3 (Copper)	GB EH40
		TWA (Dusts and mists)	1 mg/m3 (Copper)	GB EH40
		STEL (Dusts and mists)	2 mg/m3 (Copper)	GB EH40
zinc powder — zinc dust (stabilised)	7440-66-6	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40

Derived No Effect Level (DNEL)

Substance name	End Use	Routes of exposure	Potential health effects	Value
Copper	Workers	Dermal	Long-term systemic effects	137 mg/kg
	Workers	Dermal	Acute systemic effects	273 mg/kg
	Workers	Inhalation	Long-term systemic effects	20 mg/m3
	Consumers	Inhalation	Long-term local effects	1 mg/m3
	Consumers	Inhalation	Acute local effects	1 mg/m3
	Consumers	Dermal	Long-term systemic effects	137 mg/kg
	Consumers	Dermal	Acute systemic effects	273 mg/kg
	Consumers	Oral	Long-term systemic effects	0.041 mg/kg
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Workers	Inhalation	Long-term systemic effects	37 mg/m3
	Workers	Skin contact	Long-term systemic effects	10.5 mg/kg
	Consumers	Inhalation	Long-term systemic effects	4.9 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0.5 mg/kg
	Consumers	Ingestion	Long-term systemic effects	1.4 mg/kg
zinc powder — zinc dust (stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m3

	Workers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
	Consumers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Oral	Long-term systemic effects	0.83 mg/kg
Glycerol, propoxylated, esters with acrylic acid	Workers	Inhalation	Long-term systemic effects	7.4 mg/m3
	Workers	Dermal	Long-term systemic effects	1.92 mg/kg
	Consumers	Inhalation	Long-term systemic effects	4.87 mg/m3
	Consumers	Dermal	Long-term systemic effects	1.15 mg/kg
	Consumers	Oral	Long-term systemic effects	1.39 mg/kg
Bisphenol A epoxy acrylate	Workers	Inhalation	Long-term systemic effects	1.17 mg/m3
	Workers	Dermal	Long-term systemic effects	33 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0.29 mg/m3
	Consumers	Dermal	Long-term systemic effects	16.67 mg/kg
	Consumers	Oral	Long-term systemic effects	0.17 mg/kg

Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value
Copper	Fresh water	0.0078 mg/l
	Sea water	0.0052 mg/l
	STP	0.230 mg/l
	Fresh water sediment	87 mg/kg
	Sea sediment	676 mg/kg
	Soil	65 mg/kg
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Fresh water	0.002 mg/l
	Freshwater - intermittent	0.019 mg/l
	Sea water	0 mg/l
	STP	10 mg/l
	Fresh water sediment	0.008 mg/kg
	Sea sediment	0.001 mg/kg
	Soil	0.006 mg/kg
zinc powder — zinc dust (stabilised)	Fresh water	0.0206 mg/l
	Sea water	0.0061 mg/l
	STP	0.100 mg/l
	Fresh water sediment	235.6 mg/kg
	Sea sediment	121 mg/kg
	Soil	35.6 mg/kg

Glycerol, propoxylated, esters with acrylic acid	Fresh water	0.0057 mg/l
	Sea water	0.00057 mg/l
	Fresh water sediment	0.0168 mg/kg
	Sea sediment	0.00168 mg/kg
	STP	10 mg/l
	Soil	0.0011 mg/kg
Bisphenol A epoxy acrylate	Fresh water	0.025 mg/l
	Sea water	0.003 mg/l
	Intermittent Release	1 mg/l
	Fresh water sediment	8.96 mg/kg
	Sea sediment	0.896 mg/kg
	STP	10 mg/l
	Soil	1.78 mg/kg
2-hydroxy-1-(4-(4-(2-hydroxy-2-methylpropionyl)benzyl)phenyl)-2-methylpropan-1-one	Fresh water	0.001 mg/l
	Sea water	0 mg/l
	Fresh water sediment	0.008 mg/kg
	Sea sediment	0.001 mg/kg
	STP	10 mg/l
	Soil	1 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.
Equipment should conform to EN 14387

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	:	liquid
Color	:	gold
Odor	:	characteristic
Odor Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/ range	:	Not applicable
Boiling point/boiling range	:	> 100 °C
Flash point	:	> 100 °C
Flammability	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	1.4 g/cm3
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

10.5 Incompatible materials

10.6 Hazardous decomposition products

Thermal decomposition : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,448 mg/kg
Method: Calculation method

Components:

Copper:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

zinc powder — zinc dust (stabilised):

Acute oral toxicity : (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.41 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

2-hydroxy-1-(4-(4-(2-hydroxy-2-methylpropionyl)benzyl)phenyl)-2-methylpropan-1-one:
Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation
Not classified due to lack of data.

Product:
Remarks : May cause skin irritation and/or dermatitis.

Components:

Fatty acids, C18-unsatd., dimers, polymers with acrylic acid and epichlorohydrin:
Result : Skin irritation

octadecylamine:
Result : Skin irritation

Serious eye damage/eye irritation
Causes serious eye irritation.

Product:
Remarks : May cause irreversible eye damage.

Components:

Copper:
Result : Eye irritation

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:
Result : Irritating to eyes.

Glycerol, propoxylated, esters with acrylic acid:
Result : Eye irritation

Fatty acids, C18-unsatd., dimers, polymers with acrylic acid and epichlorohydrin:
Result : Eye irritation

octadecylamine:
Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization
May cause an allergic skin reaction.

Respiratory sensitization
Not classified due to lack of data.

Product:
Remarks : Causes sensitization.

Components:

Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid:
Result : May cause sensitization by skin contact.

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:
Result : May cause sensitization by skin contact.

Poly(oxy-1,2-ethanediyl),a,a'-[(1-methylethylidene)di-4,1-phenylene]bis[w_hydroxy-, polymer with 1,3-

diisocyanatomethylbenzene, 2-propenoate

(ester) 3,5,5-trimethylhexanoate (ester)

:
Result : Probability or evidence of low to moderate skin sensitization rate in humans

4,4'-Isopropylidenediphenol, ethoxylated, esters with acrylic acid and isononanoic acid:
Result : Probability or evidence of low to moderate skin sensitization rate in humans

Glycerol, propoxylated, esters with acrylic acid:
Result : May cause sensitization by skin contact.

Bisphenol A epoxy acrylate:
Result : May cause sensitization by skin contact.

2,6-bis(1,1-dimethylethyl)-4-(phenylenemethylene)cyclohexa-2,5-dien-1-one:
Result : May cause sensitization by skin contact.

Germ cell mutagenicity
Not classified due to lack of data.

Carcinogenicity
Not classified due to lack of data.

Reproductive toxicity
Not classified due to lack of data.

STOT-single exposure
Not classified due to lack of data.

STOT-repeated exposure
Not classified due to lack of data.

Components:

2-hydroxy-1-(4-(4-(2-hydroxy-2-methylpropionyl)benzyl)phenyl)-2-methylpropan-1-one:
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

octadecylamine:
Routes of exposure : Ingestion
Target Organs : Liver, digestive system, Immune system
Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity
Not classified due to lack of data.

Components:

octadecylamine:
May be fatal if swallowed and enters airways.

Further information

Product:
Remarks : No data available

Components:

zinc powder — zinc dust (stabilised):
Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Copper:
M-Factor (Short-term (acute) aquatic hazard) : 10
M-Factor (Long-term (chronic) aquatic hazard) :

Ecotoxicology Assessment
Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Ecotoxicology Assessment
Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Poly(oxy-1,2-ethanediyl),a,a'-[(1-methylethylidene)di-4,1-phenylene]bis[w_hydroxy-, polymer with 1,3-

diisocyanatomethylbenzene, 2-propenoate

(ester) 3,5,5-trimethylhexanoate (ester)

:

Ecotoxicology Assessment
Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

4,4'-Isopropylidenediphenol, ethoxylated, esters with acrylic acid and isononanoic acid:

Ecotoxicology Assessment
Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

zinc powder — zinc dust (stabilised):
M-Factor (Short-term (acute) aquatic hazard) : 1
M-Factor (Long-term (chronic) aquatic hazard) : 1

Ecotoxicology Assessment
Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Bisphenol A epoxy acrylate:

Ecotoxicology Assessment
Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

2-hydroxy-1-(4-(4-(2-hydroxy-2-methylpropionyl)benzyl)phenyl)-2-methylpropan-1-one:
M-Factor (Short-term (acute) aquatic hazard) : 1
M-Factor (Long-term (chronic) aquatic hazard) : 1

Ecotoxicology Assessment
Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

2,6-bis(1,1-dimethylethyl)-4-(phenylenemethylene)cyclohexa-2,5-dien-1-one:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

octadecylamine:

M-Factor (Short-term (acute) aquatic hazard) : 10

M-Factor (Long-term (chronic) aquatic hazard) : 10

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Poly(oxy-1,2-ethanediyl),a,a'-[(1-methylethylidene)di-4,1-phenylene]bis[w_hydroxy-, polymer with 1,3-

diisocyanatomethylbenzene, 2-propenoate

(ester) 3,5,5-trimethylhexanoate (ester)

:

Partition coefficient: n-octanol/water : Pow: 1.49 - 4.74
Method: OECD Test Guideline 117

Glycerol, propoxylated, esters with acrylic acid:

Partition coefficient: n-octanol/water : log Pow: 2.52 (23 °C)
Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

Components:

Glycerol, propoxylated, esters with acrylic acid:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

ADR : UN 3082

IMDG : UN 3082

IATA : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Copper metal powder)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Copper metal powder)

IATA : Environmentally hazardous substance, liquid, n.o.s.
(Copper metal powder)

14.3 Transport hazard class(es)

		Class	Subsidiary risks
ADR	:	9	
IMDG	:	9	
IATA	:	9	

14.4 Packing group

ADR

Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9
Tunnel restriction code	:	(-)

IMDG

Packing group	:	III
Labels	:	9
EmS Code		F-AS-F
EmS Code (EmS Code)	:	F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft)	:	964
Packing instruction (LQ)	:	Y964
Packing group	:	III
Labels	:	9

IATA (Passenger)

Packing instruction (passenger aircraft)	:	964
Packing instruction (LQ)	:	Y964
Packing group	:	III
Labels	:	9

14.5 Environmental hazards

ADR

Environmentally hazardous	:	yes

IMDG

Marine pollutant	:	yes

14.6 Special precautions for user

Remarks	:	For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries must be considered:: Number on list 3: Fatty acids, C18-unsatd., dimers, polymers with acrylic acid, bisphenol A, epichlorohydrin and nonanoic acid, Propylidynetrimethanol, ethoxylated, esters with acrylic acid, Poly(oxy-1,2-ethanediyl),a,a'-[(1-methylethylidene)di-4,1-phenylene]bis[w_hydroxy-, polymer with 1,3-diisocyanatomethylbenzene, 2-propenoate (ester) 3,5,5-trimethylhexanoate (ester) , Glycerol, propoxylated, esters with acrylic acid, Bisphenol A epoxy acrylate, Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2,6-bis(1,1-dimethylethyl)-4-(phenylenemethylene)cyclohexa-2,5-dien-1-one, (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate, cyclohexane Number on list 3 Number on list 40: cyclohexane
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation	:	Not applicable

(Annex XIV)
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH) E1 ENVIRONMENTAL HAZARDS

15.2 Chemical Safety Assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
STOT RE	:	Specific target organ toxicity - repeated exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; BGW - Biological Limit Values; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on

Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:		**Classification procedure:**
Acute Tox. 4	H302	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN