

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : METALURE A-31510 EN

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

#### 1.4 Emergency telephone number

GBK Gefahrgut Büro GmbH, Ingelheim, Germany:  
From outside US: : (001) 352-323-3500  
(First call in English, response in your language is possible)  
US & Canada (toll free) : 1-800-5355-053

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids , Category 2 H225: Highly flammable liquid and vapour.  
Eye irritation , Category 2 H319: Causes serious eye irritation.

##### Classification (67/548/EEC, 1999/45/EC)

Highly flammable R11: Highly flammable.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

Signal word	:	Danger	
Hazard statements	:	H225 H319	Highly flammable liquid and vapour. Causes serious eye irritation.
Precautionary statements	:	<b>Prevention:</b> P233 P261 P280 <b>Response:</b> P337 + P313 <b>Storage:</b> P403 + P235 <b>Disposal:</b> P501	Keep container tightly closed. Avoid breathing vapours. Wear protective gloves/ protective clothing/ eye protection/ face protection.  If eye irritation persists: Get medical advice/ attention. In case of fire: Use for extinction: Dry sand.  Store in a well-ventilated place. Keep cool.  Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
ethanol	64-17-5 200-578-6	F; R11	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 50 - <= 100
aluminium	7429-90-5 231-072-3	F; R11	Flam. Sol. 1; H228	>= 10 - < 20
acetone	67-64-1 200-662-2	F; R11 Xi; R36 R66 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 3 - < 10
propan-2-ol	67-63-0	F; R11	Flam. Liq. 2; H225	>= 1 - < 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

	200-661-7	Xi; R36 R67	Eye Irrit. 2; H319 STOT SE 3; H336	
--	-----------	----------------	---------------------------------------	--

For the full text of the R-phrases mentioned in this Section, see Section 16.  
For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.
- Move the victim to fresh air.  
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- Immediately flush eye(s) with plenty of water.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

**METALURE A-31510 EN**

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media : Dry sand, Special powder against metal fire
- Unsuitable extinguishing media : ABC powder, Carbon dioxide (CO<sub>2</sub>), Water, Foam

**5.2 Special hazards arising from the substance or mixture**

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

- Special protective equipment for firefighters : Wear self contained breathing apparatus for fire fighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

- Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Evacuate personnel to safe areas.

**6.2 Environmental precautions**

- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

### 6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Do not flush with water.
- Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Earthing of containers and apparatuses is essential. Reaction

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Keep away from oxidising agents and strongly acid or alkaline materials. Never allow product to get in contact with water during storage. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m <sup>3</sup>	2005-04-06	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used				
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	2011-12-01	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

		exposure to these must comply with the appropriate limit. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
aluminium	7429-90-5	TWA (Respirable)	4 mg/m <sup>3</sup>	2011-12-01	GB EH40
Further information		The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
aluminium	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	2005-04-06	GB EH40
Further information		For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
aluminium	7429-90-5	TWA (Respirable)	4 mg/m <sup>3</sup>	2005-04-06	GB EH40
Further information		For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

<p>when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>					
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
acetone	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information		Indicative			
acetone	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	2005-04-06	GB EH40
acetone	67-64-1	STEL	1,500 ppm 3,620 mg/m <sup>3</sup>	2005-04-06	GB EH40
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m <sup>3</sup>	2006-09-01	GB EH40
propan-2-ol	67-63-0	STEL	500 ppm 1,250 mg/m <sup>3</sup>	2006-09-01	GB EH40

### DNEL:



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

ethanol (64-17-5)

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: short term – local effects  
Value: 1900 mg/m<sup>3</sup>

**DNEL:**

ethanol (64-17-5)

End Use: Workers  
Exposure routes: Skin contact  
Potential health effects: long term – systemic effects  
Value: 343 mg/kg

**DNEL:**

ethanol (64-17-5)

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: long term – systemic effects  
Value: 950 mg/m<sup>3</sup>

**DNEL:**

ethanol (64-17-5)

End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: short term – local effects  
Value: 950 mg/m<sup>3</sup>

**DNEL:**

ethanol (64-17-5)

End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: long term – systemic effects  
Value: 87 mg/kg

**DNEL:**

ethanol (64-17-5)

End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: long term – systemic effects  
Value: 206 mg/kg

**DNEL:**

ethanol (64-17-5)

End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: long term – systemic effects  
Value: 114 mg/m<sup>3</sup>

**DNEL:**

acetone (67-64-1)

End Use: Workers  
Exposure routes: Skin contact  
Potential health effects: long term – systemic effects  
Value: 186 mg/kg

**DNEL:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

acetone (67-64-1)

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: long term – systemic effects  
Value: 1210 mg/m<sup>3</sup>

**DNEL:**

acetone (67-64-1)

End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: long term – systemic effects  
Value: 62 mg/kg

**DNEL:**

acetone (67-64-1)

End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: long term – systemic effects  
Value: 62 mg/kg

**DNEL:**

acetone (67-64-1)

End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: long term – systemic effects  
Value: 200 mg/m<sup>3</sup>

**DNEL:**

propan-2-ol (67-63-0)

End Use: Workers  
Exposure routes: Skin contact  
Potential health effects: long term – systemic effects  
Value: 888 mg/kg

**DNEL:**

propan-2-ol (67-63-0)

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: long term – systemic effects  
Value: 500 mg/m<sup>3</sup>

**DNEL:**

propan-2-ol (67-63-0)

End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: long term – systemic effects  
Value: 26 mg/kg

**DNEL:**

propan-2-ol (67-63-0)

End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: long term – systemic effects  
Value: 319 mg/kg

**DNEL:**



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

<b>PNEC:</b> propan-2-ol (67-63-0)	:	Soil Value: 28 mg/kg
<b>PNEC:</b> propan-2-ol (67-63-0)	:	Fresh water Value: 140.9 mg/l
<b>PNEC:</b> propan-2-ol (67-63-0)	:	Fresh water sediment Value: 552 mg/kg
<b>PNEC:</b> propan-2-ol (67-63-0)	:	Marine water Value: 140.9 mg/l
<b>PNEC:</b> propan-2-ol (67-63-0)	:	Marine sediment Value: 552 mg/kg
<b>PNEC:</b> propan-2-ol (67-63-0)	:	STP Value: 2251 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection	:	Goggles
	:	Eye wash bottle with pure water Wear face-shield and protective suit for abnormal processing problems.
Hand protection		
Material	:	Solvent-resistant gloves (butyl-rubber)
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the

## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Water :

:

:

: The product should not be allowed to enter drains, water courses or the soil.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : silver

Odour : characteristic

pH : no data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

---

Freezing point	: no data available
Boiling point/boiling range	: 78 °C
Flash point	: 13 °C
Bulk density	: no data available
Flammability (solid, gas)	: no data available
Auto-flammability	: no data available
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Density	: 1.08 g/cm <sup>3</sup>
Water solubility	: no data available
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, dynamic	: no data available
Viscosity, kinematic	: no data available
Flow time	: no data available

### 9.2 Other information

no data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Do not allow evaporation to dryness.

### 10.5 Incompatible materials

Materials to avoid : no data available

### 10.6 Hazardous decomposition products

Other information : no data available

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

no data available

#### Skin corrosion/irritation

##### Product

May cause skin irritation in susceptible persons.

#### Serious eye damage/eye irritation

##### Product

May cause irreversible eye damage.

#### Respiratory or skin sensitisation

no data available

#### Carcinogenicity

no data available

#### Toxicity to reproduction/fertility

no data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

---

### Reprod.Tox./Development/Teratogenicity

no data available

### STOT - single exposure

no data available

### STOT - repeated exposure

no data available

### Aspiration toxicity

no data available

### Further information

#### Product

Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

no data available

### 12.2 Persistence and degradability

no data available

### 12.3 Bioaccumulative potential

no data available

### 12.4 Mobility in soil

no data available

### 12.5 Results of PBT and vPvB assessment



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

no data available

### 12.6 Other adverse effects

**Product:**

Additional ecological information : no data available

## SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14: Transport information

### 14.1 UN number

ADR : 1263  
IMDG : 1263  
IATA : 1263

### 14.2 Proper shipping name

ADR : PAINT  
IMDG : PAINT  
IATA : PAINT

### 14.3 Transport hazard class

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

**ADR** : 3  
**IMDG** : 3  
**IATA** : 3

### 14.4 Packing group

#### ADR

Packaging group : III  
Classification Code : F1  
Hazard identification No : 33  
Labels : 3  
Tunnel restriction code : (D/E)

#### IMDG

Packaging group : III  
Labels : 3  
EmS Number : F-E, S-E

#### IATA

Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packaging group : III  
Labels : 3

### 14.5 Environmental hazards

### 14.6 Special precautions for user

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

no data available

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE A-31510 EN

Version 1.0

Revision Date 24.02.2014

Print Date 20.11.2018

### 15.2 Chemical Safety Assessment

no data available

### SECTION 16: Other information

#### Full text of R-Phrases

R11	Highly flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

#### Full text of H-Statements

H225	Highly flammable liquid and vapour.
H228	Flammable solid.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.