

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ULTRASTAR GX-2561

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number

GBK Gefahrgut Büro GmbH, Ingelheim, Germany:
From outside US: : (001) 352-323-3500
(First call in English, response in your language is possible)
US & Canada (toll free) : 1-800-5355-053

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids , Category 2	H225: Highly flammable liquid and vapour.
Serious eye damage , Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure , Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

Classification (67/548/EEC, 1999/45/EC)

Highly flammable	R11: Highly flammable.
Irritant	R36: Irritating to eyes. R67: Vapours may cause drowsiness and dizziness. R66: Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561


Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H225 Highly flammable liquid and vapour. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	Prevention: P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P240 Ground/bond container and receiving equipment. P261 Avoid breathing vapours. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER or doctor/ physician if you feel unwell. Storage: P403 + P235 Store in a well-ventilated place. Keep cool. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:
67-63-0 propan-2-ol

2.3 Other hazards

No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
propan-2-ol	67-63-0 200-661-7 01-2119457558-25	F; R11 Xi; R36 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	$\geq 25 - < 50$
ethyl acetate	141-78-6 205-500-4	F; R11 F; R11 Xi; R36 Xi; R36 R66 R66 R67 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	$\geq 25 - < 50$
ethanol	64-17-5 200-578-6 01-2119457610-43	F; R11	Flam. Liq. 2; H225 Eye Irrit. 2; H319	$\geq 3 - < 10$
butyl glycollate	7397-62-8 230-991-7 01-2119514685-36	R41	Repr. 2; H361 Eye Dam. 1; H318	$\geq 5 - < 10$
aluminium	7429-90-5 231-072-3	F; R11	Flam. Sol. 1; H228	< 10
acetone	67-64-1 200-662-2	F; R11 Xi; R36 R66 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	$\geq 1 - < 3$

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

	<p>Consult a physician. Show this safety data sheet to the doctor in attendance.</p> <p>Move the victim to fresh air. Do not leave the victim unattended.</p>
If inhaled	: Consult a physician after significant exposure. If unconscious place in recovery position and seek medical advice.
In case of skin contact	: If on skin, rinse well with water. If on clothes, remove clothes. Wash off immediately with soap and plenty of water.
In case of eye contact	: Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Immediately flush eye(s) with plenty of water.
If swallowed	: Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: No information available.
Risks	: No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: No information available.
-----------	-----------------------------

SECTION 5: Firefighting measures

5.1 Extinguishing media

ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

- Suitable extinguishing media : Dry sand, Special powder against metal fire
Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical
- Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self contained breathing apparatus for fire fighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Keep away from oxidising agents and strongly acid or alkaline materials. Never allow product to get in contact with water during storage. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m ³	2006-09-01	GB EH40
propan-2-ol	67-63-0	STEL	500 ppm 1,250 mg/m ³	2006-09-01	GB EH40
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
ethyl acetate	141-78-6	TWA	200 ppm	2005-04-06	GB EH40
ethyl acetate	141-78-6	STEL	400 ppm	2005-04-06	GB EH40
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m ³	2005-04-06	GB EH40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

Further information		Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	TWA (Inhalable)	10 mg/m ³	2011-12-01	GB EH40
Further information		The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
aluminium	7429-90-5	TWA (Respirable)	4 mg/m ³	2011-12-01	GB EH40
Further information		The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
aluminium	7429-90-5	TWA (Inhalable)	10 mg/m ³	2005-04-06	GB EH40
Further information		For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

		limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
aluminium	7429-90-5	TWA (Respirable)	4 mg/m ³	2005-04-06	GB EH40
Further information		For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
acetone	67-64-1	TWA	500 ppm 1,210 mg/m ³	2000-06-16	2000/39/EC
Further information		Indicative			
acetone	67-64-1	TWA	500 ppm 1,210 mg/m ³	2005-04-06	GB EH40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

acetone	67-64-1	STEL	1,500 ppm 3,620 mg/m ³	2005-04-06	GB EH40
---------	---------	------	--------------------------------------	------------	---------

DNEL:

propan-2-ol (67-63-0)

End Use: Workers

Exposure routes: Skin contact

Potential health effects: long term – systemic effects

Value: 888 mg/kg

DNEL:

propan-2-ol (67-63-0)

End Use: Workers

Exposure routes: Inhalation

Potential health effects: long term – systemic effects

Value: 500 mg/m³

DNEL:

propan-2-ol (67-63-0)

End Use: Consumers

Exposure routes: Ingestion

Potential health effects: long term – systemic effects

Value: 26 mg/kg

DNEL:

propan-2-ol (67-63-0)

End Use: Consumers

Exposure routes: Skin contact

Potential health effects: long term – systemic effects

Value: 319 mg/kg

DNEL:

propan-2-ol (67-63-0)

End Use: Consumers

Exposure routes: Inhalation

Potential health effects: long term – systemic effects

Value: 89 mg/m³

DNEL:

ethyl acetate (141-78-6)

End Use: Workers

Exposure routes: Inhalation

Potential health effects: short term – local effects

Value: 1468 mg/m³

DNEL:

ethyl acetate (141-78-6)

End Use: Workers

Exposure routes: Inhalation

Potential health effects: short term – systemic effects

Value: 1468 mg/m³

DNEL:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

ethyl acetate (141-78-6)

End Use: Workers
Exposure routes: Inhalation
Potential health effects: long term – local effects
Value: 734 mg/m³

DNEL:

ethyl acetate (141-78-6)

End Use: Workers
Exposure routes: Skin contact
Potential health effects: long term – systemic effects
Value: 63 mg/kg

DNEL:

ethyl acetate (141-78-6)

End Use: Workers
Exposure routes: Inhalation
Potential health effects: long term – systemic effects
Value: 734 mg/m³

DNEL:

ethyl acetate (141-78-6)

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: short term – local effects
Value: 734 mg/m³

DNEL:

ethyl acetate (141-78-6)

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: short term – systemic effects
Value: 734 mg/m³

DNEL:

ethyl acetate (141-78-6)

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: long term – local effects
Value: 367 mg/m³

DNEL:

ethyl acetate (141-78-6)

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: long term – systemic effects
Value: 37 mg/kg

DNEL:

ethyl acetate (141-78-6)

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: long term – systemic effects
Value: 367 mg/m³

DNEL:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

ethyl acetate (141-78-6)

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: long term – systemic effects
Value: 4.5 mg/kg

DNEL:

ethanol (64-17-5)

End Use: Workers
Exposure routes: Inhalation
Potential health effects: short term – local effects
Value: 1900 mg/m³

DNEL:

ethanol (64-17-5)

End Use: Workers
Exposure routes: Skin contact
Potential health effects: long term – systemic effects
Value: 343 mg/kg

DNEL:

ethanol (64-17-5)

End Use: Workers
Exposure routes: Inhalation
Potential health effects: long term – systemic effects
Value: 950 mg/m³

DNEL:

ethanol (64-17-5)

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: short term – local effects
Value: 950 mg/m³

DNEL:

ethanol (64-17-5)

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: long term – systemic effects
Value: 87 mg/kg

DNEL:

ethanol (64-17-5)

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: long term – systemic effects
Value: 206 mg/kg

DNEL:

ethanol (64-17-5)

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: long term – systemic effects
Value: 114 mg/m³

DNEL:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

butyl glycollate (7397-62-8) End Use: Workers
Exposure routes: Skin contact
Potential health effects: long term – systemic effects
Value: 34.7 mg/kg

DNEL:
butyl glycollate (7397-62-8) End Use: Workers
Exposure routes: Inhalation
Potential health effects: long term – systemic effects
Value: 21.2 mg/m³

DNEL:
butyl glycollate (7397-62-8) End Use: Consumers
Exposure routes: Ingestion
Potential health effects: long term – systemic effects
Value: 2 mg/kg

DNEL:
butyl glycollate (7397-62-8) End Use: Consumers
Exposure routes: Skin contact
Potential health effects: long term – systemic effects
Value: 20.8 mg/kg

DNEL:
butyl glycollate (7397-62-8) End Use: Consumers
Exposure routes: Inhalation
Potential health effects: long term – systemic effects
Value: 43.5 mg/m³

DNEL:
butyl glycollate (7397-62-8) End Use: Consumers
Exposure routes: Inhalation
Potential health effects: long term – local effects
Value: 43.5 mg/m³

DNEL:
butyl glycollate (7397-62-8) End Use: Consumers
Exposure routes: Skin contact
Potential health effects: long term – local effects
Value: 0.28 mg/cm²

DNEL:
acetone (67-64-1) End Use: Workers
Exposure routes: Skin contact
Potential health effects: long term – systemic effects
Value: 186 mg/kg

DNEL:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

acetone (67-64-1) End Use: Workers
Exposure routes: Inhalation
Potential health effects: long term – systemic effects
Value: 1210 mg/m³

DNEL:
acetone (67-64-1) End Use: Consumers
Exposure routes: Ingestion
Potential health effects: long term – systemic effects
Value: 62 mg/kg

DNEL:
acetone (67-64-1) End Use: Consumers
Exposure routes: Skin contact
Potential health effects: long term – systemic effects
Value: 62 mg/kg

DNEL:
acetone (67-64-1) End Use: Consumers
Exposure routes: Inhalation
Potential health effects: long term – systemic effects
Value: 200 mg/m³

PNEC: :
propan-2-ol (67-63-0) Soil
Value: 28 mg/kg

PNEC: :
propan-2-ol (67-63-0) Fresh water
Value: 140.9 mg/l

PNEC: :
propan-2-ol (67-63-0) Fresh water sediment
Value: 552 mg/kg

PNEC: :
propan-2-ol (67-63-0) Marine water
Value: 140.9 mg/l

PNEC: :
propan-2-ol (67-63-0) Marine sediment
Value: 552 mg/kg

PNEC: :
propan-2-ol (67-63-0) STP
Value: 2251 mg/l

PNEC: :

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

ethyl acetate (141-78-6)	:	Soil Value: 0.24 mg/kg
PNEC: ethyl acetate (141-78-6)	:	STP Value: 650 mg/l
PNEC: ethanol (64-17-5)	:	Soil Value: 0.63 mg/kg
PNEC: ethanol (64-17-5)	:	Fresh water Value: 0.96 mg/l
PNEC: ethanol (64-17-5)	:	Fresh water sediment Value: 3.6 mg/kg
PNEC: ethanol (64-17-5)	:	Marine water Value: 0.79 mg/l
PNEC: ethanol (64-17-5)	:	Marine sediment Value: 2.9 mg/kg
PNEC: ethanol (64-17-5)	:	STP Value: 580 mg/l
PNEC: butyl glycollate (7397-62-8)	:	Soil Value: 0.0112 mg/kg
PNEC: butyl glycollate (7397-62-8)	:	Sediment Value: 0.203 mg/kg
PNEC: butyl glycollate (7397-62-8)	:	STP Value: 232 mg/l
PNEC: butyl glycollate (7397-62-8)	:	Water Value: 0.05 mg/l
PNEC:	:	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

acetone (67-64-1)	:	Soil Value: 29.5 mg/kg
PNEC: acetone (67-64-1)	:	Fresh water Value: 10.6 mg/l
PNEC: acetone (67-64-1)	:	Fresh water sediment Value: 30.4 mg/kg
PNEC: acetone (67-64-1)	:	Marine water Value: 1.06 mg/l
PNEC: acetone (67-64-1)	:	Marine sediment Value: 3.04 mg/kg

8.2 Exposure controls

Personal protective equipment

- | | | |
|-----------------|---|--|
| Eye protection | : | Eye wash bottle with pure water
Wear face-shield and protective suit for abnormal processing problems. |
| | : | Goggles |
| Hand protection | : | |
| Material | : | Solvent-resistant gloves (butyl-rubber) |
| Remarks | : | The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

: Use suitable breathing protection if workplace concentration requires.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Water

:
: The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : silver
Odour : characteristic
pH : no data available
Freezing point : no data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

	: 46 °C
Flash point	: -4 °C
Bulk density	: no data available
Flammability (solid, gas)	: no data available
Auto-flammability	: no data available
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Density	: no data available
Water solubility	: no data available
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, dynamic	: no data available
Viscosity, kinematic	: no data available
Flow time	: no data available

9.2 Other information

no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Do not allow evaporation to dryness.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : no data available
Other information : no data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

no data available

Skin corrosion/irritation

Product

Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product

May cause irreversible eye damage.

Respiratory or skin sensitisation

no data available

Carcinogenicity

no data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

Toxicity to reproduction/fertility

no data available

Reprod.Tox./Development/Teratogenicity

no data available

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

no data available

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

no data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

no data available

12.6 Other adverse effects

Product:

Additional ecological information : no data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADR : 1210
IMDG : 1210
IATA : 1210

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

14.2 Proper shipping name

ADR : PRINTING INK
IMDG : PRINTING INK
IATA : PRINTING INK

14.3 Transport hazard class

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packaging group : II
Classification Code : F1
Hazard identification No : 33
Labels : 3
Tunnel restriction code : (D/E)

IMDG
Packaging group : II
Labels : 3
EmS Number : F-E, S-D

IATA
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packaging group : II
Labels : 3

14.5 Environmental hazards

14.6 Special precautions for user

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

no data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

no data available

15.2 Chemical Safety Assessment

no data available

SECTION 16: Other information

Full text of R-Phrases

R11	Highly flammable.
R36	Irritating to eyes.
R41	Risk of serious damage to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H228	Flammable solid.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ULTRASTAR GX-2561

Version 1.1

Revision Date 21.03.2014

Print Date 20.11.2018
