

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : STAPA NDF 200 Aluminum Paste

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

#### 1.4 Emergency telephone number

GBK Gefahrgut Büro GmbH, Ingelheim, Germany:  
From outside US: : (001) 352-323-3500  
(First call in English, response in your language is possible)  
US & Canada (toll free) : 1-800-5355-053

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable solids , Category 1 H228: Flammable solid.  
Chronic aquatic toxicity , Category 3 H412: Harmful to aquatic life with long lasting effects.

##### Classification (67/548/EEC, 1999/45/EC)

Highly flammable R11: Highly flammable.  
Dangerous for the environment R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H228 H412	Flammable solid. Harmful to aquatic life with long lasting effects.
Precautionary statements	:	<b>Prevention:</b> P210  P273 <b>Response:</b> P370 + P378  P370 + P378 <b>Disposal:</b> P501	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid release to the environment.  In case of fire: Use for extinction: Special powder for metal fires. In case of fire: Use for extinction: Dry sand.  Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
aluminium	7429-90-5 231-072-3	F; R11	Flam. Sol. 1; H228	>= 50 - <= 100
Naphtha (petroleum), hydrotreated heavy	64742-48-9 265-150-3	Xn; R65	Asp. Tox. 1; H304 Asp. Tox. 1; H304	>= 10 - < 20
Solvent naphtha (petroleum), light arom.	64742-95-6 265-199-0	Xn; R65 Xi; R37 N; R51/53 R10	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H335, H336	>= 2.5 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

		R66 R67	Aquatic Chronic 2; H411	
--	--	------------	----------------------------	--

For the full text of the R-phrases mentioned in this Section, see Section 16.  
For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Move the victim to fresh air.  
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.  
Wash off immediately with soap and plenty of water.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.  
Immediately flush eye(s) with plenty of water.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

**STAPA NDF 200 Aluminum Paste**

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media : Dry sand, Special powder against metal fire
- Unsuitable extinguishing media : ABC powder, Carbon dioxide (CO<sub>2</sub>), Water, Foam

**5.2 Special hazards arising from the substance or mixture**

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

- Special protective equipment for firefighters : Use personal protective equipment.

Wear self contained breathing apparatus for fire fighting if necessary.

- Further information : Use a water spray to cool fully closed containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

- Personal precautions : Avoid dust formation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Use personal protective equipment.

**6.2 Environmental precautions**

- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.

## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Do not flush with water.  
Keep in suitable, closed containers for disposal.

Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

Further information on storage conditions : Protect from humidity and water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

- Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Keep away from oxidising agents and strongly acid or alkaline materials. Never allow product to get in contact with water during storage. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- German storage class : 4.1B, Flammable solid hazardous materials
- Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
aluminium	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	2011-12-01	GB EH40
Further information		The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
aluminium	7429-90-5	TWA (Respirable)	4 mg/m <sup>3</sup>	2011-12-01	GB EH40
Further information		The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
aluminium	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	2005-04-06	GB EH40

## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used.</p>				
aluminium	7429-90-5	TWA (Respirable)	4 mg/m <sup>3</sup>	2005-04-06	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters</p>				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

	the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used
--	---

**DNEL:**

Naphtha (petroleum),  
hydrotreated heavy (64742-48-9)

End Use: Workers  
Exposure routes: Skin contact  
Potential health effects: long term – systemic effects  
Value: 300 mg/kg

**DNEL:**

Naphtha (petroleum),  
hydrotreated heavy (64742-48-9)

End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: long term – systemic effects  
Value: 300 mg/kg

**DNEL:**

Naphtha (petroleum),  
hydrotreated heavy (64742-48-9)

End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: long term – systemic effects  
Value: 300 mg/kg

**DNEL:**

Naphtha (petroleum),  
hydrotreated heavy (64742-48-9)

End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: long term – systemic effects  
Value: 900 mg/m<sup>3</sup>

**DNEL:**

Solvent naphtha (petroleum),  
light arom. (64742-95-6)

End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: long term – systemic effects  
Value: 11 mg/kg

**DNEL:**

Solvent naphtha (petroleum),  
light arom. (64742-95-6)

End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: long term – systemic effects  
Value: 11 mg/kg

**DNEL:**

Solvent naphtha (petroleum),  
light arom. (64742-95-6)

End Use: Consumers  
Exposure routes: Inhalation



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

Potential health effects: long term – systemic effects  
Value: 32 mg/m<sup>3</sup>

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water

: Goggles

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

The exact break through time can be obtained from the protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

#### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

If the product contaminates rivers and lakes or drains inform respective authorities.

Water

:

:

: The product should not be allowed to enter drains, water courses or the soil.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: Pasty solid
Colour	: silver
Odour	: characteristic
pH	: no data available
Freezing point	: no data available
Boiling point/boiling range	: 162 °C
Flash point	: 45 °C
Bulk density	: no data available
Flammability (solid, gas)	: no data available
Auto-flammability	: no data available
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Density	: no data available
Water solubility	: no data available
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, dynamic	: no data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

Viscosity, kinematic : no data available

Flow time : no data available

### 9.2 Other information

no data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Do not allow evaporation to dryness.

### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents

### 10.6 Hazardous decomposition products

Other information : no data available

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

no data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

### **Skin corrosion/irritation**

no data available

### **Serious eye damage/eye irritation**

no data available

### **Respiratory or skin sensitisation**

no data available

### **Carcinogenicity**

no data available

### **Toxicity to reproduction/fertility**

no data available

### **Reprod.Tox./Development/Teratogenicity**

no data available

### **STOT - single exposure**

no data available

### **STOT - repeated exposure**

no data available

### **Aspiration toxicity**

no data available

### **Further information**

#### **Product**

no data available

## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

no data available

#### 12.2 Persistence and degradability

no data available

#### 12.3 Bioaccumulative potential

no data available

#### 12.4 Mobility in soil

no data available

#### 12.5 Results of PBT and vPvB assessment

no data available

#### 12.6 Other adverse effects

**Product:**

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

---

### SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

#### 13.1 Waste treatment methods

Product

: The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

---

chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14: Transport information

#### 14.1 UN number

**ADR** : 1325  
**IMDG** : 1325  
**IATA** : 1325

#### 14.2 Proper shipping name

**ADR** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)

**IMDG** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)

**IATA** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)

#### 14.3 Transport hazard class

**ADR** : 4.1  
**IMDG** : 4.1  
**IATA** : 4.1

#### 14.4 Packing group

**ADR**

Packaging group : II  
Classification Code : F1  
Hazard identification No : 40  
Labels : 4.1  
Tunnel restriction code : (E)

**IMDG**

Packaging group : II

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

Labels : 4.1  
EmS Number : F-G, S-G

### IATA

Packing instruction (cargo aircraft) : 448

Packing instruction (passenger aircraft) : 445

Packing instruction (LQ) : Y441

Packaging group : II

Labels : 4.1

### 14.5 Environmental hazards

IMDG :

### 14.6 Special precautions for user

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

no data available

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2 Chemical Safety Assessment

no data available

## SECTION 16: Other information

### Full text of R-Phrases

R10	Flammable.
R11	Highly flammable.
R37	Irritating to respiratory system.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## STAPA NDF 200 Aluminum Paste

Version 1.1

Revision Date 09.04.2014

Print Date 20.11.2018

---

R65 Harmful: may cause lung damage if swallowed.

### Full text of H-Statements

H226 Flammable liquid and vapour.  
H228 Flammable solid.  
H304 May be fatal if swallowed and enters airways.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.