

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version 1.1      Revision Date: 26.03.2018      SDS Number: 102000000675      Print Date: 20.11.2018  
Date of first issue: 12.03.2014

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SILVERDREAM PRISMATIC H-115002  
Product code : 053002S8068 053002S8068

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
  
Telephone : +499152770  
  
Telefax : +499152777008  
  
E-mail address of person responsible for the SDS : msds.eckart@altana.com

#### 1.4 Emergency telephone number

GBK Gefahrgut Büro GmbH, Ingelheim, Germany:  
From outside US : (001) 352-323-3500  
(First call in English, response in your language is possible)  
US & Canada (toll free) : 1-800-5355-053

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2      H225: Highly flammable liquid and vapour.  
Eye irritation, Category 2      H319: Causes serious eye irritation.  
Specific target organ toxicity - single exposure, Category 3, Central nervous system      H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version 1.1      Revision Date: 26.03.2018      SDS Number: 102000000675      Print Date: 20.11.2018  
Date of first issue: 12.03.2014

Hazard pictograms	:	 
Signal word	:	Danger
Hazard statements	:	H225      Highly flammable liquid and vapour. H319      Causes serious eye irritation. H336      May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066      Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233      Keep container tightly closed. P261      Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P280      Wear protective gloves/ protective clothing/ eye protection/ face protection. <b>Response:</b> P303 + P361 + P353      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378      In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

n-butyl acetate  
acetone

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1	Flam. Liq. 3; H226 STOT SE 3; H336	>= 50 - <= 100
acetone	67-64-1 200-662-2	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 20 - < 25

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version 1.1      Revision Date: 26.03.2018      SDS Number: 102000000675      Print Date: 20.11.2018  
Date of first issue: 12.03.2014

---

STOT SE 3; H336

For explanation of abbreviations see section 16.

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version	Revision Date:	SDS Number:	Print Date: 20.11.2018
1.1	26.03.2018	102000000675	Date of first issue: 12.03.2014

---

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version 1.1      Revision Date: 26.03.2018      SDS Number: 102000000675      Print Date: 20.11.2018  
Date of first issue: 12.03.2014

Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis (Version Date)
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40 (2005-04-06)
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40 (2005-04-06)
acetone	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
Further information	Indicative			
		TWA	500 ppm 1,210 mg/m <sup>3</sup>	GB EH40 (2005-04-06)
		STEL	1,500 ppm 3,620 mg/m <sup>3</sup>	GB EH40 (2005-04-06)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version  
1.1

Revision Date:  
26.03.2018

SDS Number:  
102000000675

Print Date: 20.11.2018  
Date of first issue: 12.03.2014

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	short term – systemic effects	960 mg/m <sup>3</sup>
	Workers	Inhalation	long term – systemic effects	480 mg/m <sup>3</sup>
	Consumers	Inhalation	short term – systemic effects	859.7 mg/m <sup>3</sup>
	Consumers	Inhalation	long term – systemic effects	102.34 mg/m <sup>3</sup>
	Consumers	Inhalation	long term – local effects	102.34 mg/m <sup>3</sup>
	Workers	Inhalation	long term – local effects	480 mg/m <sup>3</sup>
	Workers	Inhalation	short term – local effects	960 mg/m <sup>3</sup>
	Consumers	Inhalation	short term – local effects	859.7 mg/m <sup>3</sup>
acetone	Workers	Skin contact	long term – systemic effects	186 mg/kg
	Workers	Inhalation	long term – systemic effects	1210 mg/m <sup>3</sup>
	Consumers	Ingestion	long term – systemic effects	62 mg/kg
	Consumers	Skin contact	long term – systemic effects	62 mg/kg
	Consumers	Inhalation	long term – systemic effects	200 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0.0903 mg/kg
	Soil	0.0903 mg/kg
	Fresh water	0.18 mg/l
	Fresh water	0.18 mg/l
	Fresh water sediment	0.981 mg/kg
	Fresh water sediment	0.981 mg/kg
	STP	35.6 mg/l
	STP	35.6 mg/l
	Marine water	0.018 mg/l
	Marine water	0.018 mg/l
	Marine sediment	0.0981 mg/kg
acetone	Marine sediment	0.0981 mg/kg
	Soil	29.5 mg/kg
	Fresh water	10.6 mg/l
	Fresh water sediment	30.4 mg/kg
	Marine water	1.06 mg/l
Marine sediment	3.04 mg/kg	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version	Revision Date:	SDS Number:	Print Date: 20.11.2018
1.1	26.03.2018	102000000675	Date of first issue: 12.03.2014

---

### 8.2 Exposure controls

#### Personal protective equipment

- Eye protection : Wear face-shield and protective suit for abnormal processing problems.
- Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : silver
- Odour : characteristic
- Odour Threshold : No data available
- pH : No data available
- Freezing point : No data available
- Boiling point/boiling range : 124 °C
- Flash point : -4 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Self-ignition : No data available
- Auto-ignition temperature : No data available
- Smoldering temperature : No data available
- Decomposition temperature : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version	Revision Date:	SDS Number:	Print Date: 20.11.2018
1.1	26.03.2018	102000000675	Date of first issue: 12.03.2014

---

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.9 g/cm<sup>3</sup>

Bulk density : No data available

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Flow time : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version	Revision Date:	SDS Number:	Print Date: 20.11.2018
1.1	26.03.2018	102000000675	Date of first issue: 12.03.2014

---

### 10.5 Incompatible materials

### 10.6 Hazardous decomposition products

Contact with water or humid air : This information is not available.

Thermal decomposition : This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

#### Product:

Remarks: May cause skin irritation in susceptible persons.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Product:

Remarks: Eye irritation

#### Respiratory or skin sensitisation

##### Skin sensitisation

Not classified based on available information.

##### Respiratory sensitisation

Not classified based on available information.

##### Germ cell mutagenicity

Not classified based on available information.

##### Carcinogenicity

Not classified based on available information.

##### Reproductive toxicity

Not classified based on available information.

##### STOT - single exposure

May cause drowsiness or dizziness.

##### STOT - repeated exposure

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version 1.1      Revision Date: 26.03.2018      SDS Number: 102000000675      Print Date: 20.11.2018  
Date of first issue: 12.03.2014

---

### Aspiration toxicity

Not classified based on available information.

### Further information

#### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version 1.1      Revision Date: 26.03.2018      SDS Number: 102000000675      Print Date: 20.11.2018  
Date of first issue: 12.03.2014

---

In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

---

### SECTION 14: Transport information

#### 14.1 UN number

ADR : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

#### 14.2 UN proper shipping name

ADR : PAINT  
IMDG : PAINT, CLASSIFIED ACCORDING TO 2.3.2.2 IMDG-CODE  
IATA : Paint, classified according to 3.3.3.1 IATA-DGR

#### 14.3 Transport hazard class(es)

ADR : 3  
IMDG : 3  
IATA : 3

#### 14.4 Packing group

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction : 355

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version 1.1      Revision Date: 26.03.2018      SDS Number: 102000000675      Print Date: 20.11.2018  
Date of first issue: 12.03.2014

---

(passenger aircraft)  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

**ADR**  
Environmentally hazardous : no

**IMDG**  
Marine pollutant : no

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

### 15.2 Chemical safety assessment

This information is not available.

---

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.

### Full text of other abbreviations

Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
2000/39/EC / TWA : Limit Value - eight hours  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILVERDREAM PRISMATIC H-115002

Version	Revision Date:	SDS Number:	Print Date: 20.11.2018
1.1	26.03.2018	102000000675	Date of first issue: 12.03.2014

---

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN