

STAPA HYDROXAL E 4000 Aluminium Paste

Version Revision Date: SDS Number: Date of last issue: -
1.1 03/26/2018 102000024321 Date of first issue: 03/21/2018

SECTION 1. IDENTIFICATION

Product name : STAPA HYDROXAL E 4000 Aluminium Paste
Product code : 022239KA0

Manufacturer or supplier's details

Company name of supplier : ECKART GmbH

Address : Guentersthal 4
 Hartenstein 91235

Telephone : +499152770

Telefax : +499152777008

Emergency telephone : CHEMTREC: 800-424-9300
 CHEMTREC: 1-703-527-3387 (International)

GBK Gefahrgut Buero GmbH, Ingelheim, Germany:
From outside US: (001) 352-323-3500
(First call in English, response in your language is possible)
US & Canada (toll free):1-800-5355-053

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Specific target organ : Category 2
systemic toxicity - repeated
exposure

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H373 May cause damage to organs through prolonged or
repeated exposure.

STAPA HYDROXAL E 4000 Aluminium Paste

Version 1.1 Revision Date: 03/26/2018 SDS Number: 102000024321 Date of last issue: -
 Date of first issue: 03/21/2018

Precautionary Statements : **Prevention:**
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

Response:
 P314 Get medical advice/ attention if you feel unwell.

Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous ingredients which must be listed on the label:
 1H-Imidazole-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-
 Phosphonic acid, P-octyl-

Other hazards
 None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum	7429-90-5	>= 50 - < 70
1H-Imidazole-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-	95-38-5	>= 3 - < 5
Phosphonic acid, P-octyl-	4724-48-5	>= 1 - < 3

SECTION 4. FIRST AID MEASURES

General advice : Take the victim into fresh air.
 Do not leave the victim unattended.
 No hazards which require special first aid measures.

If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 If eye irritation persists, consult a specialist.

STAPA HYDROXAL E 4000 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.1	03/26/2018	102000024321	Date of first issue: 03/21/2018

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : May cause damage to organs through prolonged or repeated exposure.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry sand
Special powder against metal fire

Unsuitable extinguishing media : ABC powder
Carbon dioxide (CO₂)
Water
Foam

Specific hazards during fire fighting : Contact with water liberates extremely flammable gas (hydrogen).

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Use personal protective equipment.
Avoid dust formation.

Methods and materials for containment and cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Sweep up and shovel.
Do not flush with water.
Keep in suitable, closed containers for disposal.

STAPA HYDROXAL E 4000 Aluminium Paste

Version 1.1 Revision Date: 03/26/2018 SDS Number: 102000024321 Date of last issue: -
 Date of first issue: 03/21/2018

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Earthing of containers and apparatuses is essential.
Take measures to prevent the build up of electrostatic charge.
Use explosion-proof equipment.
Store in original container.
Keep containers tightly closed in a cool, well-ventilated place.
Keep away from sources of ignition - No smoking.
Keep container closed when not in use.
- Electrical installations / working materials must comply with the technological safety standards.
- Technical measures/Precautions :
- Materials to avoid : Do not store near acids.
Do not store together with oxidizing and self-igniting products.
Keep away from oxidizing agents and strongly acid or alkaline materials.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m ³	NIOSH REL

STAPA HYDROXAL E 4000 Aluminium Paste

Version 1.1 Revision Date: 03/26/2018 SDS Number: 102000024321 Date of last issue: -
 Date of first issue: 03/21/2018

		TWA (total dust)	15 mg/m ³	OSHA Z-3
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable fraction)	1 mg/m ³	ACGIH
		TWA	5 mg/m ³ (Aluminum)	NIOSH REL
		TWA (Total)	15 mg/m ³ (Aluminum)	OSHA P0
		TWA (Respirable fraction)	5 mg/m ³ (Aluminum)	OSHA P0
		TWA (total dust)	15 mg/m ³ (Aluminum)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³ (Aluminum)	OSHA Z-1
		TWA (Total dust)	15 mg/m ³ (Aluminum)	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³ (Aluminum)	OSHA P0
		TWA (welding fumes)	5 mg/m ³ (Aluminum)	NIOSH REL
		TWA (pyro powders)	5 mg/m ³ (Aluminum)	NIOSH REL
		TWA (Respirable fraction)	1 mg/m ³ (Aluminum)	ACGIH
		TWA (Fumes)	5 mg/m ³	OSHA P0

Hazardous components without workplace control parameters

Ingredients	CAS-No.
1H-Imidazole-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-	95-38-5

STAPA HYDROXAL E 4000 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.1	03/26/2018	102000024321	Date of first issue: 03/21/2018

Phosphonic acid, P-octyl-	4724-48-5
---------------------------	-----------

Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

Eye protection : Goggles
Safety glasses

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Pasty solid
 Color : silver
 Odor : characteristic
 Odor Threshold : No data available
 pH : No data available
 Melting point/freezing point : No data available
 Initial boiling point and boiling range : No data available
 Flash point : No data available
 Evaporation rate : No data available
 Flammability (solid, gas) : Combustible Solids

Auto-flammability : not auto-flammable
 Upper explosion limit / Upper flammability limit : No data available
 Lower explosion limit / Lower flammability limit : No data available
 Vapor pressure : No data available
 Relative density : No data available
 Solubility(ies) : No data available
 Partition coefficient: n-octanol/water : No data available
 Autoignition temperature : No data available
 Decomposition temperature : No data available
 Viscosity : No data available
 Explosive properties : Not explosive

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

STAPA HYDROXAL E 4000 Aluminium Paste

Version 1.1 Revision Date: 03/26/2018 SDS Number: 102000024321 Date of last issue: -
Date of first issue: 03/21/2018

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : Contact with acids and alkalis may release hydrogen.
Stable under recommended storage conditions.

Conditions to avoid : Do not allow evaporation to dryness.

No data available

Incompatible materials : Acids
Bases
Oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Ingredients:**Phosphonic acid, P-octyl-:**

Acute oral toxicity : (Rat): 500 - 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**1H-Imidazole-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-:**

Remarks: Extremely corrosive and destructive to tissue.

Phosphonic acid, P-octyl-:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:**1H-Imidazole-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-:**

Remarks: May cause irreversible eye damage.

STAPA HYDROXAL E 4000 Aluminium Paste

Version 1.1 Revision Date: 03/26/2018 SDS Number: 102000024321 Date of last issue: -
Date of first issue: 03/21/2018

Phosphonic acid, P-octyl-:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information**Ingredients:****1H-Imidazole-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-:**

Remarks: No data available

STAPA HYDROXAL E 4000 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.1	03/26/2018	102000024321	Date of first issue: 03/21/2018

Phosphonic acid, P-octyl-:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****1H-Imidazole-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

Ingredients:**1H-Imidazole-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-:**Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.**Phosphonic acid, P-octyl-:**

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : In accordance with local and national regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
In accordance with local and national regulations.

STAPA HYDROXAL E 4000 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.1	03/26/2018	102000024321	Date of first issue: 03/21/2018

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not permitted for transport

IMDG-Code

Not regulated as a dangerous good

Remarks

: Not classified as dangerous in the meaning of transport regulations.
Due to the risk of hydrogen development we recommend to refrain from airfreighting this/these product(s).

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Aluminum	7429-90-5	>= 50 - < 70 %
----------	-----------	----------------

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

STAPA HYDROXAL E 4000 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.1	03/26/2018	102000024321	Date of first issue: 03/21/2018

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

US State Regulations

Massachusetts Right To Know

Aluminum	7429-90-5
Castor oil, ethoxylated	61791-12-6
Phosphonic acid, P-octyl-	4724-48-5

Pennsylvania Right To Know

Aluminum	7429-90-5
Water	7732-18-5
1H-Imidazole-1-ethanol, 2-(8-heptadecen-1-yl)-4,5-dihydro-	95-38-5

California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Aluminum	7429-90-5
----------	-----------

California Permissible Exposure Limits for Chemical Contaminants

Aluminum	7429-90-5
----------	-----------

The ingredients of this product are reported in the following inventories:

DSL : This product contains one or several components listed in the Canadian NDSL.

STAPA HYDROXAL E 4000 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.1	03/26/2018	102000024321	Date of first issue: 03/21/2018

TSCA : On TSCA Inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 NIOSH REL : USA. NIOSH Recommended Exposure Limits
 OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
 OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
 ACGIH / TWA : 8-hour, time-weighted average
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
 OSHA P0 / TWA : 8-hour time weighted average
 OSHA Z-1 / TWA : 8-hour time weighted average
 OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for

STAPA HYDROXAL E 4000 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.1	03/26/2018	102000024321	Date of first issue: 03/21/2018

Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/26/2018

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8