

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.3	13.04.2017	102000000226	Date of first issue: 23.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STAPA IL HYDROLAN 701 55900/G Aluminium Paste
Material number : 005735HV0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

GBK Gefahrgut Büro GmbH, Ingelheim, Germany:
From outside US: : (001) 352-323-3500
(First call in English, response in your language is possible)
US & Canada (toll free) : 1-800-5355-053

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable solids, Category 1	H228: Flammable solid.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

Classification (67/548/EEC, 1999/45/EC)

Highly flammable	R11: Highly flammable.
------------------	------------------------

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version 1.3	Revision Date: 13.04.2017	SDS Number: 102000000226	Print Date: 19.11.2018 Date of first issue: 23.01.2014
----------------	------------------------------	-----------------------------	---

Irritant

R36: Irritating to eyes.

R67: Vapours may cause drowsiness and
dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H228 Flammable solid.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks,
open flames and other ignition sources. No
smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/
vapours/ spray.
P271 Use only outdoors or in a well-ventilated
area.
Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh
air and keep comfortable for breathing. Call
a POISON CENTER/doctor if you feel
unwell.
P337 + P313 If eye irritation persists: Get medical advice/
attention.
P370 + P378 In case of fire: Use for extinction: Special
powder for metal fires.
P370 + P378 In case of fire: Use for extinction: Dry sand.

Hazardous components which must be listed on the label:

67-63-0 isopropanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent,
bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of
0.1% or higher.

No information available.

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version 1.3 Revision Date: 13.04.2017 SDS Number: 102000000226 Print Date: 19.11.2018
Date of first issue: 23.01.2014

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5 231-072-3 01-2119529243-45	F; R11	Flam. Sol. 1; H228	>= 50 - <= 100
isopropanol	67-63-0 200-661-7 01-2119457558-25	F; R11 Xi; R36 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 25 - < 50
N-(3- (trimethoxysilyl)pro pyl)ethylenediamin e	1760-24-3 217-164-6 01-2119970215-39	N; R51/53 Xn; R20 Xi; R41 Xi; R43	Acute Tox. 4; H332 Skin Sens. 1; H317 Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 0,1 - < 0,25

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical
advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Immediately flush eye(s) with plenty of water.

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.3	13.04.2017	102000000226	Date of first issue: 23.01.2014

Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand
Special powder against metal fire

Unsuitable extinguishing media : Water
Foam
Carbon dioxide (CO₂)
ABC powder

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.3	13.04.2017	102000000226	Date of first issue: 23.01.2014

Use personal protective equipment.
Use personal protective equipment.
Avoid dust formation.
Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).

Do not flush with water.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.
Avoid dust formation.
Ensure adequate ventilation.

Avoid formation of respirable particles.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the
application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national
regulations.

Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. Take
measures to prevent the build up of electrostatic charge. Use
explosion-proof equipment.

Avoid dust formation. Keep away from open flames, hot
surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.3	13.04.2017	102000000226	Date of first issue: 23.01.2014

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Storage class (TRGS 510) : 4.1B, Flammable solid hazardous materials

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis (Version Date)
aluminium powder (stabilised)	7429-90-5	NGV (Total)	5 mg/m ³	SE AFS (2011-12-16)
Further information	Inhalable dust refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.3 and having sampling characteristics as specified in paragraph 5.1. Respirable dust refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.11 and having sampling characteristics as specified in paragraph 5.3. Total dust refers to all the particles (aerosols) trapped in a filter in the sampling apparatus described in Methods, Sampling of total dust and respirable dust, method nr 1010, published by the National Board of Occupational Safety and Health, now Work Environment Authority. The filter diameter shall normally be 37 mm but can also be 25 mm. Despite its name, not the total amount of airborne particles is measured by this method.			
aluminium powder	7429-90-5	NGV	2 mg/m ³	SE AFS

**STAPA IL HYDROLAN 701 55900/G Aluminium
Paste**

Version 1.3 Revision Date: 13.04.2017 SDS Number: 102000000226 Print Date: 19.11.2018
Date of first issue: 23.01.2014

(stabilised)		(Respirable)		(2011-12-16)
Further information	Inhalable dust refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.3 and having sampling characteristics as specified in paragraph 5.1. Respirable dust refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.11 and having sampling characteristics as specified in paragraph 5.3. Total dust refers to all the particles (aerosols) trapped in a filter in the sampling apparatus described in Methods, Sampling of total dust and respirable dust, method nr 1010, published by the National Board of Occupational Safety and Health, now Work Environment Authority. The filter diameter shall normally be 37 mm but can also be 25 mm. Despite its name, not the total amount of airborne particles is measured by this method.			
isopropanol	67-63-0	NGV	150 ppm 350 mg/m3	SE AFS (2005-06-13)
isopropanol	67-63-0	KTV	250 ppm 600 mg/m3	SE AFS (2005-06-13)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium (7429-90-5)	Workers	Inhalation	long term – local effects	3,72 mg/m3
	Consumers	Oral	long term – systemic effects	3,95 mg/kg
propan-2-ol (67-63-0)	Workers	Skin contact	long term – systemic effects	888 mg/kg
	Workers	Inhalation	long term – systemic effects	500 mg/m3
	Consumers	Ingestion	long term – systemic effects	26 mg/kg
	Consumers	Skin contact	long term – systemic effects	319 mg/kg
N-(3-(trimethoxysilyl)propyl) ethylenediamine (1760-24-3)	Consumers	Inhalation	long term – systemic effects	89 mg/m3
	Workers	Inhalation	long term – systemic effects	35,5 mg/m3
	Workers	Skin contact	long term – systemic effects	5 mg/kg
	Workers	Skin contact	short term – systemic effects	5 mg/kg
	Consumers	Oral	long term – systemic	2,5 mg/kg

**STAPA IL HYDROLAN 701 55900/G Aluminium
Paste**

Version 1.3 Revision Date: 13.04.2017 SDS Number: 102000000226 Print Date: 19.11.2018
Date of first issue: 23.01.2014

			effects	
	Consumers	Inhalation	long term – systemic effects	8,7 mg/m ³
	Consumers	Skin contact	long term – systemic effects	2,5 mg/kg
	Consumers	Skin contact	short term – systemic effects	17 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium (7429-90-5)	Fresh water	0,0749 mg/l
	clarification plant	20 mg/l
propan-2-ol (67-63-0)	Soil	28 mg/kg
	Fresh water	140,9 mg/l
	Fresh water sediment	552 mg/kg
	Marine water	140,9 mg/l
	Marine sediment	552 mg/kg
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	STP	2251 mg/l
	Fresh water	0,062 mg/l
	Marine water	0,0062 mg/l
	clarification plant	25 mg/l
	Fresh water sediment	0,22 mg/kg
	Marine sediment	0,022 mg/kg
	Soil	0,0085 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.3	13.04.2017	102000000226	Date of first issue: 23.01.2014

gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Long sleeved clothing
Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

In the case of dust or aerosol formation use respirator with an approved filter.

Environmental exposure controls

Water : The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: Pasty solid
Colour	: silver
Odour	: solvent-like
Odour Threshold	: No data available
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 82 °C
Flash point	: 13 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: not auto-flammable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1,3 - 2,0 g/cm ³
Bulk density	: No data available

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.3	13.04.2017	102000000226	Date of first issue: 23.01.2014

Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not explosive Vapours may form explosive mixture with air.
Oxidizing properties	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.
Contact with acids and alkalis may release hydrogen.
Mixture reacts slowly with water resulting in evolution of hydrogen.
Vapours may form explosive mixture with air.

Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents
Highly halogenated compounds

10.6 Hazardous decomposition products

Contact with water or humid air : This information is not available.

Thermal decomposition : This information is not available.

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version 1.3 Revision Date: 13.04.2017 SDS Number: 102000000226 Print Date: 19.11.2018
Date of first issue: 23.01.2014

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

7429-90-5:

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

67-63-0:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

1760-24-3:

Acute oral toxicity : LD50 (Rat): ca. 2.400 mg/kg
Acute inhalation toxicity : LC50: 1,49 - 2,44 mg/l
Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks: Eye irritation

Respiratory or skin sensitisation

Product:

Result: Does not cause skin sensitisation.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.3	13.04.2017	102000000226	Date of first issue: 23.01.2014

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Remarks: No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number

ADR : UN 1325

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version 1.3 Revision Date: 13.04.2017 SDS Number: 102000000226 Print Date: 19.11.2018
Date of first issue: 23.01.2014

IMDG : UN 1325

IATA : UN 1325

14.2 UN proper shipping name

ADR : FLAMMABLE SOLID, ORGANIC, N.O.S.
(Aluminium pigment paste)

IMDG : FLAMMABLE SOLID, ORGANIC, N.O.S.
(Aluminium pigment paste)

IATA : Flammable solid, organic, n.o.s.
(Aluminium pigment paste)

14.3 Transport hazard class(es)

ADR : 4.1

IMDG : 4.1

IATA : 4.1

14.4 Packing group

ADR
Packing group : II
Classification Code : F1
Hazard Identification Number : 40
Labels : 4.1
Tunnel restriction code : (E)

IMDG
Packing group : II
Labels : 4.1
EmS Number : F-G,S-G

IATA
Packing instruction (cargo aircraft) : 448
Packing instruction (passenger aircraft) : 445
Packing instruction (LQ) : Y441
Packing group : II
Labels : Flammable Solid
Remarks : IMDG Code segregation group 15 - Powdered metals

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

14.6 Special precautions for user

Not applicable

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.3	13.04.2017	102000000226	Date of first issue: 23.01.2014

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of R-Phrases

R11 : Highly flammable.
R20 : Harmful by inhalation.
R36 : Irritating to eyes.
R41 : Risk of serious damage to eyes.
R43 : May cause sensitisation by skin contact.
R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67 : Vapours may cause drowsiness and dizziness.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H228 : Flammable solid.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H336 : May cause drowsiness or dizziness.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Chronic aquatic toxicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Flam. Sol. : Flammable solids
Skin Sens. : Skin sensitisation
STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive

STAPA IL HYDROLAN 701 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
1.3	13.04.2017	102000000226	Date of first issue: 23.01.2014

Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SE / EN