

**STAPA METALLUX 2154 Aluminium Paste**

Version 1.0      Revision Date: 03/27/2018      SDS Number: 102000020055      Date of last issue: -  
Date of first issue: 03/27/2018

---

**SECTION 1. IDENTIFICATION**

Product name : STAPA METALLUX 2154 Aluminium Paste

Product code : 057625G60

**Manufacturer or supplier's details**

Company name of supplier : ECKART GmbH

Address : Guentersthal 4  
Hartenstein 91235

Telephone : +499152770

Telefax : +499152777008

Emergency telephone : CHEMTREC: 800-424-9300  
CHEMTREC: 1-703-527-3387 (International)

GBK Gefahrgut Buero GmbH, Ingelheim, Germany:  
From outside US: (001) 352-323-3500  
(First call in English, response in your language is possible)  
US & Canada (toll free):1-800-5355-053

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum	7429-90-5	>= 50 - < 70
Naphtha (petroleum), hydrotreated heavy	64742-48-9	>= 10 - < 20
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 10 - < 20

**STAPA METALLUX 2154 Aluminium Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020055	Date of first issue: 03/27/2018

---

**SECTION 4. FIRST AID MEASURES**

- General advice : Take the victim into fresh air.  
Do not leave the victim unattended.  
No hazards which require special first aid measures.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Remove contact lenses.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known.
- 

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Dry sand  
Special powder against metal fire
- Unsuitable extinguishing media : Water  
Foam  
ABC powder  
Carbon dioxide (CO<sub>2</sub>)
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
-

## STAPA METALLUX 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020055	Date of first issue: 03/27/2018

---

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Avoid dust formation.

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Sweep up and shovel.  
Do not flush with water.  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.  
Earthing of containers and apparatuses is essential.

Normal measures for preventive fire protection.

Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.

For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.

## STAPA METALLUX 2154 Aluminium Paste

Version 1.0      Revision Date: 03/27/2018      SDS Number: 102000020055      Date of last issue: -  
 Date of first issue: 03/27/2018

Conditions for safe storage : Store in original container.  
 Keep containers tightly closed in a cool, well-ventilated place.  
 Keep container closed when not in use.  
 Keep away from sources of ignition - No smoking.

Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Do not store together with oxidizing and self-igniting products.  
 Never allow product to get in contact with water during storage.  
 Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	TWAEV	10 mg/m3	CA QC OEL
		TWA	10 mg/m3	CA AB OEL
		TWA (Respirable)	1 mg/m3	CA BC OEL
		TWA (Dust)	10 mg/m3	CA AB OEL
		TWAEV	10 mg/m3	CA QC OEL
		TWA (Respirable)	1 mg/m3 (Aluminum)	CA BC OEL
		TWAEV (Fumes)	5 mg/m3 (Aluminum)	CA QC OEL
		TWA (Respirable fraction)	1 mg/m3	ACGIH
		TWA (Respirable fraction)	1 mg/m3 (Aluminum)	ACGIH
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA	525 mg/m3	CA ON OEL

## STAPA METALLUX 2154 Aluminium Paste

Version 1.0      Revision Date: 03/27/2018      SDS Number: 102000020055      Date of last issue: -  
 Date of first issue: 03/27/2018

Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA AB OEL
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH

**Personal protective equipment**

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

Hand protection  
 Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : Long sleeved clothing  
 Safety shoes  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : General industrial hygiene practice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Pasty solid  
 Color : silver  
 Odor : characteristic  
 Odor Threshold : No data available

## STAPA METALLUX 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020055	Date of first issue: 03/27/2018

---

pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	162 °C
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Combustible Solids
Auto-flammability	:	not auto-flammable
Burning number	:	1
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Density	:	1.3 - 2.0 g/cm <sup>3</sup>
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Explosive properties	:	Not explosive

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	<p>Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapor/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.</p>
Conditions to avoid	:	<p>Do not allow to dry.</p> <p>No data available</p>
Incompatible materials	:	<p>Acids</p> <p>Bases</p>

**STAPA METALLUX 2154 Aluminium Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020055	Date of first issue: 03/27/2018

---

Oxidizing agents  
Highly halogenated compounds

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Ingredients:****Naphtha (petroleum), hydrotreated heavy:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): Test atmosphere: vapor  
Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 (Rat): 3,492 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**STAPA METALLUX 2154 Aluminium Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020055	Date of first issue: 03/27/2018

---

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**Ingredients:****Solvent naphtha (petroleum), light arom.:**

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Ingredients:****Solvent naphtha (petroleum), light arom.:**

May be fatal if swallowed and enters airways.

**Further information****Ingredients:****Naphtha (petroleum), hydrotreated heavy:**

Remarks: Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Solvent naphtha (petroleum), light arom.:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available



**STAPA METALLUX 2154 Aluminium Paste**

Version      Revision Date:      SDS Number:      Date of last issue: -  
1.0          03/27/2018          102000020055      Date of first issue: 03/27/2018

---

**Other adverse effects**

No data available

**Ingredients:****Naphtha (petroleum), hydrotreated heavy:**Additional ecological      : No data available  
information

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**Waste from residues      : The product should not be allowed to enter drains, water  
courses or the soil.  
In accordance with local and national regulations.

Contaminated packaging      : In accordance with local and national regulations.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations**Remarks      : Not classified as dangerous in the meaning of transport  
regulations.**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation**

---

**SECTION 15. REGULATORY INFORMATION****Canadian PBT Chemicals**      : This product contains the following components on the DSL  
that are classified as Persistent, Bioaccumulative and/or Toxic  
(PBT) under CEPA:  
Naphtha (petroleum), hydrotreated heavy**NPRI Ingredients**      : Aluminum**The ingredients of this product are reported in the following inventories:**

DSL      : All components of this product are on the Canadian DSL

TSCA      : On TSCA Inventory

**Canadian lists**

No substances are subject to a Significant New Activity Notification.

## STAPA METALLUX 2154 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020055	Date of first issue: 03/27/2018

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United

**STAPA METALLUX 2154 Aluminium Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020055	Date of first issue: 03/27/2018

---

Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 03/27/2018

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / Z8