

**Sample Aluminium Spray 400 ml 17-09021 400 ml**

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

---

**SECTION 1. IDENTIFICATION**

Product name : Sample Aluminium Spray 400 ml 17-09021 400 ml

Product code : 08844605Z

**Manufacturer or supplier's details**

Company name of supplier : ECKART GmbH

Address : Guentersthal 4  
Hartenstein 91235

Telephone : +499152770

Telefax : +499152777008

Emergency telephone number : CHEMTREC: 800-424-9300  
CHEMTREC: 1-703-527-3387 (International)

GBK Gefahrgut Buero GmbH, Ingelheim, Germany:  
From outside US: (001) 352-323-3500  
(First call in English, response in your language is possible)  
US & Canada (toll free):1-800-5355-053

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1

Eye irritation : Category 2A

Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposure

Specific target organ toxicity : Category 2  
- repeated exposure

**GHS label elements**

## Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

---

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H222 Extremely flammable aerosol.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

:

P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read label before use.

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear eye protection/ face protection.

**Response:**

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P314 Get medical advice/ attention if you feel unwell.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep

## Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

---

P405	container tightly closed.
P410 + P412	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

P501	Dispose of contents/ container to an approved waste disposal plant.
------	---

Hazardous components which must be listed on the label:

Acetic acid ethyl ester  
2-Propanone  
Benzene, dimethyl-  
Acetic acid, butyl ester

**Other hazards**

None known.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Butane	106-97-8	>= 10 - < 20
Propane	74-98-6	>= 10 - < 20
Acetic acid ethyl ester	141-78-6	>= 10 - < 20
2-Propanone	67-64-1	>= 10 - < 20
Benzene, dimethyl-	1330-20-7	>= 5 - < 10
Aluminum	7429-90-5	>= 5 - < 10
Acetic acid, butyl ester	123-86-4	>= 1 - < 5
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 1 - < 5
Naphtha (petroleum), hydrotreated heavy	64742-48-9	>= 1 - < 5

---

### SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses.

## Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

---

	Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

---

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Dry sand Carbon dioxide (CO <sub>2</sub> ) Alcohol-resistant foam ABC powder
Unsuitable extinguishing media	: Water
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Avoid breathing dust. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.
---	---

**Sample Aluminium Spray 400 ml 17-09021 400 ml**

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

---

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Do not flush with water.
- 

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
-

## Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0      Revision Date: 03/21/2018      SDS Number: 102000000137      Date of last issue: -  
Date of first issue: 03/21/2018

Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		TWA	800 ppm	CA ON OEL
Propane	74-98-6	STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m <sup>3</sup>	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
Acetic acid ethyl ester	141-78-6	TWA	1,000 ppm	ACGIH
		TWA	400 ppm 1,440 mg/m <sup>3</sup>	CA AB OEL
		TWA	150 ppm	CA BC OEL
		TWAEV	400 ppm 1,440 mg/m <sup>3</sup>	CA QC OEL
		TWA	400 ppm	ACGIH
2-Propanone	67-64-1	TWA	500 ppm 1,200 mg/m <sup>3</sup>	CA AB OEL
		STEL	750 ppm 1,800 mg/m <sup>3</sup>	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		STEV	1,000 ppm 2,380 mg/m <sup>3</sup>	CA QC OEL

# SAFETY DATA SHEET



## Sample Aluminium Spray 400 ml 17-09021 400 ml

Version  
1.0

Revision Date:  
03/21/2018

SDS Number:  
102000000137

Date of last issue: -  
Date of first issue: 03/21/2018

		TWAEV	500 ppm 1,190 mg/m <sup>3</sup>	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Benzene, dimethyl-	1330-20-7	STEL	150 ppm 651 mg/m <sup>3</sup>	CA AB OEL
		TWA	100 ppm 434 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	100 ppm 434 mg/m <sup>3</sup>	CA QC OEL
		STEV	150 ppm 651 mg/m <sup>3</sup>	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
Aluminum	7429-90-5	TWAEV	10 mg/m <sup>3</sup>	CA QC OEL
		TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Respirable)	1 mg/m <sup>3</sup>	CA BC OEL
		TWA (Dust)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable)	1 mg/m <sup>3</sup> (Aluminium)	CA BC OEL
		TWAEV (Fumes)	5 mg/m <sup>3</sup> (Aluminium)	CA QC OEL
		TWA (Respirable fraction)	1 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable fraction)	1 mg/m <sup>3</sup> (Aluminium)	ACGIH
Acetic acid, butyl ester	123-86-4	TWA	150 ppm 713 mg/m <sup>3</sup>	CA AB OEL
		STEL	200 ppm 950 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	150 ppm	CA QC OEL

## Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0      Revision Date: 03/21/2018      SDS Number: 102000000137      Date of last issue: -  
Date of first issue: 03/21/2018

			713 mg/m <sup>3</sup>	
		STEV	200 ppm 950 mg/m <sup>3</sup>	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA AB OEL
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA	525 mg/m <sup>3</sup>	CA ON OEL

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-Propanone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Benzene, dimethyl-	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1,500 mg/g	ACGIH BEI

### Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.  
In the case of dust or aerosol formation use respirator with an



**Sample Aluminium Spray 400 ml 17-09021 400 ml**

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

---

approved filter.

**Hand protection**

Material : Solvent-resistant gloves (butyl-rubber)

**Remarks**

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: aerosol
Colour	: No data available
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: -44 °C
Flash point	: -97 °C

**Sample Aluminium Spray 400 ml 17-09021 400 ml**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

---

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative density	:	No data available
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Components:****Propane:**

Acute inhalation toxicity	:	LC50 (Rat): 800000 ppm Exposure time: 0.25 h
---------------------------	---	---

**Acetic acid ethyl ester:**

Acute oral toxicity	:	(Rat): 5,620 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 56 mg/l Exposure time: 4 h Test atmosphere: vapour

---

**Sample Aluminium Spray 400 ml 17-09021 400 ml**

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

---

Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

**2-Propanone:**

Acute oral toxicity : LD50 (Rabbit): 4,700 - 5,800 mg/kg  
(Mouse): 3,000 mg/kg  
(Rat): 9,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**Benzene, dimethyl-:**

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg  
Method: Converted acute toxicity point estimate

**Solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 (Rat): 3,492 mg/kg  
Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

**Naphtha (petroleum), hydrotreated heavy:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): Test atmosphere: vapour  
Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.  
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Sample Aluminium Spray 400 ml 17-09021 400 ml**

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

---

**Components:**

**2-Propanone:**

Remarks: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:**

**2-Propanone:**

Remarks: Severe eye irritation

**Benzene, dimethyl-:**

Result: Eye irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**Benzene, dimethyl-:**

Assessment: Harmful in contact with skin or if inhaled.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause drowsiness or dizziness.

## Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

---

### Components:

#### **Benzene, dimethyl-:**

Assessment: May cause respiratory irritation.

#### **Acetic acid, butyl ester:**

Assessment: May cause drowsiness or dizziness.

#### **Solvent naphtha (petroleum), light arom.:**

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### Components:

#### **Benzene, dimethyl-:**

Assessment: May cause damage to organs through prolonged or repeated exposure.

### Components:

#### **Benzene, dimethyl-:**

Repeated dose toxicity - : Harmful in contact with skin or if inhaled.  
Assessment

### **Aspiration toxicity**

Not classified based on available information.

### Components:

#### **Benzene, dimethyl-:**

May be fatal if swallowed and enters airways.

#### **Solvent naphtha (petroleum), light arom.:**

May be fatal if swallowed and enters airways.

### **Further information**

### Components:

#### **Naphtha (petroleum), hydrotreated heavy:**

Remarks: Solvents may degrease the skin.

**Sample Aluminium Spray 400 ml 17-09021 400 ml**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

---

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Acetic acid ethyl ester:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 717 mg/l

**2-Propanone:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21,600 mg/l

**Solvent naphtha (petroleum), light arom.:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Other adverse effects**

No data available

**Components:****Naphtha (petroleum), hydrotreated heavy:**

Additional ecological information : No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

**Sample Aluminium Spray 400 ml 17-09021 400 ml**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

---

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****TDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : no

---

## Sample Aluminium Spray 400 ml 17-09021 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

---

### SECTION 15. REGULATORY INFORMATION

**Canadian PBT Chemicals** : This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA:  
Naphtha (petroleum), hydrotreated heavy

**NPRI Components** : Benzene, dimethyl-Aluminum  
1-Butanol  
Benzene, ethyl-  
2-Propanol

**The components of this product are reported in the following inventories:**

DSL : This product contains one or several components that are not on the Canadian DSL nor NDSL.

TSCA : Not On TSCA Inventory

**Canadian lists**

No substances are subject to a Significant New Activity Notification.

### SECTION 16. OTHER INFORMATION

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA AB OEL / STEL : 15-minute occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA BC OEL / STEL : short-term exposure limit  
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)  
CA QC OEL / TWA EV : Time-weighted average exposure value  
CA QC OEL / STEV : Short-term exposure value



**Sample Aluminium Spray 400 ml 17-09021 400 ml**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

---

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 03/21/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN