

STAPA WM CHROMAL V/80 Aluminium Paste

Version 1.0 Revision Date: 03/21/2018 SDS Number: 10200000301 Date of last issue: -
 Date of first issue: 03/21/2018

SECTION 1. IDENTIFICATION

Product name : STAPA WM CHROMAL V/80 Aluminium Paste

Product code : 051874VV0

Manufacturer or supplier's details

Company name of supplier : ECKART GmbH

Address : Guentersthal 4
Hartenstein 91235

Telephone : +499152770

Telefax : +499152777008

Emergency telephone number : CHEMTREC: 800-424-9300
CHEMTREC: 1-703-527-3387 (International)

GBK Gefahrgut Buero GmbH, Ingelheim, Germany:
 From outside US: (001) 352-323-3500
 (First call in English, response in your language is possible)
 US & Canada (toll free):1-800-5355-053

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum	7429-90-5	>= 70 - < 90
White mineral oil (petroleum)	8042-47-5	>= 20 - < 30
Octadecanoic acid	57-11-4	>= 1 - < 5

STAPA WM CHROMAL V/80 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000301	Date of first issue: 03/21/2018

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Use personal protective equipment.
Remove all sources of ignition.
Avoid dust formation.
- Methods and materials for containment and cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Sweep up and shovel.
Do not flush with water.
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
Earthing of containers and apparatuses is essential.

Normal measures for preventive fire protection.
- Advice on safe handling : Keep away from heat and sources of ignition.
Avoid dust formation.
Ensure adequate ventilation.

For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Store in original container.
Keep containers tightly closed in a cool, well-ventilated place.
Keep container closed when not in use.
Keep away from sources of ignition - No smoking.

Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Do not store together with oxidizing and self-igniting products.
Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

STAPA WM CHROMAL V/80 Aluminium Paste

Version 1.0 Revision Date: 03/21/2018 SDS Number: 10200000301 Date of last issue: -
 Date of first issue: 03/21/2018

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	TWAEV	10 mg/m ³	CA QC OEL
		TWA	10 mg/m ³	CA AB OEL
		TWA (Respirable)	1 mg/m ³	CA BC OEL
		TWA (Dust)	10 mg/m ³	CA AB OEL
		TWAEV	10 mg/m ³	CA QC OEL
		TWA (Respirable)	1 mg/m ³ (Aluminium)	CA BC OEL
		TWAEV (Fumes)	5 mg/m ³ (Aluminium)	CA QC OEL
		TWA (Respirable fraction)	1 mg/m ³	ACGIH
		TWA (Respirable fraction)	1 mg/m ³ (Aluminium)	ACGIH
		White mineral oil (petroleum)	8042-47-5	TWAEV
STEV	10 mg/m ³			CA QC OEL
TWA (Mist)	1 mg/m ³			CA BC OEL
TWA (Mist)	5 mg/m ³			CA AB OEL
STEL (Mist)	10 mg/m ³			CA AB OEL
TWAEV (Mist)	5 mg/m ³			CA QC OEL
STEV (Mist)	10 mg/m ³			CA QC OEL
TWA (Mist)	1 mg/m ³			CA BC OEL
TWA (Inhalable fraction)	5 mg/m ³			ACGIH
Octadecanoic acid	57-11-4			TWA

STAPA WM CHROMAL V/80 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000301	Date of first issue: 03/21/2018

--	--	--	--

Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

Filter type : Combined acidic, inorganic gas/vapour and organic vapour type

Hand protection

Material : Solvent-resistant gloves

Material : Nitrile rubber

Glove thickness : ≥ 0.11 mm

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : Long sleeved clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Pasty solid
Colour	: silver
Odour	: characteristic
Odour Threshold	: No data available

STAPA WM CHROMAL V/80 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	10200000301	Date of first issue: 03/21/2018

pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	215 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Combustible Solids
Auto-flammability	:	not auto-flammable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative density	:	No data available
Density	:	1.3 - 2.0 g/cm ³
Solubility(ies)	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Explosive properties	:	Not explosive

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.
Conditions to avoid	:	Do not allow to dry. No data available
Incompatible materials	:	Acids Bases Oxidizing agents Highly halogenated compounds

STAPA WM CHROMAL V/80 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000301	Date of first issue: 03/21/2018

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

STAPA WM CHROMAL V/80 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000301	Date of first issue: 03/21/2018

Bioaccumulative potential

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : In accordance with local and national regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION**International Regulations**

Remarks : Not classified as dangerous in the meaning of transport regulations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

SECTION 15. REGULATORY INFORMATION**NPRI Components** : Aluminum**The components of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

TSCA : On TSCA Inventory

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table)

STAPA WM CHROMAL V/80 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	10200000301	Date of first issue: 03/21/2018

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average

CA AB OEL / TWA : 8-hour Occupational exposure limit

CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 03/21/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

STAPA WM CHROMAL V/80 Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000301	Date of first issue: 03/21/2018

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN