

SILVERSHINE P-1000

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000002376 Date of last issue: -
Date of first issue: 03/21/2018

SECTION 1. IDENTIFICATION

Product name : SILVERSHINE P-1000

Product code : 052618IA0

Manufacturer or supplier's details

Company name of supplier : ECKART GmbH

Address : Guentersthal 4
Hartenstein 91235

Telephone : +499152770

Telefax : +499152777008

Emergency telephone number : CHEMTREC: 800-424-9300
CHEMTREC: 1-703-527-3387 (International)

GBK Gefahrgut Buero GmbH, Ingelheim, Germany:
From outside US: (001) 352-323-3500
(First call in English, response in your language is possible)
US & Canada (toll free):1-800-5355-053

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable solids : Category 1

Reproductive toxicity : Category 1B

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H228 Flammable solid.
H360 May damage fertility or the unborn child.

SILVERSHINE P-1000

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000002376	Date of first issue: 03/21/2018

Precautionary statements

: **Prevention:**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting equipment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P370 + P378	In case of fire: Use for extinction: Special powder for metal fires.
P370 + P378	In case of fire: Use for extinction: Dry sand.

Storage:

P405	Store locked up.
------	------------------

Disposal:

P501	Dispose of contents/ container to an approved waste disposal plant.
------	---

Hazardous components which must be listed on the label:

2-methoxypropyl acetate

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
2-Propanol, 1-methoxy-, 2-acetate	108-65-6	>= 50 - < 70
Naphtha (petroleum), hydrotreated heavy	64742-48-9	>= 10 - < 20
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 10 - < 20
Aluminum	7429-90-5	>= 10 - < 20
Aluminum	7429-90-5	>= 5 - < 10
2-Propanone	67-64-1	>= 1 - < 5
2-methoxypropyl acetate	70657-70-4	>= 0.1 - < 1

SILVERSHINE P-1000

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000002376	Date of first issue: 03/21/2018

SECTION 4. FIRST AID MEASURES

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
Move out of dangerous area.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.

If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.

Flush eyes with water as a precaution.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May damage fertility or the unborn child.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Dry sand
Special powder against metal fire
- Unsuitable extinguishing media : Water
Foam
Carbon dioxide (CO₂)
ABC powder
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

SILVERSHINE P-1000

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000002376	Date of first issue: 03/21/2018

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Use personal protective equipment.
Avoid dust formation.
Remove all sources of ignition.

Environmental precautions :
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Do not flush with water.
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential.
Take measures to prevent the build up of electrostatic charge.
Use explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Keep away from heat and sources of ignition.
Avoid dust formation.
Ensure adequate ventilation.

SILVERSHINE P-1000

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000002376 Date of last issue: -
 Date of first issue: 03/21/2018

For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Store in original container.
 Keep containers tightly closed in a cool, well-ventilated place.
 Keep container closed when not in use.
 Keep away from sources of ignition - No smoking.

No smoking.
 Keep container tightly closed in a dry and well-ventilated place.
 Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Do not store together with oxidizing and self-igniting products.
 Never allow product to get in contact with water during storage.
 Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-Propanol, 1-methoxy-, 2-acetate	108-65-6	TWA	50 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWA	50 ppm 270 mg/m ³	CA ON OEL
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA	525 mg/m ³	CA ON OEL
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	200 mg/m ³ (total hydrocarbon vapor)	CA AB OEL

SAFETY DATA SHEET



SILVERSHINE P-1000

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000002376 Date of last issue: -
 Date of first issue: 03/21/2018

		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
Aluminum	7429-90-5	TWAEV	10 mg/m3	CA QC OEL
		TWA	10 mg/m3	CA AB OEL
		TWA (Respirable)	1 mg/m3	CA BC OEL
		TWA (Dust)	10 mg/m3	CA AB OEL
		TWAEV	10 mg/m3	CA QC OEL
		TWA (Respirable)	1 mg/m3 (Aluminium)	CA BC OEL
		TWAEV (Fumes)	5 mg/m3 (Aluminium)	CA QC OEL
		TWA (Respirable fraction)	1 mg/m3	ACGIH
		TWA (Respirable fraction)	1 mg/m3 (Aluminium)	ACGIH
Aluminum	7429-90-5	TWAEV	10 mg/m3	CA QC OEL
		TWA	10 mg/m3	CA AB OEL
		TWA (Respirable)	1 mg/m3	CA BC OEL
		TWA (Dust)	10 mg/m3	CA AB OEL
		TWAEV	10 mg/m3	CA QC OEL
		TWA (Respirable)	1 mg/m3 (Aluminium)	CA BC OEL
		TWAEV (Fumes)	5 mg/m3 (Aluminium)	CA QC OEL
		TWA (Respirable fraction)	1 mg/m3	ACGIH
		TWA (Respirable fraction)	1 mg/m3 (Aluminium)	ACGIH
2-Propanone	67-64-1	TWA	500 ppm 1,200 mg/m3	CA AB OEL
		STEL	750 ppm 1,800 mg/m3	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL

SILVERSHINE P-1000

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000002376 Date of last issue: -
 Date of first issue: 03/21/2018

		STEV	1,000 ppm 2,380 mg/m ³	CA QC OEL
		TWAEV	500 ppm 1,190 mg/m ³	CA QC OEL
		TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
2-methoxypropyl acetate	70657-70-4	TWA	20 ppm	CA BC OEL
		STEL	40 ppm	CA BC OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-Propanone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

Hand protection
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

SAFETY DATA SHEET



SILVERSHINE P-1000

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000002376	Date of first issue: 03/21/2018

Eye protection : Safety glasses

Skin and body protection : Long sleeved clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Pasty solid
Colour : silver
Odour : odourless
Odour Threshold : No data available
pH : No data available
Melting point/freezing point : No data available
Boiling point/boiling range : 146 °C

Flash point : 40 °C

Evaporation rate : No data available
Flammability (solid, gas) : No data available
Auto-flammability : not auto-flammable
Upper explosion limit / Upper flammability limit : No data available
Lower explosion limit / Lower flammability limit : No data available
Vapour pressure : No data available
Relative density : No data available
Density : 1.4 g/cm³

Solubility(ies) : No data available
Partition coefficient: n-octanol/water : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Explosive properties : Not explosive Vapours may form explosive mixture with air.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

SILVERSHINE P-1000

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000002376	Date of first issue: 03/21/2018

Possibility of hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapours may form explosive mixture with air. Stable under recommended storage conditions.

Conditions to avoid : Do not allow to dry.
Heat, flames and sparks.

Incompatible materials : Acids
Bases
Oxidizing agents
Highly halogenated compounds

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated heavy:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): Test atmosphere: vapour
Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 (Rat): 3,492 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

SILVERSHINE P-1000

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000002376	Date of first issue: 03/21/2018

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility or the unborn child.

STOT - single exposure

Not classified based on available information.

Components:

Solvent naphtha (petroleum), light arom.:

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum), light arom.:

May be fatal if swallowed and enters airways.

Further information

Components:

Naphtha (petroleum), hydrotreated heavy:

Remarks: Solvents may degrease the skin.

SILVERSHINE P-1000

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000002376	Date of first issue: 03/21/2018

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Solvent naphtha (petroleum), light arom.:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

Components:

Naphtha (petroleum), hydrotreated heavy:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

SILVERSHINE P-1000

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000002376	Date of first issue: 03/21/2018

IATA-DGR

UN/ID No.	: UN 1325
Proper shipping name	: Flammable solid, organic, n.o.s. (Aluminium pigment paste)
Class	: 4.1
Packing group	: II
Labels	: Flammable Solid
Packing instruction (cargo aircraft)	: 448
Packing instruction (passenger aircraft)	: 445

IMDG-Code

UN number	: UN 1325
Proper shipping name	: FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste)
Class	: 4.1
Packing group	: II
Labels	: 4.1
EmS Code	: F-A, S-G
Marine pollutant	: no
Remarks	: IMDG Code segregation group 15 - Powdered metals

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**TDG**

UN number	: UN 1325
Proper shipping name	: FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste)
Class	: 4.1
Packing group	: II
Labels	: 4.1
ERG Code	: 133
Marine pollutant	: no

SECTION 15. REGULATORY INFORMATION

Canadian PBT Chemicals	: This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA: Naphtha (petroleum), hydrotreated heavy
-------------------------------	--

NPRI Components	: Aluminum Aluminum
------------------------	------------------------

The components of this product are reported in the following inventories:

SILVERSHINE P-1000

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000002376	Date of first issue: 03/21/2018

DSL : All components of this product are on the Canadian DSL

TSCA : On TSCA Inventory

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit

CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA BC OEL / STEL : short-term exposure limit

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)

CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships;

SAFETY DATA SHEET



SILVERSHINE P-1000

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000002376	Date of first issue: 03/21/2018

n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 03/21/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN