

**STAPA IL HYDROLAN 212 55900/G Aluminium  
Paste**

|                |                              |                             |  |
|----------------|------------------------------|-----------------------------|--|
| Version<br>1.0 | Revision Date:<br>03/21/2018 | SDS Number:<br>102000020062 | Date of last issue: -<br>Date of first issue: 03/21/2018 |
|----------------|------------------------------|-----------------------------|--|

---

**SECTION 1. IDENTIFICATION**

Product name : STAPA IL HYDROLAN 212 55900/G Aluminium Paste

Product code : 005289GD0

**Manufacturer or supplier's details**

Company name of supplier : ECKART GmbH

Address : Guentersthal 4  
Hartenstein 91235

Telephone : +499152770

Telefax : +499152777008

Emergency telephone number : CHEMTREC: 800-424-9300  
CHEMTREC: 1-703-527-3387 (International)

GBK Gefahrgut Buero GmbH, Ingelheim, Germany:  
From outside US: (001) 352-323-3500  
(First call in English, response in your language is possible)  
US & Canada (toll free):1-800-5355-053

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable solids : Category 1

Eye irritation : Category 2A

Skin sensitisation : Category 1

Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposure

**GHS label elements**

## STAPA IL HYDROLAN 212 55900/G Aluminium Paste

|                |                              |                             |  |
|----------------|------------------------------|-----------------------------|--|
| Version<br>1.0 | Revision Date:<br>03/21/2018 | SDS Number:<br>102000020062 | Date of last issue: -<br>Date of first issue: 03/21/2018 |
|----------------|------------------------------|-----------------------------|--|

---

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H228 Flammable solid.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements

:

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use for extinction: Special

## STAPA IL HYDROLAN 212 55900/G Aluminium Paste

|                |                              |                             |  |
|----------------|------------------------------|-----------------------------|--|
| Version<br>1.0 | Revision Date:<br>03/21/2018 | SDS Number:<br>102000020062 | Date of last issue: -<br>Date of first issue: 03/21/2018 |
|----------------|------------------------------|-----------------------------|--|

---

P370 + P378 powder for metal fires.  
In case of fire: Use for extinction: Dry sand.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

2-Propanol  
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-

**Other hazards**

None known.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Hazardous components**

| Chemical name                                      | CAS-No.   | Concentration (% w/w) |
|--|-----------|-----------------------|
| Aluminum   | 7429-90-5 | >= 50 - < 70          |
| 2-Propanol   | 67-63-0   | >= 30 - < 50          |
| 1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]- | 1760-24-3 | >= 0.1 - < 1          |

---

### SECTION 4. FIRST AID MEASURES

General advice : Move the victim to fresh air.  
Do not leave the victim unattended.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.

If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : Wash off immediately with soap and plenty of water.  
  
If on skin, rinse well with water.  
If on clothes, remove clothes.

## STAPA IL HYDROLAN 212 55900/G Aluminium Paste

|                |                              |                             |  |
|----------------|------------------------------|-----------------------------|--|
| Version<br>1.0 | Revision Date:<br>03/21/2018 | SDS Number:<br>102000020062 | Date of last issue: -<br>Date of first issue: 03/21/2018 |
|----------------|------------------------------|-----------------------------|--|

---

- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Dry sand  
Special powder against metal fire
- Unsuitable extinguishing media : Water  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
ABC powder
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Use personal protective equipment.  
  
Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Use personal protective equipment.  
Avoid dust formation.  
Remove all sources of ignition.

**STAPA IL HYDROLAN 212 55900/G Aluminium  
Paste**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 03/21/2018     | 102000020062 | Date of first issue: 03/21/2018 |

---

- Environmental precautions :  
Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
  
Do not flush with water.  
Keep in suitable, closed containers for disposal.
- 

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential.  
Take measures to prevent the build up of electrostatic charge.  
Use explosion-proof equipment.  
  
Avoid dust formation.  
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.  
  
Avoid formation of respirable particles.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Store in original container.  
Keep containers tightly closed in a cool, well-ventilated place.  
Keep container closed when not in use.  
Keep away from sources of ignition - No smoking.
-

## STAPA IL HYDROLAN 212 55900/G Aluminium Paste

|                |                              |                             |  |
|----------------|------------------------------|-----------------------------|--|
| Version<br>1.0 | Revision Date:<br>03/21/2018 | SDS Number:<br>102000020062 | Date of last issue: -<br>Date of first issue: 03/21/2018 |
|----------------|------------------------------|-----------------------------|--|

---

No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

---

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

| Components | CAS-No.   | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis     |
|------------|-----------|----------------------------------|--|-----------|
| Aluminium  | 7429-90-5 | TWAEV                            | 10 mg/m <sup>3</sup>                           | CA QC OEL |
|            |           | TWA                              | 10 mg/m <sup>3</sup>                           | CA AB OEL |
|            |           | TWA<br>(Respirable)              | 1 mg/m <sup>3</sup>                            | CA BC OEL |
|            |           | TWA (Dust)                       | 10 mg/m <sup>3</sup>                           | CA AB OEL |
|            |           | TWAEV                            | 10 mg/m <sup>3</sup>                           | CA QC OEL |
|            |           | TWA<br>(Respirable)              | 1 mg/m <sup>3</sup><br>(Aluminium)             | CA BC OEL |
|            |           | TWAEV<br>(Fumes)                 | 5 mg/m <sup>3</sup><br>(Aluminium)             | CA QC OEL |
|            |           | TWA<br>(Respirable fraction)     | 1 mg/m <sup>3</sup>                            | ACGIH     |
|            |           | TWA<br>(Respirable fraction)     | 1 mg/m <sup>3</sup><br>(Aluminium)             | ACGIH     |
| 2-Propanol | 67-63-0   | TWA                              | 200 ppm<br>492 mg/m <sup>3</sup>               | CA AB OEL |

## STAPA IL HYDROLAN 212 55900/G Aluminium Paste

Version 1.0      Revision Date: 03/21/2018      SDS Number: 102000020062      Date of last issue: -  
Date of first issue: 03/21/2018

|  |  |       |                                    |           |
|--|--|-------|------------------------------------|-----------|
|  |  | STEL  | 400 ppm<br>984 mg/m <sup>3</sup>   | CA AB OEL |
|  |  | TWA   | 200 ppm                            | CA BC OEL |
|  |  | STEL  | 400 ppm                            | CA BC OEL |
|  |  | TWAEV | 400 ppm<br>983 mg/m <sup>3</sup>   | CA QC OEL |
|  |  | STEV  | 500 ppm<br>1,230 mg/m <sup>3</sup> | CA QC OEL |
|  |  | TWA   | 200 ppm                            | ACGIH     |
|  |  | STEL  | 400 ppm                            | ACGIH     |

### Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sampling time                   | Permissible concentration | Basis     |
|------------|---------|--------------------|---------------------|---------------------------------|---------------------------|-----------|
| 2-Propanol | 67-63-0 | Acetone            | Urine               | End of shift at end of workweek | 40 mg/l                   | ACGIH BEI |

### Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be

## STAPA IL HYDROLAN 212 55900/G Aluminium Paste

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 03/21/2018     | 102000020062 | Date of first issue: 03/21/2018 |

---

washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

- Eye protection : Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Long sleeved clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Pasty solid
- Colour : silver
- Odour : solvent-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 82 °C
- Flash point : 13 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Auto-flammability : not auto-flammable
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : No data available
- Relative density : No data available
- Density : 1.3 - 2.0 g/cm<sup>3</sup>
- Solubility(ies) : No data available
- Partition coefficient: n-octanol/water : No data available
- Auto-ignition temperature : No data available



**STAPA IL HYDROLAN 212 55900/G Aluminium  
Paste**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 03/21/2018     | 102000020062 | Date of first issue: 03/21/2018 |

---

|                           |   |  |
|---------------------------|---|--|
| Decomposition temperature | : | No data available  |
| Viscosity                 | : | No data available  |
| Explosive properties      | : | Not explosive Vapours may form explosive mixture with air. |

---

**SECTION 10. STABILITY AND REACTIVITY**

|                                    |   |   |
|------------------------------------|---|---|
| Reactivity                         | : | No decomposition if stored and applied as directed.   |
| Chemical stability                 | : | No decomposition if stored and applied as directed.   |
| Possibility of hazardous reactions | : | Reacts with alkalis, acids, halogenes and oxidizing agents.<br>Contact with acids and alkalis may release hydrogen.<br>Mixture reacts slowly with water resulting in evolution of hydrogen.<br>Vapours may form explosive mixture with air.<br>Stable under recommended storage conditions. |
| Conditions to avoid                | : | Do not allow to dry.<br><br>Heat, flames and sparks.  |
| Incompatible materials             | : | Acids<br>Bases<br>Oxidizing agents<br>Highly halogenated compounds  |

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Components:****2-Propanol:**

|                       |   |                              |
|-----------------------|---|------------------------------|
| Acute oral toxicity   | : | LD50 (Rat): > 2,000 mg/kg    |
| Acute dermal toxicity | : | LD50 (Rabbit): > 2,000 mg/kg |

**1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-:**

|                           |   |   |
|---------------------------|---|---|
| Acute oral toxicity       | : | LD50 (Rat): ca. 2,400 mg/kg   |
| Acute inhalation toxicity | : | LC50: 1.49 - 2.44 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapour |

---

**STAPA IL HYDROLAN 212 55900/G Aluminium  
Paste**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 03/21/2018     | 102000020062 | Date of first issue: 03/21/2018 |

---

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation****Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

## STAPA IL HYDROLAN 212 55900/G Aluminium Paste

|                |                              |                             |  |
|----------------|------------------------------|-----------------------------|--|
| Version<br>1.0 | Revision Date:<br>03/21/2018 | SDS Number:<br>102000020062 | Date of last issue: -<br>Date of first issue: 03/21/2018 |
|----------------|------------------------------|-----------------------------|--|

---

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

- Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

- UN/ID No. : UN 1325  
Proper shipping name : Flammable solid, organic, n.o.s.  
(Aluminium pigment paste)  
Class : 4.1  
Packing group : II  
Labels : Flammable Solid  
Packing instruction (cargo aircraft) : 448  
Packing instruction (passenger aircraft) : 445

#### IMDG-Code

- UN number : UN 1325  
Proper shipping name : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)  
Class : 4.1  
Packing group : II  
Labels : 4.1  
EmS Code : F-A, S-G  
Marine pollutant : no  
Remarks : IMDG Code segregation group 15 - Powdered metals

## STAPA IL HYDROLAN 212 55900/G Aluminium Paste

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 03/21/2018     | 102000020062 | Date of first issue: 03/21/2018 |

---

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### TDG

|                      |   |   |
|----------------------|---|---|
| UN number            | : | UN 1325   |
| Proper shipping name | : | FLAMMABLE SOLID, ORGANIC, N.O.S.<br>(Aluminium pigment paste) |
| Class                | : | 4.1   |
| Packing group        | : | II  |
| Labels               | : | 4.1   |
| ERG Code             | : | 133   |
| Marine pollutant     | : | no  |

---

### SECTION 15. REGULATORY INFORMATION

**NPRI Components** : Aluminum  
2-Propanol

#### The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : On TSCA Inventory

#### Canadian lists

No substances are subject to a Significant New Activity Notification.

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

|                  |   |   |
|------------------|---|---|
| ACGIH            | : | USA. ACGIH Threshold Limit Values (TLV)   |
| ACGIH BEI        | : | ACGIH - Biological Exposure Indices (BEI)   |
| CA AB OEL        | : | Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)   |
| CA BC OEL        | : | Canada. British Columbia OEL  |
| CA QC OEL        | : | Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants |
| ACGIH / TWA      | : | 8-hour, time-weighted average   |
| ACGIH / STEL     | : | Short-term exposure limit   |
| CA AB OEL / TWA  | : | 8-hour Occupational exposure limit  |
| CA AB OEL / STEL | : | 15-minute occupational exposure limit   |
| CA BC OEL / TWA  | : | 8-hour time weighted average  |

---

## STAPA IL HYDROLAN 212 55900/G Aluminium Paste

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 03/21/2018     | 102000020062 | Date of first issue: 03/21/2018 |

---

CA BC OEL / STEL : short-term exposure limit  
 CA QC OEL / TWAEV : Time-weighted average exposure value  
 CA QC OEL / STEV : Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 03/21/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN