

**STAPA IL HYDROLAN 214 55900/G Aluminium  
Paste**

Version 1.0      Revision Date: 03/27/2018      SDS Number: 102000020062      Date of last issue: -  
Date of first issue: 03/27/2018

---

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : STAPA IL HYDROLAN 214 55900/G Aluminium Paste

Product code : 005367GD0

**Manufacturer or supplier's details**

Company name of supplier : ECKART GmbH

Address : Guentersthal 4  
Hartenstein 91235

Telephone : +499152770

Telefax : +499152777008

Emergency telephone : CHEMTREC: 800-424-9300  
CHEMTREC: 1-703-527-3387 (International)

GBK Gefahrgut Buero GmbH, Ingelheim, Germany:  
From outside US: (001) 352-323-3500  
(First call in English, response in your language is possible)  
US & Canada (toll free):1-800-5355-053

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable solids : Category 1

Eye irritation : Category 2A

Specific target organ  
systemic toxicity - single  
exposure : Category 3 (Central nervous system)

**GHS label elements**

Hazard pictograms :



## STAPA IL HYDROLAN 214 55900/G Aluminium Paste

Version 1.0	Revision Date: 03/27/2018	SDS Number: 102000020062	Date of last issue: - Date of first issue: 03/27/2018
----------------	------------------------------	-----------------------------	--

---

Signal Word : Danger

Hazard Statements : H228 Flammable solid.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370 + P378 In case of fire: Use for extinction: Special powder for metal fires.

P370 + P378 In case of fire: Use for extinction: Dry sand.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous ingredients which must be listed on the label:

2-Propanol

## STAPA IL HYDROLAN 214 55900/G Aluminium Paste

Version 1.0      Revision Date: 03/27/2018      SDS Number: 102000020062      Date of last issue: -  
Date of first issue: 03/27/2018

---

### Other hazards

None known.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum	7429-90-5	>= 50 -< 70
2-Propanol	67-63-0	>= 30 -< 50
Silica	7631-86-9	>= 1 -< 5

---

### SECTION 4. FIRST AID MEASURES

- General advice : Take the victim into fresh air.  
Do not leave the victim unattended.  
Move out of dangerous area.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
  
Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms : Causes serious eye irritation.
-

## STAPA IL HYDROLAN 214 55900/G Aluminium Paste

Version 1.0	Revision Date: 03/27/2018	SDS Number: 102000020062	Date of last issue: - Date of first issue: 03/27/2018
----------------	------------------------------	-----------------------------	--

---

and effects, both acute and delayed      May cause drowsiness or dizziness.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry sand  
Special powder against metal fire

Unsuitable extinguishing media : Water  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
ABC powder

Specific extinguishing methods : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for fire-fighters : Use personal protective equipment.  
  
Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Use personal protective equipment.  
Avoid dust formation.  
Remove all sources of ignition.

Environmental precautions :  
  
Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
  
Do not flush with water.

## STAPA IL HYDROLAN 214 55900/G Aluminium Paste

Version 1.0	Revision Date: 03/27/2018	SDS Number: 102000020062	Date of last issue: - Date of first issue: 03/27/2018
----------------	------------------------------	-----------------------------	--

---

Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential.  
Take measures to prevent the build up of electrostatic charge.  
Use explosion-proof equipment.

Avoid dust formation.  
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.

Avoid formation of respirable particles.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.  
Keep containers tightly closed in a cool, well-ventilated place.  
Keep container closed when not in use.  
Keep away from sources of ignition - No smoking.

No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Do not store together with oxidizing and self-igniting products.

## STAPA IL HYDROLAN 214 55900/G Aluminium Paste

Version 1.0      Revision Date: 03/27/2018      SDS Number: 102000020062      Date of last issue: -  
Date of first issue: 03/27/2018

Never allow product to get in contact with water during storage.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	LMPE-PPT	10 mg/m <sup>3</sup>	MX OEL
		LMPE-PPT (Dust)	10 mg/m <sup>3</sup>	MX OEL
		TWA (Respirable fraction)	1 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable fraction)	1 mg/m <sup>3</sup> (Aluminum)	ACGIH
2-Propanol	67-63-0	VLE-PPT	200 ppm	NOM-010-STPS-2014
		VLE-CT	400 ppm	NOM-010-STPS-2014
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
Silica	7631-86-9	LMPE-PPT (Respirable)	3 mg/m <sup>3</sup>	MX OEL
		LMPE-PPT (Inhalable)	10 mg/m <sup>3</sup>	MX OEL

#### Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-Propanol	67-63-0	Acetone	Urine	End of	40 mg/l	MX BEI

## STAPA IL HYDROLAN 214 55900/G Aluminium Paste

Version 1.0      Revision Date: 03/27/2018      SDS Number: 102000020062      Date of last issue: -  
Date of first issue: 03/27/2018

				shift at end of workweek		
		Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

### Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Long sleeved clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**STAPA IL HYDROLAN 214 55900/G Aluminium  
Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020062	Date of first issue: 03/27/2018

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	Pasty solid
Color	:	silver
Odor	:	solvent
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	82 °C
Flash point	:	13 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Auto-flammability	:	not auto-flammable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Density	:	1.3 - 2.0 g/cm <sup>3</sup>
Solubility(ies)	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Explosive properties	:	Not explosive Vapors may form explosive mixture with air.

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapors may form explosive mixture with air. Stable under recommended storage conditions.

---



**STAPA IL HYDROLAN 214 55900/G Aluminium  
Paste**

Version 1.0	Revision Date: 03/27/2018	SDS Number: 102000020062	Date of last issue: - Date of first issue: 03/27/2018
----------------	------------------------------	-----------------------------	--

---

Conditions to avoid : Do not allow to dry.  
Heat, flames and sparks.

Incompatible materials : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Ingredients:****2-Propanol:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**Silica:**

Acute oral toxicity : LD50 (Rat): 5,000 mg/kg  
(Mouse): 15,000 mg/kg  
Acute inhalation toxicity : (Rat): 0.139 mg/l  
Exposure time: 4 h  
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

---

**STAPA IL HYDROLAN 214 55900/G Aluminium  
Paste**

Version 1.0	Revision Date: 03/27/2018	SDS Number: 102000020062	Date of last issue: - Date of first issue: 03/27/2018
----------------	------------------------------	-----------------------------	--

---

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Silica:**Toxicity to daphnia and other : (Daphnia): 7,600 mg/l  
aquatic invertebrates

Toxicity to algae : (Chlorella pyrenoidosa): 440 mg/l

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Other adverse effects**

No data available

## STAPA IL HYDROLAN 214 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020062	Date of first issue: 03/27/2018

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 1325  
Proper shipping name : Flammable solid, organic, n.o.s.  
(Aluminium pigment paste)  
Class : 4.1  
Packing group : II  
Labels : Flammable Solid  
Packing instruction (cargo aircraft) : 448  
Packing instruction (passenger aircraft) : 445

##### IMDG-Code

- UN number : UN 1325  
Proper shipping name : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)  
Class : 4.1  
Packing group : II  
Labels : 4.1  
EmS Code : F-A, S-G  
Marine pollutant : no  
Remarks : IMDG Code segregation group 15 - Powdered metals

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## STAPA IL HYDROLAN 214 55900/G Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020062	Date of first issue: 03/27/2018

---

### Domestic regulation

#### NOM-002-SCT

UN number	: UN 1325
Proper shipping name	: FLAMMABLE SOLID, ORGANIC, N.O.S. (Aluminium pigment paste)
Class	: 4.1
Packing group	: II
Labels	: 4.1

#### Special precautions for user

Not applicable

---

## SECTION 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Federal Law for the control of chemical precursors, : Not applicable  
essential chemical products and machinery for  
producing capsules, tablets and pills.

### The ingredients of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
TSCA	: On TSCA Inventory

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
MX BEI	: Official Mexican Norm NOM-047-SSA1-2011, Environmental Health - Biological exposure indices for workers occupationally exposed to chemical agents
MX OEL	: Mexico. Occupational Exposure Limits
NOM-010-STPS-2014	: Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
MX OEL / LMPE-PPT	: Time weighted average
NOM-010-STPS-2014 / VLE- PPT	: Time weighted average limit value
NOM-010-STPS-2014 / VLE- CT	: Short term exposure limit value

---

**STAPA IL HYDROLAN 214 55900/G Aluminium  
Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/27/2018	102000020062	Date of first issue: 03/27/2018

---

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 03/27/2018

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MX / Z8