

**STAPA NDF 130 Aluminum Paste**

Version            Revision Date:            SDS Number:            Date of last issue: -  
1.0                05/07/2018              102000001203        Date of first issue: 05/07/2018

---

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name                                : STAPA NDF 130 Aluminum Paste

Product code                                : 052112G60

**Manufacturer or supplier's details**

Company name of supplier                : ECKART GmbH

Address                                        : Guentersthal 4  
    Hartenstein 91235

Telephone                                    : +499152770

Telefax                                        : +499152777008

Emergency telephone                      : CHEMTREC: 800-424-9300  
    CHEMTREC: 1-703-527-3387 (International)

GBK Gefahrgut Buero GmbH, Ingelheim, Germany:  
From outside US: (001) 352-323-3500  
(First call in English, response in your language is possible)  
US & Canada (toll free):1-800-5355-053

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable solids                            : Category 1

Skin irritation                                : Category 2

Specific target organ                        : Category 3 (Central nervous system)  
systemic toxicity - single  
exposure

Acute aquatic toxicity                       : Category 3

Chronic aquatic toxicity                     : Category 2

**GHS label elements**

## STAPA NDF 130 Aluminum Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/07/2018	102000001203	Date of first issue: 05/07/2018

---

Hazard pictograms

:



Signal Word

: Danger  
Danger

Hazard Statements

: H228 Flammable solid.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H228 Flammable solid.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H402 Harmful to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

## STAPA NDF 130 Aluminum Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/07/2018	102000001203	Date of first issue: 05/07/2018

---

P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.  
 P370 + P378 In case of fire: Use for extinction: Special powder for metal fires.  
 P370 + P378 In case of fire: Use for extinction: Dry sand.  
 P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.  
 P370 + P378 In case of fire: Use for extinction: Special powder for metal fires.  
 P370 + P378 In case of fire: Use for extinction: Dry sand.  
 P391 Collect spillage.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.  
 P501 Dispose of contents/ container to an approved waste disposal plant.

## STAPA NDF 130 Aluminum Paste

Version 1.0      Revision Date: 05/07/2018      SDS Number: 102000001203      Date of last issue: -  
 Date of first issue: 05/07/2018

Hazardous ingredients which must be listed on the label:

Distillates (petroleum), hydrotreated light  
 Solvent naphtha (petroleum), light arom.  
 Distillates (petroleum), hydrotreated light  
 Solvent naphtha (petroleum), light arom.

**Other hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum	7429-90-5	>= 50 -< 70
Distillates (petroleum), hydrotreated light	64742-47-8	>= 20 -< 30
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 5 -< 10
Benzene, 1,2,4-trimethyl-	95-63-6	>= 1 -< 5
Fatty acids, C14-18 and C16-18-unsatd.	67701-06-8	>= 1 -< 5

### SECTION 4. FIRST AID MEASURES

- General advice : Take the victim into fresh air.  
 Do not leave the victim unattended.  
 Move out of dangerous area.  
 Show this material safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.  
 If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
  
 If skin irritation persists, call a physician.  
 If on skin, rinse well with water.  
 If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
  
 Flush eyes with water as a precaution.  
 Remove contact lenses.

## STAPA NDF 130 Aluminum Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/07/2018	102000001203	Date of first issue: 05/07/2018

---

Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause drowsiness or dizziness.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry sand  
Special powder against metal fire

Unsuitable extinguishing media : Water  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
ABC powder

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : Use personal protective equipment.  
  
Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Use personal protective equipment.  
Avoid dust formation.  
Remove all sources of ignition.

Environmental precautions :

## STAPA NDF 130 Aluminum Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/07/2018	102000001203	Date of first issue: 05/07/2018

---

Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Do not flush with water.  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential.  
Take measures to prevent the build up of electrostatic charge.  
Use explosion-proof equipment.

Avoid dust formation.  
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.

Avoid formation of respirable particles.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.  
Keep containers tightly closed in a cool, well-ventilated place.  
Keep container closed when not in use.  
Keep away from sources of ignition - No smoking.

## STAPA NDF 130 Aluminum Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/07/2018	102000001203	Date of first issue: 05/07/2018

No smoking.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.  
 Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	LMPE-PPT	10 mg/m <sup>3</sup>	MX OEL
		LMPE-PPT (Dust)	10 mg/m <sup>3</sup>	MX OEL
		TWA (Respirable fraction)	1 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable fraction)	1 mg/m <sup>3</sup> (Aluminum)	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH
Benzene, 1,2,4-trimethyl-	95-63-6	VLE-PPT	25 ppm	NOM-010-STPS-2014

## STAPA NDF 130 Aluminum Paste

Version 1.0      Revision Date: 05/07/2018      SDS Number: 102000001203      Date of last issue: -  
 Date of first issue: 05/07/2018

		TWA	25 ppm	ACGIH
--	--	-----	--------	-------

**Personal protective equipment**

Respiratory protection : Use suitable breathing protection if workplace concentration requires.  
 In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection  
 Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : Long sleeved clothing  
 Safety shoes  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Pasty solid  
 Color : silver  
 Odor : No data available  
 Odor Threshold : No data available  
 pH : No data available  
 Melting point/freezing point : No data available



## STAPA NDF 130 Aluminum Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/07/2018	102000001203	Date of first issue: 05/07/2018

---

Boiling point/boiling range	:	170 °C
Flash point	:	43 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	The substance or mixture is a flammable solid with the category 1.
Auto-flammability	:	not auto-flammable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Solubility(ies)	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	240 °C
Decomposition temperature	:	No data available
Viscosity	:	No data available
Explosive properties	:	Not explosive Vapors may form explosive mixture with air.

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	<p>Reacts with alkalis, acids, halogenes and oxidizing agents.            Contact with acids and alkalis may release hydrogen.            Mixture reacts slowly with water resulting in evolution of hydrogen.            Vapors may form explosive mixture with air.            Stable under recommended storage conditions.</p>
Conditions to avoid	:	<p>Do not allow to dry.</p> <p>Heat, flames and sparks.</p>
Incompatible materials	:	<p>Acids            Bases            Oxidizing agents            Highly halogenated compounds</p>

---

**STAPA NDF 130 Aluminum Paste**

Version      Revision Date:      SDS Number:      Date of last issue: -  
1.0          05/07/2018          102000001203      Date of first issue: 05/07/2018

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Ingredients:****Benzene, 1,2,4-trimethyl-:**

Acute inhalation toxicity      :    Assessment: The component/mixture is moderately toxic after short term inhalation.

**Fatty acids, C14-18 and C16-18-unsatd.:**

Acute oral toxicity              :    LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity      :    LC50 (Rat): > 46 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist

Acute dermal toxicity          :    LD50 (Rabbit): > 3,160 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Ingredients:****Distillates (petroleum), hydrotreated light:**

Result: Skin irritation

**Benzene, 1,2,4-trimethyl-:**

Result: Skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Ingredients:****Benzene, 1,2,4-trimethyl-:**

Result: Mild eye irritation

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**STAPA NDF 130 Aluminum Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/07/2018	102000001203	Date of first issue: 05/07/2018

---

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

May cause drowsiness or dizziness.

**Ingredients:****Distillates (petroleum), hydrotreated light:**

Assessment: May cause drowsiness or dizziness.

**Solvent naphtha (petroleum), light arom.:**

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

**Benzene, 1,2,4-trimethyl-:**

Assessment: May cause respiratory irritation.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Ingredients:****Distillates (petroleum), hydrotreated light:**

May be fatal if swallowed and enters airways.

**Solvent naphtha (petroleum), light arom.:**

May be fatal if swallowed and enters airways.

**STAPA NDF 130 Aluminum Paste**

Version 1.0      Revision Date: 05/07/2018      SDS Number: 102000001203      Date of last issue: -  
Date of first issue: 05/07/2018

---

**Further information****Ingredients:****Fatty acids, C14-18 and C16-18-unsatd.:**

Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Distillates (petroleum), hydrotreated light:****Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**Solvent naphtha (petroleum), light arom.:****Ecotoxicology Assessment**

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Benzene, 1,2,4-trimethyl-:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Other adverse effects**

No data available

**Ingredients:****Fatty acids, C14-18 and C16-18-unsatd.:**

Additional ecological information : No data available

## STAPA NDF 130 Aluminum Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/07/2018	102000001203	Date of first issue: 05/07/2018

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 1325  
Proper shipping name : Flammable solid, organic, n.o.s.  
(Aluminium pigment paste)  
Class : 4.1  
Packing group : II  
Labels : Flammable Solid  
Packing instruction (cargo aircraft) : 448  
Packing instruction (passenger aircraft) : 445

##### IMDG-Code

- UN number : UN 1325  
Proper shipping name : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)  
Class : 4.1  
Packing group : II  
Labels : 4.1  
EmS Code : F-A, S-G  
Marine pollutant : no  
Remarks : IMDG Code segregation group 15 - Powdered metals

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

## STAPA NDF 130 Aluminum Paste

Version 1.0      Revision Date: 05/07/2018      SDS Number: 102000001203      Date of last issue: -  
 Date of first issue: 05/07/2018

---

**NOM-002-SCT**

UN number : UN 1325  
 Proper shipping name : FLAMMABLE SOLID, ORGANIC, N.O.S.  
 (Aluminium pigment paste)  
 Class : 4.1  
 Packing group : II  
 Labels : 4.1

**Special precautions for user**

Not applicable

---

**SECTION 15. REGULATORY INFORMATION****Safety, health and environmental regulations/legislation specific for the substance or mixture**

NOM-165-SEMARNAT-2013, Norm establishing a list of substances subject to report for the Registry of Emissions and Pollutant Transfer

Ingredients	CAS-No.	MPU (kg/year)	Transfer/Release (kg/year)
Benzene, dimethyl-cumene	1330-20-7	5000 kg/year	1000 kg/year
	98-82-8	5000 kg/year	1000 kg/year

MPU: Applicable reporting threshold when the substance, pure or in mixture in a composition of more than 1% by weight, is used for industrial activities at facilities that are subject to report or are produced by them

Federal Law for the control of chemical precursors, essential chemical products and machinery for producing capsules, tablets and pills. : Not applicable

**The ingredients of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL  
 TSCA : On TSCA Inventory

---

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 MX OEL : Mexico. Occupational Exposure Limits  
 NOM-010-STPS-2014 : Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits  
 ACGIH / TWA : 8-hour, time-weighted average  
 MX OEL / LMPE-PPT : Time weighted average  
 NOM-010-STPS-2014 / VLE- : Time weighted average limit value

---

## STAPA NDF 130 Aluminum Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/07/2018	102000001203	Date of first issue: 05/07/2018

---

## PPT

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 05/07/2018

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MX / Z8