

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

SECTION 1. IDENTIFICATION

Product name : Sample Aluminium Spray 400 ml 17-09021 400 ml

Product code : 08844605Z

Manufacturer or supplier's details

Company name of supplier : ECKART GmbH

Address : Guentersthal 4
Hartenstein 91235

Telephone : +499152770

Telefax : +499152777008

Emergency telephone number : CHEMTREC: 800-424-9300
CHEMTREC: 1-703-527-3387 (International)

GBK Gefahrgut Buero GmbH, Ingelheim, Germany:
From outside US: (001) 352-323-3500
(First call in English, response in your language is possible)
US & Canada (toll free):1-800-5355-053

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Flammable aerosols : Category 1

Eye irritation : Category 2A

Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure

Specific target organ toxicity : Category 2
- repeated exposure

GHS label elements

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

Hazard pictograms

:



Signal word

: Danger

Hazard statements

:

- H222 Extremely flammable aerosol.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

:

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P403 + P233 Store in a well-ventilated place. Keep

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

P405	container tightly closed.
P410 + P412	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501	Dispose of contents/ container to an approved waste disposal plant.
------	---

Hazardous components which must be listed on the label:

Acetic acid ethyl ester
2-Propanone
Benzene, dimethyl-
Acetic acid, butyl ester

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Butane	106-97-8	>= 10 - < 20
Propane	74-98-6	>= 10 - < 20
Acetic acid ethyl ester	141-78-6	>= 10 - < 20
2-Propanone	67-64-1	>= 10 - < 20
Benzene, dimethyl-	1330-20-7	>= 5 - < 10
Aluminum	7429-90-5	>= 5 - < 10
Acetic acid, butyl ester	123-86-4	>= 1 - < 5
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 1 - < 5
Naphtha (petroleum), hydrotreated heavy	64742-48-9	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses.

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry sand
Carbon dioxide (CO₂)
Alcohol-resistant foam
ABC powder

Unsuitable extinguishing media : Water

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid breathing dust.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Do not flush with water.
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
-

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000000137 Date of last issue: -
Date of first issue: 03/21/2018

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butane	106-97-8	TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		TWA	800 ppm 1,900 mg/m ³	OSHA P0
		STEL	1,000 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m ³	OSHA P0
Acetic acid ethyl ester	141-78-6	TWA	400 ppm	ACGIH
		TWA	400 ppm 1,400 mg/m ³	NIOSH REL
		TWA	400 ppm 1,400 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,400 mg/m ³	OSHA P0
2-Propanone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m ³	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	750 ppm 1,800 mg/m ³	OSHA P0

SAFETY DATA SHEET



Sample Aluminium Spray 400 ml 17-09021 400 ml

Version
1.0

Revision Date:
03/21/2018

SDS Number:
102000000137

Date of last issue: -
Date of first issue: 03/21/2018

		STEL	1,000 ppm 2,400 mg/m ³	OSHA P0
Benzene, dimethyl-	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m ³	OSHA P0
		TWA	100 ppm 435 mg/m ³	OSHA P0
		TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m ³	OSHA P0
		TWA	100 ppm 435 mg/m ³	OSHA P0
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA Z-3
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable fraction)	1 mg/m ³	ACGIH
		TWA	5 mg/m ³ (Aluminium)	NIOSH REL
		TWA (Total)	15 mg/m ³ (Aluminium)	OSHA P0
		TWA (Respirable fraction)	5 mg/m ³ (Aluminium)	OSHA P0
		TWA (total dust)	15 mg/m ³ (Aluminium)	OSHA Z-1

SAFETY DATA SHEET


Sample Aluminium Spray 400 ml 17-09021 400 ml
Version
1.0Revision Date:
03/21/2018SDS Number:
102000000137Date of last issue: -
Date of first issue: 03/21/2018

		TWA (respirable fraction)	5 mg/m ³ (Aluminium)	OSHA Z-1
		TWA (Total dust)	15 mg/m ³ (Aluminium)	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³ (Aluminium)	OSHA P0
		TWA (welding fumes)	5 mg/m ³ (Aluminium)	NIOSH REL
		TWA (pyro powders)	5 mg/m ³ (Aluminium)	NIOSH REL
		TWA (Respirable fraction)	1 mg/m ³ (Aluminium)	ACGIH
		TWA (Fumes)	5 mg/m ³	OSHA P0
Acetic acid, butyl ester	123-86-4	ST	200 ppm 950 mg/m ³	NIOSH REL
		TWA	150 ppm 710 mg/m ³	NIOSH REL
		TWA	150 ppm 710 mg/m ³	OSHA Z-1
		TWA	150 ppm 710 mg/m ³	OSHA P0
		STEL	200 ppm 950 mg/m ³	OSHA P0
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0

SAFETY DATA SHEET



Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000000137 Date of last issue: -
 Date of first issue: 03/21/2018

Butane	106-97-8	TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		TWA	800 ppm 1,900 mg/m ³	OSHA P0
		STEL	1,000 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m ³	OSHA P0
Acetic acid ethyl ester	141-78-6	TWA	400 ppm	ACGIH
		TWA	400 ppm 1,400 mg/m ³	NIOSH REL
		TWA	400 ppm 1,400 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,400 mg/m ³	OSHA P0
2-Propanone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m ³	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	750 ppm 1,800 mg/m ³	OSHA P0
		STEL	1,000 ppm 2,400 mg/m ³	OSHA P0
Benzene, dimethyl-	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m ³	OSHA P0
		TWA	100 ppm 435 mg/m ³	OSHA P0
		TWA	100 ppm	OSHA Z-1

SAFETY DATA SHEET



Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000000137 Date of last issue: -
 Date of first issue: 03/21/2018

			435 mg/m ³	
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m ³	OSHA P0
		TWA	100 ppm 435 mg/m ³	OSHA P0
Aluminum	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA Z-3
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-3
		TWA (respirable fraction)	15 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable fraction)	1 mg/m ³	ACGIH
		TWA	5 mg/m ³ (Aluminium)	NIOSH REL
		TWA (Total)	15 mg/m ³ (Aluminium)	OSHA P0
		TWA (Respirable fraction)	5 mg/m ³ (Aluminium)	OSHA P0
		TWA (total dust)	15 mg/m ³ (Aluminium)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³ (Aluminium)	OSHA Z-1
		TWA (Total dust)	15 mg/m ³ (Aluminium)	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³ (Aluminium)	OSHA P0
		TWA (welding fumes)	5 mg/m ³ (Aluminium)	NIOSH REL

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000000137 Date of last issue: -
Date of first issue: 03/21/2018

		TWA (pyro powders)	5 mg/m ³ (Aluminium)	NIOSH REL
		TWA (Respirable fraction)	1 mg/m ³ (Aluminium)	ACGIH
		TWA (Fumes)	5 mg/m ³	OSHA P0
Acetic acid, butyl ester	123-86-4	ST	200 ppm 950 mg/m ³	NIOSH REL
		TWA	150 ppm 710 mg/m ³	NIOSH REL
		TWA	150 ppm 710 mg/m ³	OSHA Z-1
		TWA	150 ppm 710 mg/m ³	OSHA P0
		STEL	200 ppm 950 mg/m ³	OSHA P0
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-Propanone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0 Revision Date: 03/21/2018 SDS Number: 10200000137 Date of last issue: -
Date of first issue: 03/21/2018

Benzene, dimethyl-	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1,500 mg/g	ACGIH BEI
2-Propanone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Benzene, dimethyl-	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1,500 mg/g	ACGIH BEI

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection
Material : Solvent-resistant gloves (butyl-rubber)

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Tightly fitting safety goggles
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : aerosol
- Colour : No data available
- Odour : characteristic
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : -44 °C
- Flash point : -97 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

flammability limit	
Vapour pressure	: No data available
Relative density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Components:**Propane:**

Acute inhalation toxicity	: LC50 (Rat): 800000 ppm Exposure time: 0.25 h
---------------------------	---

Acetic acid ethyl ester:

Acute oral toxicity	: (Rat): 5,620 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 56 mg/l Exposure time: 4 h Test atmosphere: vapour

Acute dermal toxicity	: LD50 (Rabbit): > 18,000 mg/kg
-----------------------	---------------------------------

2-Propanone:

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

Acute oral toxicity : LD50 (Rabbit): 4,700 - 5,800 mg/kg
(Mouse): 3,000 mg/kg
(Rat): 9,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Benzene, dimethyl-:

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg
Method: Converted acute toxicity point estimate

Solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 (Rat): 3,492 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

Naphtha (petroleum), hydrotreated heavy:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): Test atmosphere: vapour
Remarks: An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**2-Propanone:**

Remarks: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000000137 Date of last issue: -
Date of first issue: 03/21/2018

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**2-Propanone:**

Remarks: Severe eye irritation

Benzene, dimethyl-:

Result: Eye irritation

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Benzene, dimethyl-:**

Assessment: Harmful in contact with skin or if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Sample Aluminium Spray 400 ml 17-09021 400 mlVersion
1.0Revision Date:
03/21/2018SDS Number:
102000000137Date of last issue: -
Date of first issue: 03/21/2018

STOT - single exposure

May cause drowsiness or dizziness.

Components:**Benzene, dimethyl-:**

Assessment: May cause respiratory irritation.

Acetic acid, butyl ester:

Assessment: May cause drowsiness or dizziness.

Solvent naphtha (petroleum), light arom.:

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:**Benzene, dimethyl-:**

Assessment: May cause damage to organs through prolonged or repeated exposure.

Components:**Benzene, dimethyl-:**Repeated dose toxicity - : Harmful in contact with skin or if inhaled.
Assessment**Aspiration toxicity**

Not classified based on available information.

Components:**Benzene, dimethyl-:**

May be fatal if swallowed and enters airways.

Solvent naphtha (petroleum), light arom.:

May be fatal if swallowed and enters airways.

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000000137 Date of last issue: -
Date of first issue: 03/21/2018

Further information**Components:****Naphtha (petroleum), hydrotreated heavy:**

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Acetic acid ethyl ester:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 717 mg/l

2-Propanone:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21,600 mg/l

Solvent naphtha (petroleum), light arom.:**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Other adverse effects

No data available

Components:**Naphtha (petroleum), hydrotreated heavy:**

Additional ecological information : No data available

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.
-

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

- UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

- UN number : UN 1950
Proper shipping name : AEROSOLS
- Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0 Revision Date: 03/21/2018 SDS Number: 102000000137 Date of last issue: -
Date of first issue: 03/21/2018

49 CFR

UN/ID/NA number : UN 1950
 Proper shipping name : Aerosols

 Class : 2.1
 Packing group : Not assigned by regulation
 Labels : FLAMMABLE GAS
 ERG Code : 126
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)
Benzene, dimethyl-	1330-20-7	100

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Serious eye damage or eye irritation
 Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Benzene, dimethyl-	1330-20-7	>= 5 - < 10 %
Aluminum	7429-90-5	>= 5 - < 10 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Benzene, dimethyl-	1330-20-7	8.6614 %
--------------------	-----------	----------

The following chemical(s) are listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F):

Butane	106-97-8	18.67 %
--------	----------	---------

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

Propane	74-98-6	18.66 %
The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489):		
Acetic acid ethyl ester	141-78-6	15 %
2-Propanone	67-64-1	13.33 %
Benzene, dimethyl-	1330-20-7	8.6614 %
Acetic acid, butyl ester	123-86-4	4.9606 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Benzene, dimethyl-	1330-20-7	8.6614 %
Acetic acid, butyl ester	123-86-4	4.9606 %
Benzene, ethyl-	100-41-4	0.0557 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Benzene, dimethyl-	1330-20-7	8.6614 %
Acetic acid, butyl ester	123-86-4	4.9606 %
Benzene, ethyl-	100-41-4	0.0557 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

US State Regulations

Massachusetts Right To Know

Butane	106-97-8
Propane	74-98-6
Acetic acid ethyl ester	141-78-6
2-Propanone	67-64-1
Benzene, dimethyl-	1330-20-7
Aluminum	7429-90-5
Acetic acid, butyl ester	123-86-4
Solvent naphtha (petroleum), light arom.	64742-95-6

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

Pennsylvania Right To Know

Butane	106-97-8
Propane	74-98-6
Acetic acid ethyl ester	141-78-6
2-Propanone	67-64-1
Benzene, dimethyl-	1330-20-7
Aluminum	7429-90-5
	Not Assigned
Acetic acid, butyl ester	123-86-4
Solvent naphtha (petroleum), light arom.	64742-95-6
Naphtha (petroleum), hydrotreated heavy	64742-48-9
1-Butanol	71-36-3
Benzene, ethyl-	100-41-4
2-Propanol	67-63-0

California Prop. 65



WARNING: This product can expose you to chemicals including lead and cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



WARNING: This product can expose you to chemicals including Benzene, ethyl-, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Butane	106-97-8
Acetic acid ethyl ester	141-78-6
2-Propanone	67-64-1

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version 1.0	Revision Date: 03/21/2018	SDS Number: 102000000137	Date of last issue: - Date of first issue: 03/21/2018
----------------	------------------------------	-----------------------------	--

Benzene, dimethyl- 1330-20-7

Aluminum 7429-90-5

Acetic acid, butyl ester 123-86-4

California Permissible Exposure Limits for Chemical Contaminants

Butane 106-97-8

Propane 74-98-6

Acetic acid ethyl ester 141-78-6

2-Propanone 67-64-1

Benzene, dimethyl- 1330-20-7

Aluminum 7429-90-5

Acetic acid, butyl ester 123-86-4

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not on the Canadian DSL nor NDSL.

TSCA : Not On TSCA Inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
 NIOSH REL : USA. NIOSH Recommended Exposure Limits
 OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
 OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
 ACGIH / TWA : 8-hour, time-weighted average
 ACGIH / STEL : Short-term exposure limit
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
 NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
 OSHA P0 / TWA : 8-hour time weighted average
 OSHA P0 / STEL : Short-term exposure limit
 OSHA Z-1 / TWA : 8-hour time weighted average
 OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -

Sample Aluminium Spray 400 ml 17-09021 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000137	Date of first issue: 03/21/2018

Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/21/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN