

**Date of impression** 25.01.2016/11:10:47  
**page/of** 1/1

**edition** 23.03.2015

**material denomination** **STAPA UCP 130 Aluminium Paste**

**material-no.** 021370

**material description** Encapsulated, extreme chemical resistant Aluminium paste for solvent-borne and water-borne paint systems

Specific gravity app. 1,0 kg/l  
 Aluminium paste in isopropyl alcohol incl. additives.  
 Pigmentcomposition :  
 Aluminium app. 80 %  
 Coatings app. 20 %

<b>insp. characteristic</b>	<b>specification</b>	<b>unit</b>
T100004 pigment content / non volatile	33,0 - 37,0	%
T100004 volatile content	63,0 - 67,0	%
T100005 sieving < 40 µm	99,0 - 100,0	%
T100009 D 10	8,0 - 12,0	µm
T100009 D 50	12,0 - 17,0	µm
T100009 D 90	19,0 - 27,0	µm
T100290 visual Inspection	O.K.	

total shelf life in month: 12

EC-safety data sheet-no. 021370ZZ5

The Data on this technical information sheet correspond with the current status of our knowledge and experience.  
 The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.  
 We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

**ECKART GmbH**  
**quality control department**

This document has been printed automatically and will not be signed.