

Technical Data

Metal Primer grey

For indoor and outdoor applications

Technical details SPRAY		Advice for handling	
Colour shade	light grey	Application temperature	approx. 18 - 25 °C
Degree of gloss	mat	Surface preparation	clean, dry, free of grease and rust
Base of binder	alkyd resin	Primer	--
Base of pigment	zinc phosphate / white pigment	Touch dry at +20 °C	after approx. 15 min.
Temperature stability	up to approx. +200 °C	Fully hardened	after approx. 4 - 6 hours
Flash point/aerosol paint	below +21 °C	Recoat	after approx. 6 hours
Danger class	acc. to TRG 300		
Marking	Danger! Please see MSDS		
Propellant agent	propane / butane	Category "B/e" specialties	VOC max. 840 g/l (2007).
Storage	cool and dry; acc. to TRG 300	VOC directive: 2004/42 EG	< 840 g/l VOC

Test results

Cross cut test DIN 53151 / ISO 2409	GT 0-2
Salt spray test ISO 9227	150 hours
Humidity test DIN 50017	--
T-bend test 5 mm	<input checked="" type="checkbox"/>
UV-durable	--
Minimum Film thickness	approx. 50 µm

Product features

Good corrosion protection
 Weather resistant
 Very good adhesion
 Flexible Lacquer
 Quick drying
 Short-term resistance to oil and petrol

Applications

Suitable for technical applications e.g. pipes, steel pipe structures, automobile/trailer parts, bicycles and motorcycles, automobile rims, wrought iron.

Suitable for metal, wood, cardboard and most of the common plastics.

Store in a dry place and at room temperature (15-25°C), minimum durability two years.

"The Data on this technical information sheet correspond with the current status of our knowledge and experience. The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights. We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process".

For more information and samples, please contact:

ECKART GmbH / Güntersthal 4 / 91235 Hartenstein / Germany
 Tel.: ++ 49-(0)9152-77 0 / Fax: ++49-(0)9152-77 4435 / E-mail: info.eckart@altana.com